

REPORT ON ELECTRICAL EQUIPMENT.

(OTHER THAN FOR THE PROPULSION OF THE VESSEL)

AUG 12 1939

Received at London Office

Date of writing Report 10-8-1939 When handed in at Local Office 11-8-1939 Port of Aberdeen

No. in Survey held at Aberdeen Date, First Survey 10th July Last Survey 1st August 1939
 Reg. Book. on the Non propelling dredger "FOREMOST CLAN" (Number of Visits 4)

Tons { Gross 314.46
 Net 190.04

Built at Aberdeen By whom built A. Hall & Co. Ltd Yard No. 664 When built 1939.

Owners James Gowing & Dredging Co. Ltd Port belonging to London

Electric Light Installation fitted by C. and H. Hamilton (Aberdeen) Ltd Contract No. When fitted 1939.

Is the Vessel fitted for carrying Petroleum in bulk No.

System of Distribution Two wires

Pressure of supply for Lighting 110 volts, Heating ✓ volts, Power ✓ volts.

Direct or Alternating Current, Lighting Direct current Power ✓

If alternating current system, state frequency of periods per second ✓

Has the Automatic Governor been tested and found efficient when the whole load is suddenly thrown on or off Yes

Generators, do they comply with the requirements regarding temperature rise Yes, are they compound wound Yes

are they over compounded 5 per cent. Yes, if not compound wound state distance between each generator ✓

Where more than one generator is fitted are they arranged to run in parallel ✓, is an adjustable regulating resistance fitted in

series with each shunt field Yes Have certificates of test results for machines under 100 kw. been submitted and

approved Yes Have machines over 100 kw. been inspected by the Surveyors during manufacture and testing ✓

Have certificates for generators under 100 kw. been supplied and approved Yes

Are all terminals accessible, clearly marked, and furnished with sockets Yes, are they so spaced or shielded that they cannot be accidentally earthed,

short circuited, or touched Yes Are the lubricating arrangements of the generators as per Rule Yes.

Position of Generators Forward end of Engine room, on starting platform, is the ventilation

in way of the generators satisfactory Yes are they clear of all inflammable material Yes if situated near unprotected

woodwork or other combustible material, state distance of same horizontally from or vertically above the generators. ✓ and ✓

are the generators protected from mechanical injury and damage from water, steam or oil Yes, are their axes of rotation fore and aft No

Earthing, are the bedplates and frames of the generating plant efficiently earthed Yes are the prime movers and their respective generators

in metallic contact Yes Main Switch Boards, where placed Engine room forward bulkhead

If the generators and main switchboard are not placed in the same compartment, is each generator provided with

a fuse on each insulated pole as near as possible to the terminals of the generator, additional to that provided on the main switchboard ✓

Switchboards, are they placed in accessible positions, free from inflammable gases and acid fumes Yes, are they protected from mechanical

injury and damage from water, steam or oil Yes, if situated near unprotected woodwork or other combustible material, state distance of same

horizontally from or vertically above the switchboards. ✓ and ✓, are they constructed wholly of durable, non-ignitable non-absorbent

materials Yes, is all insulation of high dielectric strength and of permanently high insulation resistance Yes.

is it of an approved type Yes, if semi-insulating material is used, are all conducting parts insulated from the slab with mica or micanite or other

non-hygroscopic insulating material, and the slab similarly insulated from its framework. ✓, is the non-hygroscopic insulating material of an approved

type ✓, and is the frame effectively earthed Yes. Are the fittings as per Rule regarding:— spacing or shielding of live parts

Yes, accessibility of all parts Yes, absence of fuses on back of board Yes, temperature rise of

omnibus bars Yes, individual fuses to voltmeter, pilot or earth lamp Yes, are moving parts of switches alive in the

"off" position No are all screws and nuts securing connections effectively locked Yes are any fuses fitted on the live side of

switches Yes. Main Switchgear, description of switchgear for each generator and each outgoing circuit, and arrangement of equalizer switches

Double pole, double throw to Generator Single pole double throw to outgoing circuits.

Are turbine driven generators fitted with emergency trip switch as per rule ✓ Are cupboards or compartments containing switchboards composed of


fire-resisting material or lined with approved material ✓ Instruments on main switchboard One ammeters One

voltage meters ✓ synchronising device for paralleling purposes. For compound machines is the ammeter connected on the opposite pole to equaliser connection

✓ Earth Testing, state what means are provided at the main switchboard for indicating the state of the insulation of the system

Earth lamp. Switches, Circuit Breakers and Fusible Cut-outs,

do these comply with the requirements of the Rules. Yes are the fusible cutouts of an approved type Yes have the reversed



© 2020

Lloyd's Register Foundation

current protection devices been tested under working conditions. ☒ are all fuses labelled as per rule yes

Joint Boxes, Section and Distribution Boards, is the construction, protection, insulation, material, and position of these as per rule yes

Cables: Single, twin, concentric, or multicore twin are the cables insulated and protected as per Tables IV, V, X, XI, XII or XIII of the Rules yes

If the cables are insulated otherwise than as per Rule, are they of an approved type ☒ **Fall of Pressure,** state maximum between bus bars and any point of the installation under maximum load 25 volts **Cable Sockets,** are the ends of all cables having a sectional area of 0.04 square inch and above provided with soldering sockets yes **Paper Insulated and Varnished Cambric Insulated Cables.**

If conductors are paper or varnished cambric insulated, is the dielectric at the exposed ends of the conductor protected from moisture by being suitably sealed with insulating compound ☒ or waterproof insulating tape ☒ **Cable Runs,** are the cables fixed as far as possible in accessible positions not exposed to drip or accumulation of water or oil, or to high temperature from boilers, steam pipes, uptakes or other hot objects, or to avoidable risk of mechanical damage yes are cables laid under machines or floorplates No if so, are they adequately protected ☒

Are cables in machinery spaces, galleys, laundries, bathrooms and lavatories lead covered or run in conduit L.C. & A.

Support and Protection of Cables, state how the cables are supported and protected clipped to beams etc & armoured

If cables are run in wood casings, are the casings and caps secured by screws ☒, are the cap screws of brass ☒, are the cables run in separate grooves ☒ If armoured and lead covered cables are secured by metal clips, are the clips spaced as per Table VIII yes

Refrigerated Chambers, are the cables and fittings in accordance with the special requirements ☒

Joints in Cables, state if any, and how made, insulated, and protected water tight joint boxes with porcelain insulators

Watertight Glands and Deck Tubes, are all cables passing through decks and watertight bulkheads provided with deck tubes or watertight glands yes **Bushes in Beams and Non-watertight Partitions,** where unarmoured cables pass through beams and non-watertight partitions, are the holes efficiently bushed yes state the material of which the bushes are made lead

Earthing Connections, state what earthing connections are fitted and their respective sectional areas Lead covering earthed by 7/0244 to ship frame. are their connections made as per Rule yes

Alternative Lighting, are the groups of lights in the propelling machinery space arranged as per Rule yes **Emergency Supply,** state position and method of control of the emergency supply and how the generator is driven ☒

Navigation Lamps, are these separately wired None controlled by separate switch and separate fuses ☒ are the fuses double pole ☒ are the switches and fuses grouped in a position accessible only to the officers on watch ☒ has each navigation lamp an automatic indicator as per Rule ☒ **Secondary Batteries,** are they constructed and fitted as per Rule ☒ are they ventilated as per Rule ☒

Fittings, are all fittings on weather decks, in stokeholds and engine rooms and wherever exposed to drip or condensed moisture, watertight yes are any fittings placed in spaces in which goods are liable to be stacked in close proximity to them; if so, how are they protected ☒ are any fittings placed in spaces where inflammable or explosive dust or gases are liable to be present, if so, how are they protected ☒ how are the cables led ☒ where are the controlling switches situated ☒ are all fittings suitably ventilated yes are all switches and lampholders constructed wholly of non-ignitable, non-absorbent materials yes

Heating and Cooking Appliances, are they constructed and fitted as per Rule ☒ are air heaters constructed and fitted as per Rule ☒

Searchlight Lamps, No. of ☒ whether fixed or portable ☒ are their fittings as per Rule ☒

Motors, are their working parts readily accessible ☒ are the coils self-contained and readily removable for replacement ☒ are the brushes, brush holders, terminals and lubricating arrangements as per Rule ☒ are the motors placed in well-ventilated compartments in which inflammable gases cannot accumulate and clear of all inflammable material ☒ are they protected from mechanical injury and damage from water, steam or oil ☒ are their axes of rotation fore and aft ☒ if situated near unprotected woodwork or other combustible material, are the motors of the totally enclosed, pipe ventilated, forced draught, drip or flame proof type ☒ if not of this type, state distance of the combustible material horizontally or vertically above the motors ☒ and ☒ have machines of over 100 BHP been inspected by the Surveyors during manufacture and testing ☒ have certificates for all motors for essential services been supplied and approved ☒ **Control Gear and Resistances,** are the generator field and motor speed regulators, starters and controllers constructed and fitted as per Rule yes **Lightning Conductors,** where lightning conductors are required, are these fitted as per Rule None **Ships carrying Oil having a Flash Point less than 150° F.** Have the special requirements of the Rules been complied with regarding switches, joint boxes, section and distribution boards, protection of cables, method of distribution, lead of cables, lights and fittings ☒ are all fuses of the filled cartridge type ☒ are they of an approved type ☒ If portable lamps for use in dangerous spaces are supplied, are they of a self-contained, battery-fed flameproof type approved for use in dangerous spaces ☒ **Spare Gear,** if the vessel is for open sea service have spares been supplied as per Rule ☒ are they suitably stored in dry situations ☒

PARTICULARS OF GENERATING PLANT.									
DESCRIPTION OF GENERATOR.	No. of	RATED AT				DRIVEN BY	WHERE DRIVEN BY AN INTERNAL COMBUSTION ENGINE.		
		Kilowatts.	Volts.	Ampères.	Revs. per Min.		Fuel Used.	Flash Point of Fuel.	
MAIN	One	3	110	243	450	Steam engine			
AUXILIARY									
EMERGENCY									
ROTARY TRANSFORMER									

GENERATOR, LIGHTING AND HEATING CONDUCTORS.									
DESCRIPTION.	CONDUCTORS.		COMPOSITION OF STRAND.		TOTAL MAXIMUM CURRENT.		Approximate Length (Lead and Return) Feet.	Insulated with	HOW PROTECTED.
	No. per Pole.	Total Nominal Area per Pole Sq. Ins.	No.	Diameter.	In Circuit.	Rule.			
MAIN GENERATOR	1	0100	4	044	23	311	22.0	V.I.R.	L.C. & A. in tube.
EQUALISER CONNECTIONS									
AUXILIARY GENERATOR									
EMERGENCY GENERATOR									
ROTARY TRANSFORMER									
ENGINE ROOM									
BOILER ROOM									
AUXILIARY SWITCHBOARDS									
ENG. ROOM FUSE BOARD	8	0040	7	026	13.25	24.1	9.0	V.I.R.	L.C. & A.
ACCOMMODATION									
PORT FUSE BOARD	3	0030	3	036	4.3	12	46.0	V.I.R.	L.C. & A.
STAR	3	0030	3	036	4.4	12	46.0	V.I.R.	L.C. & A.
WIRELESS									
SEARCHLIGHT									
MASTHEAD LIGHT									
SIDE LIGHTS									
COMPASS LIGHTS									
CARGO LIGHTS	2	0020	3	029	4.5	4.8	200.0	V.I.R.	L.C. & A.
HEATERS									

MOTOR CONDUCTORS.										
DESCRIPTION.	No. of Motors.	CONDUCTORS.		COMPOSITION OF STRAND.		TOTAL MAXIMUM CURRENT.		Approximate Length (Lead and Return) Feet.	Insulated with	HOW PROTECTED.
		No. Per Pole.	Total Nominal Area per Pole Sq. Ins.	No.	Diameter.	In Circuit.	Rule.			
BALLAST PUMP										
MAIN BILGE LINE PUMPS										
GENERAL SERVICE PUMP										
EMERGENCY BILGE PUMP										
SANITARY PUMP										
CIRC. SEA WATER PUMPS										
CIRC. FRESH WATER PUMPS										
AIR COMPRESSOR										
FRESH WATER PUMP										
ENGINE TURNING GEAR										
ENGINE REVERSING GEAR										
LUBRICATING OIL PUMPS										
OIL FUEL TRANSFER PUMP										
WINDLASS										
WINCHES, FORWARD										
WINCHES, AFT										
STEERING GEAR—										
(a) MOTOR GENERATOR										
(b) MAIN MOTOR										
WORKSHOP MOTOR										
VENTILATING FANS										

The Electrical Equipment is installed in accordance with the approved plans.

All Insulated Conductors are guaranteed to withstand the immersion and resistance tests specified in the Rules.

The foregoing is a correct description.

CLAUD HAMILTON (ABERDEEN) LTD.
ELECTRICAL ENGINEERS
254 UNION STREET, ABERDEEN

J. Walker Electrical Engineers.

Date *10th August 1939*

COMPASSES.

Minimum distance between electric generators or motors and standard compass

Minimum distance between electric generators or motors and steering compass

The nearest cables to the compasses are as follows:—

A cable carrying Ampères feet from standard compass feet from steering compass.

A cable carrying Ampères feet from standard compass feet from steering compass.

A cable carrying Ampères feet from standard compass feet from steering compass.

Have the compasses been adjusted with and without the electric installation at work at full power

Has the effect of switching on and off circuits, motors and other electro-magnetic apparatus within the vicinity of the compasses been noted

The maximum deviation due to electric currents was found to be degrees on course in the case of the standard

compass, and degrees on course in the case of the steering compass.

Builder's Signature.

Date

Is this installation a duplicate of a previous case *NO* If so, state name of vessel ☒

General Remarks (State quality of workmanship, opinions as to class, etc.) *The electrical installation of*

this vessel has been fitted on board under special survey. The materials and workmanship are good. It has been tried under working conditions & found good

Noted
L.Y.
16/8/39

Total Capacity of Generators *3* Kilowatts.

The amount of Fee ... £ *3* : - - : When applied for, 19.....

Travelling Expenses (if any) £ : : *11-9-39* 15/9

J. A. May
Surveyor to Lloyd's Register of Shipping.

Committee's Minute

Assigned

FRI 18 AUG 1939

See F.E. r/t



© 2020

Lloyd's Register
Foundation