


FLY to "CITY of CAPE TOWN" Lix Fbd. Rpt. N^o. 109456.

PARTICULARS OF PROTECTION TO OPENINGS, ETC.

HATCHWAYS ON FREEBOARD AND SUPERSTRUCTURE DECKS									
<i>Inside combined fore and bridge</i> <i>Inside poop.</i>									
Description of Hatchway	No. 1	No. 2	No. 3	No. 4	Deep Tank	No. 6	
Dimensions of Hatchway	20'-3" x 14'-2 1/4"	44'-9" x 18'-2 1/4"	17'-6" x 16'-3 1/4"	12'-2 1/2" x 14'-8 1/4"	12'-6" x 18'-2 1/4"	17'-6" x 18'-2 1/4"	
COAMINGS	Height above Deck	...	9"						
	Thickness	{ Sides	9 x 3 1/2" x 40 B.P.	As No. 1	As No. 1	As No. 1	As No. 1	As No. 1	
		{ Ends	7 x 3 1/2" x 40" angle						
	Stiffeners	and No. 17 Twp. plating						
	Brackets, Stays	...							
HATCH BEAMS	Number	...	3	8	3	2	2	3	
	Spacing	...	5'-0 1/4"	4'-11 3/4"	4'-4 1/2"	4'-1"	4'-2"	4'-4 1/2"	
	Scantling and Sketch	...							
		Plate	12" x 32"	16" x 36"	20" x 38"	12" x 32"	15" x 34"	15" x 34"	
		4 Angles	3 x 3 x 4 1/2"	4 x 3 x 4 1/2"	4 x 3 x 4 1/2"	3 x 3 x 4 1/2"	4 x 3 x 4 1/2"	4 x 3 x 4 1/2"	
	Bearing Surface	...	4"	4"	4"	4"	4"	4"	
FORE AND AFTERS	Number	...							
	Spacing	...							
	Unsupported Lengths	...							
	Scantling* and Sketch	...		none	fitted.				
	Bearing Surface	...							
HATCH COVERS	Material	...	B.P.						
	Thickness	...	2 1/2"	As No. 1	As No. 1	As No. 1	As No. 1	As No. 1	
	How fitted	...	1st						
	Bearing Surface	...	3"						
Spacing of Cleats	24"	As No. 1	As No. 1	As No. 1	As No. 1	As No. 1	
Number of Tarpaulins	1						
<p>*Are wood fore and afters steel shod at all bearing surfaces? <input checked="" type="checkbox"/></p> <p>Are battens and wedges efficient and in good condition? <input checked="" type="checkbox"/></p> <p>Are tarpaulins in good condition and in accordance with rule requirements? <input checked="" type="checkbox"/></p> <p>Are lashings provided in accordance with rule requirements? <input checked="" type="checkbox"/></p>									

© 2020



Lloyd's Register
Foundation

004866 • 004872 • 0085