


DIMENSIONS:- 200'-0 B.P. x 33'-0 MLD. x 13'-6 MLD. to UPPER DECK.  
TO MEET REQUIREMENTS OF CLASS \*

RUDDER:- AREA OF RUDDER BELOW 200 LOAD LINE MEASURED BETWEEN CENTRE  
LINE OF PINTLES AND BACK EDGE OF RUDDER 44.31 SQUARE FEET.  
CENTRE OF GRAVITY OF IMMERSED RUDDER AREA FROM CR LINE OF  
PINTLES = 217 FEET. SPEED NOT TO EXCEED 10 KNOTS.  
RIVET HOLES TO BE COUNTER SUNK.  
RUDDER TO BE RIVET HOLE BORED.  
RUDDER ARM TO BE SHUNK ON AND KEYED

STERNPOST:- TO BE FORGED

STERNPOST TO BE RIVET HOLE BORED WITH HOLES SPACED AS SHOWN  
3089 TO BE RIVET HOLE BORED AS SHOWN.  
SIZE OF RIVET HOLES MUST NOT BE LESS THAN SHOWN  
ANY EXCESS ON GIVEN SCANTLING WILL NOT BE PAID FOR





Lithgow's L<sup>td</sup>  
751  
Sternpost & rudder  
By

DESTROY  
1973

LITHGOWS LTD

N<sup>o</sup> 751

STERNPOST & RUDDER

3-8-22

SS. ULMARRA

5

004982-004987-0131



© 2020

Lloyd's Register  
Foundation