

Norderwerft Koser V. Meyer, Hamburg.

2,500.10.47.

DCW

Received by Chief Ship Surveyor

Received from Chief Ship Surveyor

VESSEL'S NAME Stm. Trl. 'SLETNES' ex "P.V. 6111" REPORT Gms. No. 23351

The remarks of the Chief Ship Surveyor are desired on this case for the consideration of the Classing Committee.

("The endorsement to contain a succinct summary of any repairs that have been required and to show the cause or causes of such repairs, and also to bring out clearly any exceptional features in connection with the case, so that the Classing Committee may have all the salient points presented in the endorsement."—Extract from Sub-Committee's Report, 24/5/92.)

This vessel is an ex German Trawler used for war purposes and built in 1940.

She has been purchased by British Owners for reconversion for fishing purposes.

Classification with this Society is desired.

The scantlings and arrangements have been examined in this Office and found, with certain amendments, to be suitable for the class 100A—"Steam Trawler".

The GRIMSBY Surveyors in a First Entry Report and Rpt. 8, report 10.48, the vessel examined in drydock and afloat, and the scantlings and arrangements verified and the requirements of a PERIODICAL SPECIAL SURVEY FOR CLASSIFICATION complied with.

The wartime fittings removed and the necessary alterations for fishing purposes carried out in accordance with the approved plans.

The existing coal bunkers dispensed with, and oil fuel bunkers constructed in lieu, in accordance with the approved plans.

Repairs and renewals effected to a number of shell plates (p & s), and minor items.

The equipment of anchors and chain cables on board now replaced by equipment to the Rule requirements, and tested by the Society's Surveyors, and IT IS SUBMITTED the figure '1' and the Notation "Lloyd's A & CP" be assigned.

IT IS FURTHER SUBMITTED the vessel is eligible to be classed 100A "Stm Trawler" and to have record of docking 8.48 and the Notation "S.S. Gms.- 10.48".

100A "Stm Trawler". "Fitted for oil fuel 10,48 F.P. above 150°F." 8.48 Gms.

S.S. Gms.- 10.48.

Classed 10.48.

Cell DBa 5', 4t. f 50'. 32t. side tanks aft 20t. DTf 24'. 30t.

BK 7". 3 BH. pt Cem. Lloyd's A & CP.

F 31'

O.L. 190'

E.S.D.

"Radar"

"v"



© 2020

Lloyd's Register  
Foundation

005194-005209-0011