

For Scantling Purpose only

Lloyd's Register of Shipping.  
SURVEYS FOR FREEBOARD.  
(COMPUTATION FOR STEAMER, SAILING SHIP, TANKER.)

Index. No. \_\_\_\_\_  
(For London Office only).

Ship's Name <i>Vickers 948/9</i> <i>for Elder Dempster</i>	Official Number	Nationality and Port of Registry	Gross Tonnage	Date of Build	Port of Survey
Moulded Dimensions: Length <i>446</i> Breadth <i>66</i> Depth <i>36-6</i> <i>28-0</i>	Moulded displacement at moulded draught = 85 per cent. of moulded depth _____ tons				Date of Survey <i>4-4-45</i>
Coefficient of fineness for use with Tables <i>.74 assumed</i>					Surveyor's Signature _____
					Particulars of Classification <i>100A1</i> <i>with 1st. Certificate</i>

Depth for Freeboard (D). Moulded depth ... <i>Vertical</i> ... <i>29.25</i> ✓ Stringer plate ... .. <i>.04</i> Sheathing on exposed deck $T \left( \frac{L-S}{L} \right) =$ Depth for Freeboard (D) = <i>29.29</i> ✓	Depth correction. (a) Where D is greater than Table depth (D-Table depth) R =  (b) Where D is less than Table depth (if allowed) (Table depth-D) R = <i>(29.73-29.29) x 3 = -13.2</i> ✓ <i>44</i> ✓ If restricted by superstructures	Round of Beam correction. Moulded Breadth (B) Standard Round of Beam = $\frac{B \times 12}{50} =$ Ship's Round of Beam = <i>Standard</i> Difference Restricted to Correction = $\frac{\text{Diff}^a}{4} \times \left( 1 - \frac{S_1}{L} \right) =$ <i>Nil</i> ✓
---	---	---

DEDUCTION FOR SUPERSTRUCTURES.

	Mean Covered Length (S)	Equivalent Enclosed Length (S <sub>1</sub> )	Height	Height Correction	Effective Length (E)	
Poop enclosed ... ..						Standard Height of Superstructure _____
„ overhang ... ..						„ „ R.Q.D. _____
R.Q.D. enclosed ... ..						Deduction for complete superstructure _____
„ overhang ... ..						Percentage covered $\frac{S}{L} =$
Bridge enclosed ... ..						„ „ $\frac{S_1}{L} =$
„ overhang aft ... ..						„ „ $\frac{E}{L} =$
„ overhang forward ... ..						Percentage from Table, Line A. (corrected for absence of forecastle (if required))
F'cle enclosed ... ..						Percentage from Table, Line B. (corrected for absence of forecastle (if required))
„ overhang ... ..						Interpolation for bridge less than .2L (if required)
Trunk aft ... ..						Deduction = <i>-42.00</i> ✓
„ forward ... ..						
Tonnage opening aft ... ..						
„ „ forward ... ..						
Total ... ..						

SHEER CORRECTION.

Station	Standard Ordinate	S M	Product	Actual Ordinate	Effective Ordinate	S M	Product	
A.P. ... ..		1				1		Mean actual sheer aft =
$\frac{1}{8}$ L from A.P. ... ..		4				4		Mean standard sheer aft =
$\frac{2}{8}$ L „ ... ..		2				2		Mean actual sheer forward =
Amidships ... ..		4				4		Mean standard sheer forward =
$\frac{2}{8}$ L from F.P. ... ..		2				2		Length of enclosed superstructure forward of amidships =
$\frac{1}{8}$ L „ ... ..		4				4		„ „ aft of „ =
F.P. ... ..		1				1		
Total ... ..								

Correction =  $\frac{\text{Difference between sums of products}}{18} \left( \frac{75-S}{2L} \right) =$   
If limited on account of midship superstructure.

Mean actual sheer aft =  
Mean standard sheer aft =  
Mean actual sheer forward =  
Mean standard sheer forward =  
Length of enclosed superstructure forward of amidships =  
„ „ aft of „ =  
If limited to maximum allowance of  $1\frac{1}{2}$  ins. per 100 ft.

Deduction for Tropical Freeboard. Addition for Winter and Winter North Atlantic Freeboard. Depth to Freeboard Deck = <i>29.29</i> ✓ Summer freeboard = <i>3.86</i> ✓ Moulded draught (d) = <i>25.43</i> ✓ Deduction for Tropical freeboard and addition for Winter freeboard = $\frac{d}{4}$ inches = Addition for Winter North Atlantic Freeboard (if required) =	Deduction for Fresh Water. Displacement in salt water at summer load water line $\Delta =$ Tons per inch immersion at summer load water line $T =$ Deduction = $\frac{\Delta}{40T}$ inches =	TABULAR FREEBOARD corrected for Flush Deck (if required) Correction for coefficient <i>.74 + .05 = 1.42</i> <i>1.26</i> Depth Correction ... .. Deduction for superstructures ... .. Sheer correction ... .. Round of Beam correction ... .. Correction for Thickness of Deck amidships ... .. Other corrections, scantlings, etc. ... .. Summer Freeboard = <i>46.28</i> ✓	<i>85.86</i> ✓ <i>89.65</i> ✓ <i>1.32</i> ✓ <i>42.00</i> ✓ <i>.05</i> ✓ <i>43.37</i> ✓ <i>-43.37</i> ✓ <i>46.28</i> ✓
--	---	--	--

SUMMER FREEBOARD amidships from Centre of Disc to top of Deck Line, Wood, Steel, Deck:

Tropical Fresh Water Line above Centre of Disc	...	...	Tropical Fresh Water Freeboard	...
Fresh Water Line	„	...	Fresh Water	„
Tropical Line	„	...	Tropical	„
Winter Line	below	„	Winter	„
Winter North Atlantic Line	„	...	Winter North Atlantic	„