





MASTS, SPARS, &c.											
	Material.	Total Length.	DIAMETER AND THICKNESS.				No. of Plates in round.	ANGLES.		RIVETING.	
			At Partners.	Heel.	Hounds.	Head.		Number.	Size.	Scams.	Butts.
LOWER MASTS.....	Fore .....		<i>One sheet seamless mast for signal purposes only.</i>								
	Main .....										
	Mizen.....										
Bowsprit											
Topmasts, Yards and Remainder of <b>Spars</b> ✓											
<b>Rigging,</b> Material and Size, <b>Shrouds</b> ✓ <b>Stays</b> ✓											
<b>Sails.</b> ✓ Suit of ✓ Sails, and the following spare sails ✓											

Character assigned

10001  
wrist pad  
Carrying petal on in back  
Lloyd's 206P  
wrist ~~R~~  
Jpl

+ L.D. 5.24  
F.D. C.L.  
Lilled for oil fuel  
F.D. above 150°F

© 2021  
Lloyd's Re



## PARTICULARS OF LONGITUDINAL FRAMING.

FRAMING.		AMIDSHIPS.			ENDS.			AMIDSHIPS.			ENDS.			RIVETING.			
		In Ship.			In Ship.			Per Rule or as approved.			Per Rule or as approved.			Spacing of Rivets on each side of Transverses and Bulkheads. Inches.	Rivets in Brackets to Bulkheads.		
		Ins.	Ins.	Ins.	Ins.	Ins.	Ins.	Ins.	Ins.	Ins.	Ins.	Ins.	Ins.		Number.	Diameter. Inches.	
Framing* of L, I or C .....																	
Frames in Bridge 'tween Decks ...																	
Frames from Uppermost Continuous Deck																	
Framing from Awning, Shelter or Upper Deck to Margin Plate.																	
No. 1																	
" 2																	
" 3																	
" 4																	
" 5																	
" 6																	
" 7																	
" 8																	
" 9																	
" 10																	
" 11																	
" 12																	
" 13																	
" 14																	
" 15																	
" 16																	
Spacing of Longitudinal Frames																	
Amidships .....																	
At Ends .....																	
Double Bottoms																	
Tank Top Longitudinals																	
Bottom																	
Spacing of Longitudinals																	
Amidships																	
At Ends...																	
Transverses.																	
In Bridge																	
'tween Decks																	
In Awning, Shelter or Upper 'tween Decks.																	
In Hold.																	
Spacing of Transverse Frames .....																	
* State if joggled or liners.																	
Longitudinal Beams of																	
Bridge Deck ...																	
Upper																	
Second																	
Third																	
Transverse Beams.																	

The particulars of framing in peaks (if ordinary), Floors, Centre Girder, Side Girders and Margin Plate and their angle attachments, etc., to be entered in their respective places provided for on the Report Forms.

NOTE:—This slip to be pasted on the fourth page of the Report, and reference to same to be made under framing, etc., on the first page.



GENERAL REMARKS—(continued).

PARTICULARS FOR RECORD in the REGISTER BOOK.—Length of Poop ☒ ft., R.Q.D. *86.6* ft., Bridge ☒ ft., Forecastle *28.5* ft. (in feet and tenths). When the Poop is joined to the B.D., this should be distinctly stated ☒

No. and Material of Decks (if Iron or Steel) and whether wholly or partially covered with wood, and No. of tiers of Beams (this information is to be given as should appear in the Register Book) *One steel Deck.*

Official No. \_\_\_\_\_; Signal Letters \_\_\_\_\_ State if Machinery is fitted aft *Yes*.  
How are the surfaces preserved from oxidation? Inside *Bituminous Ery & Boilerspace cement in peaks & fairhold.* Outside *Paint.*

PARTICULARS OF WATER BALLAST.—State whether the Double bottom is constructed on the cellular system or with girders on floors

PARTICULARS OF WATER BALLAST.			PARTICULARS OF WATER CAPACITY.			
Where Fitted.	Length.	Water Capacity.	Where Fitted.	Length.	Water Capacity.	
	Feet.			Tons.		Feet.
Double bottom, aft,	/	/	Fore peak tank,	<i>Dry tank</i>	<i>28.5</i>	<i>80.5</i>
Double bottom, under Engines and Boilers,			After peak tank,	<i>18</i>	<i>80.5</i>	
Double bottom, if under Engines only,			Deep tank, aft,			
Double bottom, if under Boilers only,			Deep tank, forward,	<i>Oil fuel bunkers as per plan.</i>		
Double bottom, forward,			Other tanks, if fitted,			
Total capacity of double bottom			(If necessary, furnish further information by sketch.)			
			Approved by the Rules <i>See sketch</i>			

\* The wells are not to be included in the lengths of the tanks.

State whether the above have been tested as required by the Rules *Yes* *Light.*

Order for Special Survey No. *659*  
Date *18/12-1923*  
No. *93* in builder's yard.  
DATES of Surveys held while building  
*12-14-20/11; 4-15-17-27/12; 1923; 2-8-18-23-25-28/1; 4-6-8-11-12-14-18-20-21-23/2; 1-4-5-12-18-20-26/3; 2-4-5-8-14-15-16-17-18-19-22-23-24-25-26-29-30/4; 1-2-3/5; 1924;*

Surveyor's Signature



© 2021

Lloyd's Register Foundation