

Rpt. 13.

REPORT ON ELECTRICAL EQUIPMENT.

(OTHER THAN FOR THE PROPULSION OF THE VESSEL)

No. 46855

29 MAY 1936

Date of writing Report

19

When handed in at Local Office

28 MAY 1936

19

Received at London Office

No. in Survey held at

Hull

Port of

HULL

Reg. Book.

18231 on the

Steam Trawler "Lord Middleton"

Date, First Survey

24th April 1936

Last Survey

20th May 1936

(Number of Visits...)

Tons

Gross 464

Net 188

Built at

Selly

By whom built

Cochrane & Sons Ltd.

Yard No.

1155

When built

1936

Owners

Pickering & Haldanes Steam Trawling Co. Ltd.

Port belonging to

Hull

Electric Light Installation fitted by

Pickering & Haldanes' Steam Trawling Co. Ltd.

Contract No.

When fitted

1936

Is the Vessel fitted for carrying Petroleum in bulk

No

System of Distribution

Two wire

Pressure of supply for Lighting

100

volts, Heating

volts, Power

volts.

Direct or Alternating Current, Lighting

Direct

Power

If alternating current system, state frequency of periods per second

✓

Has the Automatic Governor been tested and found efficient when the whole load is suddenly thrown on or off

Yes

Generators, do they comply with the requirements regarding temperature rise

Yes

are they compound wound

Yes

are they over compounded 5 per cent.

Yes

if not compound wound state distance between each generator

✓

Where more than one generator is fitted are they arranged to run in parallel

✓

series with each shunt field

Yes

is an adjustable regulating resistance fitted in

approved

✓

Have certificates of test results for machines under 100 kw. been submitted and

✓

Are all terminals accessible, clearly marked, and furnished with sockets

Yes

are they so spaced or shielded that they cannot be accidentally earthed,

short circuited, or touched

Yes

Are the lubricating arrangements of the generators as per Rule

Yes

Position of Generators

Starboard side of Engine room

in way of the generators satisfactory

Yes

are they clear of all inflammable material

Yes

is the ventilation

woodwork or other combustible material, state distance of same horizontally from or vertically above the generators

✓

and

✓

are the generators protected from mechanical injury and damage from water, steam or oil

Yes

are their axes of rotation fore and aft

Yes

Earthing, are the bedplates and frames of the generating plant efficiently earthed

Yes

are the prime movers and their respective generators

in metallic contact

Yes

Main Switch Boards, where placed

Beside generator

If the generators and main switchboard are not placed in the same compartment, is each generator provided with a fuse on each insulated pole as near as possible to the terminals of the generator, additional to that provided on the main switchboard

✓

Switchboards, are they placed in accessible positions, free from inflammable gases and acid fumes

Yes

injury and damage from water, steam or oil

Yes

if situated near unprotected woodwork or other combustible material, state distance of same horizontally from or vertically above the switchboards

✓

and

✓

materials

Yes

is all insulation of high dielectric strength and of permanently high insulation resistance

Yes

is it of an approved type

Yes

if semi-insulating material is used, are all conducting parts insulated from the slab with mica or micanite or other non-hygroscopic insulating material, and the slab similarly insulated from its framework

Yes

type

Yes

and is the frame effectively earthed

Yes

Are the fittings as per Rule regarding:— spacing or shielding of live parts

omnibus bars

Yes

individual fuses to voltmeter, pilot or earth lamp

Yes

"off" position

No

are all screws and nuts securing connections effectively locked

Yes

switches

No

are any fuses fitted on the live side of

Main Switchgear, description of switchgear for each generator and each outgoing circuit, and arrangement of equalizer switches

Are turbine driven generators fitted with emergency trip switch as per rule

✓

Are cupboards or compartments containing switchboards composed of

fire-resisting material or lined with approved material

Yes

Instruments on main switchboard

one

ammeter

one

voltage

✓

synchronising device for paralleling purposes.

For compound machines is the ammeter connected on the opposite pole to equaliser connection

Earth Testing, state what means are provided at the main switchboard for indicating the state of the insulation of the system

Earth lamps


do these comply with the requirements of the Rules

Yes

are the fusible cutouts of an approved type

Yes

have the reversed



Lloyd's Register Foundation

005377-005386-0129

current protection devices been tested under working conditions ✓

Joint Boxes, Section and Distribution Boards, is the

construction, protection, insulation, material, and position of these as per rule *yes*

Cables: Single, twin, concentric, or multicore *Twin* are the cables insulated and protected as per Tables IV, V, X or XI of the Rules *yes*.

If the cables are insulated otherwise than as per Rule, are they of an approved type ✓

Fall of Pressure, state maximum between bus bars and

any point of the installation under maximum load *nil.*

Cable Sockets, are the ends of all cables having a sectional

area of 0.04 square inch and above provided with soldering sockets *yes*

Paper Insulated and Varnished Cambric Insulated Cables.

If conductors are paper or varnished cambric insulated, is the dielectric at the exposed ends of the conductor protected from moisture by being suitably sealed with

insulating compound ✓, or waterproof insulating tape ✓

Cable Runs, are the cables fixed as far as possible in accessible positions

not exposed to drip or accumulation of water or oil, or to high temperature from boilers, steam pipes, uptakes or other hot objects, or to avoidable risk of mechanical

damage *yes* Are cables in machinery spaces, galleys, laundries, bathrooms and lavatories lead covered or run in conduit *yes*.

Support and Protection of Cables, state how the cables are supported and protected *Armoured cables with G.I. clips*

L.C. cables with brass clips

If cables are run in wood casings, are the casings and caps secured by screws ✓, are the cap screws of brass ✓, are the cables run in

separate grooves ✓. If armoured and lead covered cables are secured by metal clips, are the clips spaced as per Table VIII *yes*.

Refrigerated Chambers, are the cables and fittings in accordance with the special requirements ✓

Joints in Cables, state if any, and how made, insulated, and protected *No joints*.

Watertight Glands and Deck Tubes, are all cables passing through decks and watertight bulkheads provided with deck tubes or watertight glands

yes

Bushes in Beams and Non-watertight Partitions, where unarmoured cables pass through beams and non-watertight partitions, are the

holes efficiently bushed *yes* state the material of which the bushes are made *Lead*.

Earthing Connections, state what earthing connections are fitted and their respective sectional areas ✓

are their connections made as per Rule ✓

Alternative Lighting, are the groups of lights in the propelling machinery space arranged as per Rule *yes*

Emergency Supply, state

position and method of control of the emergency supply and how the generator is driven ✓

Navigation Lamps, are these separately wired *yes*, controlled by separate switch and separate fuses *yes*, are the fuses double pole *yes*

are the switches and fuses grouped in a position accessible only to the officers on watch *yes*

has each navigation lamp an automatic indicator as per Rule ✓. Secondary Batteries, are they constructed and fitted as per Rule ✓

Fittings, are all fittings on weather decks, in stokeholds and engine rooms and wherever exposed to drip or condensed moisture, watertight *yes*

are any fittings placed in spaces in which goods are liable to be stacked in close proximity to them; if so, how are they protected ✓

are any fittings placed in spaces where inflammable or explosive dust or gases are liable to be present, if so, how are they protected ✓

how are the cables led

where are the controlling switches situated ✓

are all fittings suitably ventilated ✓, are all switches and lampholders constructed wholly of non-ignitable, non-absorbent materials ✓

Heating and Cooling Appliances, are they constructed and fitted as per Rule *yes*, are air heaters constructed and fitted as per Rule ✓

Searchlight Lamps, No. of ✓, whether fixed or portable ✓, are their fittings as per Rule ✓

Arc Lamps, other than searchlight lamps, No. of ✓, are their live parts insulated from the frame or case ✓, are their fittings as per Rule ✓

Motors, are their working parts readily accessible ✓, are the coils self-contained and readily removable for replacement ✓

are the brushes, brush holders, terminals and lubricating arrangements as per Rule ✓, are the motors placed in well-ventilated compartments in which

inflammable gases cannot accumulate and clear of all inflammable material ✓, are they protected from mechanical injury and damage from

water, steam or oil ✓ are their axes of rotation fore and aft ✓, if situated near unprotected woodwork or other combustible

material, are the motors of the totally enclosed, pipe ventilated, forced draught, drip or flame proof type ✓

✓, if not of this type, state distance of the combustible material horizontally or vertically above the motors ✓ and ✓

have machines of over 100 BHP been inspected by the Surveyors during manufacture and testing ✓ Control Gear and Resistances, are the generator

field and motor speed regulators, starters and controllers constructed and fitted as per Rule ✓ Lightning Conductors, where lightning conductors

are required, are these fitted as per Rule ✓ Ships carrying Oil having a Flash Point less than 150° F. Have the special requirements of

the Rules been complied with regarding switches, joint boxes, section and distribution boards, protection of cables, method of distribution, lead of cables, lights and

fittings ✓ are all fuses of the filled cartridge type ✓ are they of an approved type ✓

If portable lamps for use in dangerous spaces are supplied, are they of a self-contained, battery-fed type approved by the Home Office ✓

Spare Gear, if the vessel is for open sea service have spares been supplied as per Rule ✓

PARTICULARS OF GENERATING PLANT.

DESCRIPTION OF GENERATOR.	No. of	RATED AT				DRIVEN BY	WHERE DRIVEN BY AN INTERNAL COMBUSTION ENGINE.	
		Kilowatts.	Volts.	Ampères.	Revs. per Min.		Fuel Used.	Flash Point of Fuel.
MAIN ...	1	8	100	80	400	Steam Engine		
AUXILIARY ...								
EMERGENCY ...								
ROTARY TRANSFORMER								

GENERATOR, LIGHTING AND HEATING CONDUCTORS.

DESCRIPTION.	CONDUCTORS.		COMPOSITION OF STRAND.		TOTAL MAXIMUM CURRENT.		Approximate Length. (Lead and Return.) Feet.	Insulated with	HOW PROTECTED.
	No. per Pole.	Total Nominal Area per Pole Sq. Ins.	No.	Diameter.	In Circuit.	Rule.			
MAIN GENERATOR ...	1	1.009	19	.083	80	118	15	V.I.R.	L.C. & Armoured.
EQUALISER CONNECTIONS									
AUXILIARY GENERATOR ...									
EMERGENCY GENERATOR									
ROTARY TRANSFORMER } MOTOR GENERATOR ...									
ENGINE ROOM ...	1	.002	3	.029	5	7.8	40	"	"
BOILER ROOM ...	1	.002	3	.029	5	7.8	80	"	"
AUXILIARY SWITCHBOARDS									
ACCOMMODATION ...	1	.022	7	.064	15	46	70	"	"
WIRELESS ...	1	.007	7	.036	10	24	160	"	"
SEARCHLIGHT ...	1	.002	3	.029	1	5.7	260	"	"
MASTHEAD LIGHT ...	1	.003	28	.012	1	8	30	"	(Cab Type Flex)
SIDE LIGHTS ...	1	.003	28	.012	5	8	20	"	"
POOP LIGHTS ...									
CARGO LIGHTS ...									
ARC LAMPS									
HEATERS (Chartroom)	1	.007	7	.036	10	24	48	"	L.C.

MOTOR CONDUCTORS.

DESCRIPTION.	No. of Motors.	CONDUCTORS.		COMPOSITION OF STRAND.		TOTAL MAXIMUM CURRENT.		Approximate Length. (Lead and Return.) Feet.	Insulated with	HOW PROTECTED.
		No. per Pole.	Total Nominal Area per Pole Sq. Ins.	No.	Diameter.	In Circuit.	Rule.			
BALLAST PUMP ...										
MAIN BILGE LINE PUMPS ...										
GENERAL SERVICE PUMP ...										
EMERGENCY BILGE PUMP ...										
SANITARY PUMP ...										
CIRC. SEA WATER PUMPS ...										
CIRC. FRESH WATER PUMPS ...										
AIR COMPRESSOR ...										
FRESH WATER PUMP ...										
ENGINE TURNING GEAR ...										
ENGINE REVERSING GEAR ...										
LUBRICATING OIL PUMPS ...										
OIL FUEL TRANSFER PUMP ...										
WINDLASS ...										
WINCHES, FORWARD ...										
WINCHES, AFT ...										
STEERING GEAR—										
(a) MOTOR GENERATOR ...										
(b) MAIN MOTOR ...										
WORKSHOP MOTOR ...										
VENTILATING FANS ...										



© 2021

Lloyd's Register Foundation

All Conductors are of annealed copper conforming to British Standard Specification No. 7 (or International Electro-technical Commission Publication No. 28).

The Insulated Conductors are guaranteed to withstand the immersion and resistance tests specified in the Rules.

The foregoing is a correct description

PICKERING & HALDANE'S
STEAM TRAWLING Co. Ltd.

Electrical Engineers.

Date May 16th 1936

J. Clark
DIRECTOR

COMPASSES.

Distance between electric generators or motors and standard compass

80 ft

Distance between electric generators or motors and steering compass

83 ft

The nearest cables to the compasses are as follows:—

A cable carrying .5 Ampères to feet from standard compass 9 to feet from steering compass.

A cable carrying ✓ Ampères ✓ feet from standard compass ✓ feet from steering compass.

A cable carrying ✓ Ampères ✓ feet from standard compass ✓ feet from steering compass.

Have the compasses been adjusted with and without the electric installation at work at full power yes

Has the effect of switching on and off circuits, motors and other electro-magnetic apparatus within the vicinity of the compasses been noted yes

The maximum deviation due to electric currents was found to be no degrees on any course in the case of the standard compass, and no degrees on any course in the case of the steering compass.

FOR GOCHRANE & SONS, LTD.

J. Gochrane
DIRECTOR

Builder's Signature.

Date 23 MAY 1936

Is this installation a duplicate of a previous case No If so, state name of vessel ✓

General Remarks (State quality of workmanship, opinions as to class, etc.)

The electrical installation of this vessel has been fitted on board under Special Survey, tried under working conditions and found satisfactory.

*Notice
L.Y.
6/6/36*

Total Capacity of Generators 8 Kilowatts.

The amount of Fee ... £ 4 : 0 : When applied for, 28 MAY 1936

Travelling Expenses (if any) £ : : When received, 16-7-36

W.B. Edwards
Surveyor to Lloyd's Register of Shipping.

Committee's Minute TUE. 9 JUN 1936 FRI. 17 JUL 1936

Assigned

See other vol JE 46855



© 2021

Lloyd's Register
Foundation