

PARTICULARS RELATING TO ALL STEAM SHIPS EITHER ^{FLUSH} DECKED, OR WITH TOP GALLANT FORECASTLES, SHORT POOPS AND BRIDGE HOUSES DISCONNECTED, ~~OR WITH TOP GALLANT FORECASTLES HAVING LONG POOPS, OR RAISED QUARTER DECKS CONNECTED WITH BRIDGE HOUSES, OR OTHERWISE.~~

Port of Survey *Nagasaki*
Date of Survey *26 June 1916*
Name of Surveyor *E. D. Cushman*

Ship's Name. N ^o 270-71 Mitsubishi D & E. Works Number in Register Book	Port of Registry and Nationality. Jap.	Official Number. -	Gross Tonnage.	Date of Build.	Particulars of Classification. 100 A.I. shells & with freeboard. (passenger) contaminator
---	--	--------------------------	-------------------	----------------	--

Registered dimensions from Ship's Register.	LENGTH. 475	BREADTH. 61' 2"	DEPTH. 38.0	UNDER DECK TONNAGE. 6886 upper 8808 Shelter
Length on LOADLINE.	475	Frame Depth 12" Rule ,,	Ceiling under hatchways only Sheer 5" drop in tank	Peak Tanks } incl Suez.
CORRECTED DIMENSIONS.				

ok. Moulded Depth as measured..... 32'-9" up sk
40'-9" shell-sk.

NOTE. — If the depth is measured when vessel is afloat, the details of measurement should be reported.

Co-efficient of fineness.....

Any modification necessary }
[Para. 4 (a) to (e)]* }

Co-efficient as corrected

CORRECTION FOR LENGTH.

Length of Ship on Loadline.....	
Length in Table	
Difference	
Correction for 10ft., Table A.	Table C.
× Difference divided by 10	(if required.)
If $\frac{6}{10}$ ths length covered divide by 2	

Sheer at	{	Stem..... Sternpost ...	}	$\frac{114}{43} \div 2 = 13.57$...Mean	78.57
Sheer at $\frac{1}{2}$ of the length from	{	Stem Sternpost	}	$\frac{65}{23} \div 2 = 1.43$...Mean	88.57
Gradual mean Sheer						
Standard mean Sheer [Table, Para. 18]						
Difference.....						$\div 4 =$
§ If limited as Para. 18 (f).....						

CORRECTION FOR ROUND OF BEAM.

NOTE. — The round of beam should be reported on the full breadth of vessel at the gunwale.

Breadth at Gunwale amidships.....	
Round of Beam	15 $\frac{1}{4}$
Normal round.....	
Difference	÷ 2 =.....
Proportion of Deck uncovered (Para. 19)	

Rise in Sheer	{	At front of bridge house.....
from amidships		At after end of forecastle
[Para. 18 (e)]		

¶ Fall in Shear } $\div 2 =$
 Para. 18 (*d*) }
 Length uncovered Correction

ALLOWANCE FOR DECK ERECTIONS :—

Freeboard, Table C.....

Correction for Length, if required (Para. 12, 13, and 14)

Freeboard by Table A. corrected for sheer, and for length, }
if required (Para. 12, 13, and 14) }

Difference

Percentage as below

Correction for R. Q. Dk. if engine and boiler openings not covered by bridge house (Para. 11)

Allowance for Deck Erections

	Length.	Length allowed.	Height.
Forecastle.....	44.5'	44.5'	7-6
Bridge House	29.7	29.7	7-6
† Raised Qr. Dk.....			
POOP.....	34.5'	34.5'	7-6

Total

Length of Ship

Corresponding percentage
(Para. 11, 12, 13, or 14)

FREEBOARD recommended amidships from centre of Disc to top of Statutory Deck Line, Wood (Iron) Deck :—

[illegible]

* If the frames, skin planking, or ceiling are of unusual thickness the breadth of vessel to inside of ceiling should be reported if possible.
 † In vessels obtaining an allowance for deck erections under Part. II where the sheer drops abaft amidships the height of the R. Q. D. is to be taken from the level of the top of the mainmast beam.
 § In flush-decked vessels the total standard mean sheer means the sheer measured from the stem and stern-post. In vessels having poops and forecastles, it means the sheer measured at points distant one eighth of the vessel's length from stem and stern-post.

† State dimensions of freeing port area on back of this form.

The Surveyor should state whether the fall in sheer as reported is measured relatively to the straight line of keel or to the water line. If measured relatively to water line the vessel's draft at time of survey, and also the usual load draft forward and aft should be reported.

Do all the Frames extend to the top height in the Poop? Raised Quarter Deck? Bridge House? Forecastle?

To what height do the Reverse Frames extend?

Has the Poop or Raised Quarter Deck an efficient Iron Bulkhead at the fore end?

Give particulars of the means for closing the openings in Bulkhead

Is the Poop or Raised Quarter Deck connected with the Bridge House?

Has the Bridge House an efficient Bulkhead at the fore end?

Give particulars of the means for closing the openings in Bulkhead

What is the thickness of the Bridge Front plating? and Coaming plate?

Give scantlings and spacing of the Stiffeners

Are bracket plates fitted at each end of the Stiffeners?

Are hor'l. brackets fitted connecting Bridge Bulk'd. with Bulwarks?

Has the Bridge House an efficient Iron Bulkhead at the after end?

How are the openings closed?

Is the Forecastle at least as high as the main or top-gallant rail?

Has the Forecastle an efficient Iron or Wood Bulk'd. at after end?

Are the Engine and Boiler openings covered by a Bridge, Poop, Raised Quarter Deck, or enclosed by a Strong Iron or Steel Deckhouse?

If the openings are not so protected are the exposed parts of the Casings efficiently constructed?

Give thickness of plating; scantlings and spacing of Stiffeners

What is the height of the exposed Casings?

Are suitable means provided for closing all openings in them in bad weather?

Are the Weather Deck Hatchways efficiently constructed and at least equal to the requirements of Section 28 of the Rules for 1904-5? Give particulars below:—

Position and Size.											
Item.		Ship.	Rule.	Ship.	Rule.	Ship.	Rule.	Ship.	Rule.	Ship.	Rule.
COAMING.	Height above top of DECK										
	Thickness { Sides.....										
	Ends.....										
SHIFTING BEAMS OR WEB PLATES.	Number										
	Section and Scantlings										
	Material										
* FORE AND AFTERS.	Number										
	Section and Scantlings										
	Material										
HATCHES Thickness											
Remarks.....											

* When the Fore and Afters are of wood the depth should be stated from the underside of the hatches.

(If the sill of the lowest side scuttle will be less than 6 inches above the Indian Summer Load Line if assigned under the tables, state vertical distance from top of deck at side amidships to lower edge of lowest side scuttle.)

The following information is to be given in all Cases of vessels dealt with under Paras. 11, 12 (under 15 feet Moulded depth) and under Shelter Deck Rules.

What is the thickness of the Bridge Sheerstrake? Strake between Main and Bridge Sheerstrakes?


Delete the words { The Crew are, are not, berthed in the bridge house.
that do not apply { The arrangements to enable them to get backwards and forwards from their quarters are, are not satisfactory.

Length of Bulwarks in well

Area of Freeing Ports required by Para. 11 (e) each side of vessel = Sq. ft.

Ft.	Tenths.	Ft.	Tenths.	No.	Freeing Ports (each side of vessel)	=	Sq. ft.
x			x				
x			x				

Total deficiency or excess = Sq. ft.



Show hereon line of Floors or Tank Top with position of any Breaks in same; also height of Peak Tank tops, &c., &c.

State any special features in the construction of the Vessel *Sister vessel to Manila Maru*
Plans in London Office. Request form enclosed.
Vessel to carry passengers.

Owners

Address

Fee £

Received by me



© 2021

Lloyd's Register
Foundation