

num pressure in cylinders 35 kg/cm<sup>2</sup> Diameter of cylinders 550 mm / 21 752 / Length of stroke 600 mm Is there a bearing between each crank

1m,431.

1E

Received by Chief Engineer Surveyor

Received from Chief Engineer Surveyor

VESSEL'S NAME

Senaloi

Rpt.

Gor

No.

9708.

The remarks of the Chief Engineer Surveyor are desired on this case for the consideration of the Classing Committee.

("The endorsement to contain a succinct summary of any repairs that have been required and to show the cause or causes of such repairs, and also to bring out clearly any exceptional features in connection with the case, so that the Classing Committee may have all the salient points presented in the endorsement."—Extract from Sub-Committee's Report, 24/5/92).

Type of Engine

Oil Engines

4. S.C.S.A.

If Boilers fitted with forced draught

Tail Shaft. If fitted with a continuous liner

If fitted with an outside gland of

approved type

Yes

This vessel's machinery appears to have been built in accordance with the Rules and the approved plans, and it is submitted she is eligible to be classed

+ Lmc. 3.34

2.D.B. 150 lb.

Run

6.4.3.1



© 2020

Lloyd's Register  
Foundation

005756-005778-0252

seamless, lap welded or riveted longitudinal joint

2x10.3 = 20.6 litres Internal diameter

1800

thickness

25