

These particulars are supplied by the Resident General of Shipping and Seamen for the sale of

See file

Turbine Steamer "SAINT GEORGE"

Auxiliary Engines etc:-

Two Main Circulating and Dry Air Pumps, Circulating Engine Cylinders $10\frac{1}{2}$ " diameter. Dry Air Pump 16" diameter. Stroke 9". (Weir)

Two Wet Air Pumps (Twin Cylinder) Cylinders $8\frac{1}{2}$ " diameter Pumps 22" diameter. Stroke 15". (Weir)

Two Duplex Fresh Water Pumps Cylinders 3" diameter. Pump 2" diameter Stroke 3". (Watson)

Two Ash. Ejector Pumps (Duplex) cylinder 8" diameter. Pump 5" diameter Stroke 8". (Clarke Chapman)

1 Sanitary Duplex Pump, Cylinder $7\frac{1}{2}$ " diameter Pumps 5" diameter. Stroke 10". (Watson)

Two Compound Electric Engines and Dynamos, Cylinders 11" and 15" diameter. Stroke 7". (Allen)

One Duplex Circulating Pump for oil cooler, for Parson's Steam Turbines (Lamont)

Two Oil Pumps for Parson's Steam Turbines.

One Oil Cooler -do-

One Feed Water Heater, 398 sq ft heating surface. (Weir)

A One Feed Water Filter. (Liverpool Eng: Co)

Forced Draught Fans. Four - 54" Howdens with Boothroyd's Motors.



© 2020

Lloyd's Register
Foundation

00611-006125-0047