

CERTIFICATE FOR STEEL WIRE RIGGING.

We hereby Certify that the 2 - 90 fathoms of
4 inch circumference galvanized Steel Wire Rigging
 applied to Messrs Workman, Clark & Co. Ltd.,
 in the S/S" No. ~~341~~ "368. S/S "Appleleaf" is
 composed of 6 strands, each containing 24 wires of .070 inch
 diameter, and that the several wires, after being galvanized, have
 been subjected to, and have successfully withstood, the following
 tests, viz.:

Each wire has withstood a tensile stress at least equivalent to that
 set forth in Table No. 11 of the Rules of Lloyd's Register
 of Shipping, and the aggregate strength of the wires is not less
 than 10 per cent. in excess of that stress.

Each wire has been twisted eight times round itself as a core, and
 untwisted again and straightened without fracture.


No hemp has been used in the strands, a hemp core only being fitted.

We guarantee that the Steel Wire Rigging of
4 inches in circumference above described will bear a strain
 of 47 tons without breaking.

Clyde Wire Ropery,

April 1916.

Rutherglen, Glasgow.



Manufacturer

© 2021

Lloyd's Register
 Foundation

SECRET & CONFIDENTIAL

Referred to the Chief Ship Surveyor,
and the Chief Engineer Surveyor.

Co. 2

MAR 12 1917

Also for Mr. & A. Hill to note

M
12.3.17

Handwritten signature

Handwritten text

Handwritten text



© 2021

Lloyd's Register
Foundation