

Do all the Frames extend to the top height of the Poop? *Longer to the top of the Quarter Deck* Bridge House? *Yes* Forecastle? *Yes*
 To what height do the Reverse Frames extend? *Both angles longitudinal framing*
 Are the Poop or Raised Quarter Deck an efficient Iron Bulkhead at the fore end? *Yes*
 Give particulars of the means for closing the openings in Bulkhead *no openings*
 Is the Poop or Raised Quarter Deck connected with the Bridge House? *no* Has the Bridge House an efficient Bulkhead at the fore end?
 Give particulars of the means for closing the openings in Bulkhead *Steel hinged doors*
 What is the thickness of the Bridge Front plating? *40* and Coaming plate? *40*
 Give scantlings and spacing of the Stiffeners *9 x 2 1/2 x 3 1/2 x 50 channels spaced 30" apart*
 Are bracket plates fitted at each end of the stiffeners? *yes* Are hor'l. brackets fitted connecting Bridge Bulkhead with Bulwarks? *no*
 Does the Bridge House have an efficient Bulkhead at the after end? *no*
 How are the openings closed? *open aft*
 Is the Forecastle at least as high as the main or top-gallant rail? *yes* Has the Forecastle an efficient Iron or Wood Bulkhead at after end? *yes*
 Are the Engine and Boiler openings covered by a Bridge, Poop, Raised Quarter Deck, or enclosed by a Strong Iron or Steel Deckhouse? *no*
 If the openings are not so protected are the exposed parts of the Casings efficiently constructed? *yes*
 Give thickness of plating, scantlings and spacing of Stiffeners *plating 40 lb. 3/4" Stiffeners 4 x 2 1/2 x 30 spaced 24" x 48" well supported by locks and dunnage bulkheads and additional well in way*
 What is the height of the exposed Casings *5.0 upper to boat deck and 2 1/2 above boat deck* Are suitable means provided for closing all openings in them in bad weather? *yes*
 Are the Weather Deck Hatchways efficiently constructed and at least equal to the requirements of Section 28 of the Rules for 1904-5? Give particulars below:— *yes*

Position and Size.		Ship.		Rule.		Ship.		Rule.		Ship.		Rule.	
Item.		Ship.		Rule.		Ship.		Rule.		Ship.		Rule.	
Height above top of Deck		Steel watertight hatches 3' x 3' and 3' above deck fitted with watertight.											
Thickness { Sides.....													
Ends.....		hatch covers fastened with butterfly nuts and screws											
SHIFTING BEAMS OR WEB PLATES		Coamings 40 shielded											
Number													
Section and Scantlings.....													
Material.....		Coamings 50 d											
FOLE AND AFTERS		✓											
Number													
Section and Scantlings.....													
Material.....		✓											
HATCHES THICKNESS		✓											
Remarks.....													

* When the Fore and Afters are of wood the depth should be stated from the underside of the hatches.

(If the sill of the lowest side scuttle will be less than 6 inches above the Indian Summer Load Line if assigned under the tables, state vertical distance from top of deck at side amidships to lower edge of lowest side scuttle.)

The following information is to be given in all Cases of vessels dealt with under Paras. 11, 12 (under 15 feet Moulded depth) and under Shelter Deck Rules.

What is the thickness of the Bridge Sheerstrake? _____ Strake between Main and Bridge Sheerstrakes? _____

Delete the words { The Crew are, are not, berthed in the bridge house.
 that do not apply { The arrangements to enable them to get backwards and forwards from their quarters are, are not satisfactory.

Length of Bulwarks in well _____

Area of Freeing Ports required by Para. 11 (e) each side of vessel = _____ Sq. ft.

Ft. Tenths. Ft. Tenths. No.

x x
 x x

Freeing Ports (each side of vessel) = _____ Sq. ft.

Total deficiency or excess = _____ Sq. ft.



© 2021
 Lloyd's Register
 Foundation