

1 or 2 Dks., R.Q.Dk.
and Pt. Awng. Dk.

IRON OR STEEL STEAMER.

No. 16782

State if Report is also sent on the Machinery of the Vessel

Received at London Office

Date of completion of Report 8th May 1905.

Port of Hull

Date, First Survey Nov. 18/04

Last Survey

May 4th 1905

Rig Ketch.

Survey held at

On the Steam Trawler "GAMECOCK."

TONNAGE under

160.55

Do. of Poop

Do. of Raised Qr.

Do. of Bridge House

Do. of Forecastle

Do. of Houses on Deck

Do. of excess of Hatchways

Do. above Crown of

Engine Room

Gross Tonnage

Less Crew Space

Less above Crown of

Engine Room

TONNAGE FOR FEES

Less Engine Room

Less Navigation Spaces

Abolition of

Register Tonnage

as cut on Beam

ONE OR TWO DECKED VESSEL.

CLASS 100A1. Steam Trawler.

Master

Year of appointment

Built at

When built 1905

Launched 23rd March.

By whom built Gool Shipbuilding & Repairing Co. Ltd.

Owners. Kelsall Brothers & Beeching, Sim.

Managers

(Where necessary to be entered in Reg. Book).

Residence Hull.

Port belonging to Hull.

If Surveyed while Building, Afloat, or in Dry Dock

Yes

LENGTH on Deck as per Rule 108 Feet. 108 Inches. 10 1/2 BREADTH Moulded 21 Feet. 0 Inches. DEPTH, ACTUAL Top of Floors to top of Main Deck Beams 11 Feet. 2 Inches. No. of Decks with Flat laid On No. of Tiers of Beams On

Dimensions of Ship per Register, Length, 110.3 breadth, 21.1 depth, 11.2 Moulded Depth, 12 ft. 0 ins. Round of Beam, Actual 6 ins.

FRAMING.				FORGINGS AND CASTINGS.				KEELSONS AND STRINGERS.			
FRAME. Angles, 7×6 for $\frac{1}{2}$ length amidships				KEEL, Bar or Side Plates depth and thickness				CENTRE LINE KEELSON, Vertical Plate above floors, $8 \times 1 \frac{1}{2}$			
Do. for $\frac{1}{2}$ at each end	3	2 1/2	6	STEM, moulding and thickness	7 1/2 x 1 1/2	7 1/2 x 1 1/2	7 1/2 x 1 1/2	Do. for Rudder do. do.	6 x 2 1/2	6 x 2 1/2	6 x 2 1/2
Do. in way of Double Bottoms at Solid Floors				MAIN PIECE of Rudder, diameter at head	4 1/2	4 1/2	4 1/2	Do. at heel	3 x 2 1/2	2 1/2 x 2 1/2	2 1/2 x 2 1/2
Spacing of Frames from centre to centre	21	21	21	RUDDER, how constructed Forged iron frame, plated.				Can the Rudder be unshipped afloat?	Yes		
REVERSED FRAME, Angles	2 1/2	2 1/2	6								
DEEP FRAMING, depth of girder											
FLOORS, depth and thickness of Floor Plate at mid-line for $\frac{1}{2}$ length amidships	16	16	16								
Do. in way of Engines and Boilers	E 10 B 5/20	10	20								
Do. thickness at the ends of vessel											
Do. depth at $\frac{1}{2}$ the half breadth, as per Rule											
Do. height extended at the Bilges											
FLOORS & BRACKETS, in Cell Dble Bottoms											
Do. state if flanged (top & bottom)											
Do. Spacing											
CENTRE GIRDER, in Double Bottom, depth and thickness											
Do. Angles, Top											
Do. Bottom											
SIDE GIRDERS, number on each side & thickness											
Do. state if flanged (top & bottom)											
Do. Angles											
MARGIN PLATE, depth (exclusive of flange) and thickness											
Do. Angles to Outside Plating											
Do. Floors											
Do. Height of Floors at the Bilges											
INNER BOTTOM PLATING, breadth and thickness of Middle Line Strake		5	5								
Do. thickness in Engine and Boiler space											
Do. Remainder in Holds											
BEAMS, Main and Raised Quarter Deck, Single Angle, Bulb Angle, Plate or Tee Bulb	5 1/2	3	5 1/2								
Do. Angles on Upper Edge											
Do. Spacing		42	42								
BEAMS, Lower Deck, Single Angle, Bulb Angle, Plate or Tee Bulb											
Do. Angles on Upper Edge											
Do. Spacing											
BEAMS, Hold, Plate or Tee Bulb											
Do. Angles on Upper Edge											
Do. Spacing											
BEAMS, Poop Deck, Angle, Bulb Angle, Plate or Tee Bulb											
Do. Angles on Upper Edge											
Do. Spacing											
BEAMS, Bridge or Pt. Awng. Deck, Angle, Bulb Angle, Plate, or Tee Bulb											
Do. Angles on Upper Edge											
Do. Spacing											
BEAMS, Forecastle Deck, Angle, Bulb Angle, Plate or Tee Bulb	5 1/2	3	5 1/2								
Do. Angles on Upper Edge											
Do. Spacing		42	42								
PILLARS, In 'tween Decks, Size and Spacing											
Do. Hold		2 1/2	2 1/2								
Do. Quarter, 'tween Dks.											
Do. in Hold											
WEB FRAMES, In Fore Body, No. and Spacing											
Do. Brdth. & Thickness											
Do. No. of Side Stringers											
WEB FRAMES, In E. & B. Space, No. & Spacing											
Do. Brdth. & Thickness											
WEB FRAMES, In After Body, No. and Spacing											
Do. Brdth. & Thickness											
Do. No. of Side Stringers											
Do. Size of Angles or Tee Bars to Web Frames											
BRACKET PLATES to Stringers between Web Frames, Depth and Thickness											

