

WED. MAR 31 1920

Index No. 28811
(For London Office only.)

Lloyd's Register of Shipping.

SURVEYS FOR FREEBOARD STEAM SHIPS.

PARTICULARS RELATING TO ALL STEAM SHIPS EITHER FLUSH DECKED, OR WITH
TOP GALLANT FORECASTLES, SHORT POOPS AND BRIDGE HOUSES DISCONNECTED, OR
WITH TOP GALLANT FORECASTLES HAVING LONG POOPS, OR RAISED QUARTER DECKS
CONNECTED WITH BRIDGE HOUSES, OR OTHERWISE.

Port of Survey Nagasaki
Date of Survey 14th Jan. 20.
Name of Surveyor R. Croxford

Ship's Name. S.S. "Atlas Mara" Port of Registry and Nationality. Osaka Japanese
Official Number. 7.342.06 Date of Build. 1920
Particulars of Classification. +100 A-1 Shelter 8k with fld. contemplated

Registered ons from Register.	LENGTH. <u>420</u>	BREADTH. <u>56.23</u>	DEPTH. <u>35.92</u>	UNDER DECK TONNAGE. <u>6855.78</u>
gth on DLINE.	<u>419.5</u>	Frame Depth <u>9 1/2</u> Rule " <u>7</u>	Ceiling <u>fitted</u> Sheer <u>+50</u> <u>2 1/2</u> <u>8 1/2</u> in <u>-4 1/2</u> <u>tank 2"</u> <u>+08</u>	Peak Tanks
RECTED ENSIONS.	<u>419.5</u>	<u>55.81</u>	<u>36.50</u>	<u>6855.78</u>

efficient of fineness..... 80 ✓
y modification necessary } 02 C.B.
[Para. 4 (a) to (e)]* }
efficient as corrected 78 ✓

eer { Stem..... 106 1/2 } 150 ÷ 2 = 75 ...Mean
t { Sternpost ... 43 1/2 }
eer at 1/2 of the length from { Stem 55 1/2 } 74 ÷ 2 = 38 1/2 ...Mean
{ Sternpost 21 1/2 } 55
radual mean Sheer 40 - = 70
andard mean Sheer [Table, Para. 18] 51.95 - Correction
Difference..... 18.05 ÷ 4 = -4 3/4
If limited as Para. 18 (f) 4 1/2

Rise in Sheer { At front of bridge house.....
om amidships {
Para. 18 (e) } At after end of forecastle

Fall in Sheer } ÷ 2 =
Para. 18 (d) }
ngth uncovered Correction

ALLOWANCE FOR DECK ERECTIONS :-

eeboard, Table C.....
rection for Length, if required (Para. 12, 13, and 14)

eeboard by Table A. corrected for sheer, and for length, }
if required (Para. 12, 13, and 14) }

ference
centage as below.....

rection for R. Q. Dk. if engine and boiler openings not }
covered by bridge house (Para. 11) }

allowance for Deck Erections

	Length.	Length allowed.	Height.
orecastle.....	<u>45.9</u>		<u>7.5</u>
Bridge House			
† Raised Qr. Dk.....			
Poop.....			

Total

length of Ship

Corresponding percentage }
(Para. 11, 12, 13, or 14) }

FREEBOARD recommended amidships from centre of Disc to top of Statutory Deck Line, Wood (Iron) Deck :-

Fresh Water Line	above centre of Disc
Indian Summer Line	"	"	"
Winter Line	below	"	"
Winter North Atlantic Line	"	"	"

If the frames, skin planking, or ceiling are of unusual thickness the breadth of vessel to inside of ceiling should be reported if possible.

In vessels obtaining an allowance for deck erections under Para. 11 where the sheer drops abaft amidships the height of the R.Q.D. is to be taken from the level of the top of the amidships. In flush-decked vessels the total standard mean sheer means the sheer measured at the stem and sternpost. In vessels having poops and forecastles, it means the sheer measured at points distant one eighth of the vessel's length from stem and sternpost.

B. T.

MARKING FORM

RECEIVED - 5 AUG 1924

006760-006771-0082

Moulded Depth as measured..... 38'-6"
wood deck less str. 3 1/2
Addition for Keel below base line 38'-2 1/2"
for draught record..... 2 1/4 inches. W

NOTE - If the depth is measured when vessel is afloat, the details of measurement should be reported.

CORRECTION FOR LENGTH.

Length of Ship on Loadline..... 419.5
Length in Table 458.5
Difference 39
Correction for 10ft., Table A. 1.4 - Table C.
× Difference divided by 10 66 (if required.)
If 1/10ths length covered divide by 2 -6 1/2

CORRECTION FOR IRON DECK.

Proportion covered, if less than 1/10ths length covered allowed in
Thickness of usual wood deck, less stringer reduced mld depth

CORRECTION FOR ROUND OF BEAM.

Breadth at Gunwale amidships..... 54
Round of Beam 14
Normal round..... 13 1/2
Difference 1/2 ÷ 2 = -1/4"
Proportion of Deck uncovered (Para. 19)

NOTE - The round of beam should be reported on the full breadth of vessel at the gunwale.

Freeboard, Table A 10' - 11 1/4"
Correction for Sheer -4 3/4"
10' - 6 3/4"
Correction for Length -6 1/2"
8' - 11 1/2"
Allowance for Deck Erections 10' - 0 1/4"

Correction for Round of Beam..... -1/4
10' - 11 1/4"
Correction for fall in Sheer (if any)..... ✓

Correction for Iron Deck (if required) ✓

Additions for non-compliance with provisions of }
Para. 11 (a) and (e) † }
Other Corrections (if any) shortings & construction } + 1' - 8 1/2"

Winter Freeboard 10' - 11 1/4"
Summer Freeboard 10' - 4 1/4"
Indian Summer Freeboard 9' - 9 1/4"
N. A. Winter Freeboard ✓

Correction necessary because clearside amidships, measured in accordance with the Statute is not taken at the intersection of the wood or iron deck with side. = 1 3/4"

Winter Freeboard from deck line 11' - 1"
Summer " " " 10' - 6"
Indian Summer " " " 9' - 11"
N. A. Winter " " " 10' - 6"

† State dimensions of erecing port area on back of this form.

‡ The surveyor should state whether the fall in sheer as reported is measured relatively to the straight line of keel or to the water line. If measured relatively to water line the vessel's draft at time of survey, and also the usual load draft forward and aft, should be reported.

© 2021

Lloyd's Register Foundation

Do all the Frames extend to the top height in the Poop? ☒ Raised Quarter Deck? ☒ Bridge House? ☒ Forecastle? ☒ *Yes.*

To what height do the Reverse Frames extend? *Upper Deck.*

Has the Poop or Raised Quarter Deck an efficient Iron Bulkhead at the fore end? ☒

Give particulars of the means for closing the openings in Bulkhead ☒

Is the Poop or Raised Quarter Deck connected with the Bridge House? ☒ Has the Bridge House an efficient Bulkhead at the fore end? ☒

Give particulars of the means for closing the openings in Bulkhead ☒

What is the thickness of the Bridge Front plating? ☒ and Coaming plate? ☒

Give scantlings and spacing of the Stiffeners ☒

Are bracket plates fitted at each end of the Stiffeners? ☒ Are hor'l. brackets fitted connecting Bridge Bulk'd. with Bulwarks? ☒

Has the Bridge House an efficient Iron Bulkhead at the after end? ☒

How are the openings closed? ☒

Is the Forecastle at least as high as the main or top-gallant rail? *Yes* Has the Forecastle an efficient Iron or Wood Bulk'd. at after end? *Yes. (Iron)*

Are the Engine and Boiler openings covered by a Bridge, Poop, Raised Quarter Deck, or enclosed by a Strong Iron or Steel Deckhouse? *Yes*

If the openings are not so protected are the exposed parts of the Casings efficiently constructed? ☒

Give thickness of plating; scantlings and spacing of Stiffeners ☒

What is the height of the exposed Casings? ☒ Are suitable means provided for closing all openings in them in bad weather? *yes*

Are the Weather Deck Hatchways efficiently constructed and at least equal to the requirements of Section 28 of the Rules for 1904-5? Give particulars below:— *yes.*

Position and Size.	N ^o 1. 29'-3" x 20'-0"		N ^o 2. 32'-6" x 20'-0"		N ^o 3. 15' x 18'		N ^o 4. 12'-6" x 20'		N ^{os} 5+6 24'-6" x 20'	
Item.	Ship.	Rule.	Ship.	Rule.	Ship.	Rule.	Ship.	Rule.	Ship.	Rule.
COAMING.	Height above top of DECK	24"	24"	24"	24"	24"	24"	24"	24"	
	Sides.....	.50	.50	.44	.44	.44	.44	.50	.44	
	Ends.....	.44	.44	.44	.44	.44	.44	.44	.44	
SHIFTING BEAMS OR WEB PLATES.	Number	5	6	3	2	5				
	Section and Scantlings	17" x 36	17" x 40	14" x 40	15" x 36	17" x 36				
	Material	Steel	Steel	Steel	Steel	Steel				
* FORE AND AFTERS.	Number									
	Section and Scantlings									
	Material									
HATCHES	Thickness	3"								
Remarks.....	<i>Good</i>									

* The depth of Fore and Afters should be stated from the underside of the hatches in all cases.

(If the sill of the lowest side scuttle will be less than 6 inches above the Indian Summer Load Line if assigned under the tables, state vertical distance from top of deck at side amidships to lower edge of lowest side scuttle.)

The following information is to be given in all Cases of vessels dealt with under Paras. 11, 12 (under 15 feet Moulded depth) and under Shelter Deck Rules.

What is the thickness of the ^{3. P.} Bridge Sheerstrake? *.44* Strake between Main and Bridge Sheerstrakes? *.70*



Delete the words { The Crew are, are not, berthed in the bridge house.
that do not apply { The arrangements to enable them to get backwards and forwards from their quarters are, are not satisfactory.

Length of Bulwarks in well

Area of Freeing Ports required by Para. 11 (e) each side of vessel = Sq. ft.

Ft.	Tenths.	Ft.	Tenths.	No.	} Freeing Ports (each side of vessel)	=	Sq. ft.
x	x	x	x				
x	x	x	x				

Total deficiency or excess = Sq. ft.



Show hereon line of Floors or Tank Top with position of any Breaks in same; also height of Peak Tank tops, &c., &c.

State any special features in the construction of the Vessel *Vessel constructed with deep built angle frames & angles reverse frames, Two steel decks & beams every frame at each deck. No scuppers or other openings thro' the ship's side affect the position of load line disc!*

Owner's *Asaka Shoen Kaisha*
Address *Asaka, Japan.*
Fees *Yen 160.00*
Received by *me*

R. Crawford

Lloyd's Register
Foundation