

17615

EXT Syd 27/10/32

Rpt. Pt. 11b

copy written

Lloyd's Register of British & Foreign Shipping.

SURVEYS FOR FREEBOARD.

PARTICULARS IN RESPECT OF STEAM SHIPS WITH TOP GALLANT FORECASTLES, HAVING LONG POOPS OR RAISED QUARTER DECKS CONNECTED WITH BRIDGE HOUSES, SHORT POOP AND BRIDGE HOUSE DISCONNECTED, OR BRIDGE HOUSE

Port of Survey
Date of Survey
Name of Surveyor

Delete words which do not apply.

Ship's Name. <i>S.S. Ashridge</i>	Gross Tonnage. 2884	Official Number. 120500	Type of Ship. <i>me. STB deep framing</i>	Date of Build. 1905	Particulars of Classification. 100 A-1
Number in Register Book 1303					

Registered Length as shown by ship's register. *325.8* Breadth *47* Depth *22.25*

Length on Loadline *325.5*
Breadth *47*

Moulded Depth as measured *24'-10"*

NOTE. - If the depth is measured when vessel is afloat, the details of measurement should be reported.

Depth *22.25*
Correction for excess or deficiency of Gradual Sheer (Para. 3) *0.83*

Depth to be used *23.08*

Tons and Dk. *2740*
wil. plank
x 100

CORRECTION FOR LENGTH.

Length of Ship on Loadline	<i>325.5</i>
Length in Table	<i>298</i>
Difference	<i>27.5</i>
Correction for 10ft., Table A	<i>1.3</i>
x Difference divided by 10	<i>0.7</i>
If $\frac{1}{10}$ ths length covered divide by 2 for vessels coming under Para. 11 and Para. 12	<i>+ 3 1/2</i>
	<i>+ 2</i>

Efficient of fineness *0.777*

Modification necessary [Para. 4 (a) to (e)*] *6 in 518 deep framing*

Efficient as corrected *0.77*

CORRECTION FOR IRON DECK.

Proportion covered, if less than $\frac{1}{10}$ ths length covered	<i>46</i>
Thickness of usual wood deck, less stringer	<i>3 1/2</i>
	<i>- 1 1/2</i>

Stem *99*
Sternpost *46* } $145 \div 2 = 72.5$ Mean

at $\frac{1}{4}$ of the length from Stem *56 1/2*
Sternpost *25* } $81.5 \div 2 = 40.75$ Mean

Gradual Sheer

Standard Sheer (Table, Para. 18) *42.5* Correction
Difference *30 \div 4 = - 7 1/2*

CORRECTION FOR ROUND OF BEAM.

Breadth at Gunwale amidships	<i>46</i>
Round of Beam	<i>11 3/4</i>
Normal round	<i>11 1/2</i>
Difference	$\frac{1}{4} \div 2 =$ <i>1/8</i>
Proportion of Deck uncovered (Para. 19)	

NOTE. - The round of beam should be reported on the full breadth of vessel at the gunwale

Increase in Sheer in amidships [Para. 18 (e)]

At front of bridge house

At after end of forecastle

ALLOWANCE FOR DECK ERECTIONS :-

Freeboard, Table C	<i>2.6 3/4</i>
Correction for Length, if required (Para. 12 and 13)	<i>+ 2</i>
Freeboard by Table A, corrected for sheer, and for length, if required (Para. 12 and 13)	<i>5-2</i>
Difference	<i>2.5 1/4</i>
Percentage as below	<i>29.2%</i>
	<i>- 8 1/2</i>

Freeboard, Table A	<i>5.6</i>
Correction for Sheer	<i>- 7 1/2</i>
Correction for Length	<i>4.10 1/2</i>
Allowance for Deck Erections	<i>+ 3 1/2</i>
Correction for Round of Beam	<i>5.2 1/2</i>
Correction for Iron Deck (if required)	<i>- 8 1/2</i>
Additions for non-compliance with provisions of Para. 11 (d) and (e) †	<i>4.4</i>
Other corrections (if any)	

	Length.	Length allowed.	Height.
Forecastle	<i>40</i>	<i>40</i>	<i>7-7</i>
Bridge House	<i>88</i>	<i>88</i>	<i>7-6</i>
Raised Qr. Dk.			
Poop	<i>22</i>	<i>22</i>	<i>7-9</i>
Total		<i>150</i>	<i>46</i>
Length of Ship	<i>325.5</i>		

Winter Freeboard	<i>4.4</i>
Summer Freeboard	<i>4.0</i>
N. A. Winter Freeboard	<i>4.6</i>
Correction necessary because clear side amidships measured in accordance with the Statutes is not taken at the intersection of the wood or iron deck with side.	<i>1 3/4</i>
Winter Freeboard from deck line §	<i>4.5 2/3</i>
Summer " " " "	<i>4.1 2/3</i>
N. A. Winter, " " " "	<i>4.7 2/3</i>

Corresponding percentage (Para. 11, 12, or 13.) *29.2%*

FREEBOARD recommended amidships from centre of Disc to top of Statutory Deck Line, Wood (Iron) Deck :-

Fresh Water Line above centre of Disc	<i>4 1/2</i>
Indian Summer Line " " " "	<i>5</i>
Winter Line below " " " "	<i>4</i>
Winter North Atlantic Line " " " "	<i>4</i>

† If the frames skin planking or ceiling are of unusual thickness the breadth of vessel to inside of ceiling should be reported if possible.
‡ In vessels obtaining an allowance for deck erections under Para. 11 where the sheer drops abaft amidships the height of the R.Q.D. is to be taken from the level of the top of the amidship beam.

DELETE WORDS WHICH DO NOT APPLY.

The Crew *are, are not*, berthed in the bridge house.

The arrangements to enable them to get backwards and forwards from their quarters *are, are not* satisfactory.

Length of Bulwarks in well

Area of freeing ports required by Para. 11 (e) each side of vessel

Sq. Ft.

Freeing Ports (each side of vessel)

Ft.	Tenths.	Ft.	Tenths.	No.	}	=	Sq. Ft.
	x		x				
	x		x				

Total deficiency =

Sq. Ft.

Total excess =

"

Vertical distance from bottom of keel or from top of deck at side amidships to lower edge of lowest side scuttle.

(N.B.—This dimension need not be reported unless the sill of the lowest side scuttle would be less than 6 inches above the Indian Summer Load Line if assigned under the tables.)

Do all the Frames extend to the top height in the Poop?

Do. do. do. in the Raised Quarter Deck?

Do. do. do. Bridge House?

Do. do. do. Forecastle?

To what height do the Reverse Frames extend?

Has the Poop or Raised Quarter Deck an efficient Iron Bulkhead at the fore end?

Give particulars of the means for closing the openings in Bulkhead

Is the Poop or raised Quarter Deck connected with the Bridge House?

State whether the Bridge House efficiently covers the Engine and Boiler Openings

Has the Bridge House an efficient Iron Bulkhead at the fore end?

Give particulars of the means for closing the openings in Bulkhead

Describe how and to what extent it is Stiffened, give scantlings and spacing of Angle Irons, Bulb Plates, etc.

Has the Bridge House an efficient Iron Bulkhead at the after end?

How are the openings closed?

Is the forecastle at least as high as the main or top-gallant rail?


Has the Forecastle an efficient Iron or Wood Bulkhead at its after end?

Are the Hatchways efficiently constructed? What is the thickness of the Hatches?

State the height of the Coamings in fore well? In after well

Are the exposed parts of the Engine and Boiler Casings efficiently constructed?

State any special features in the construction of the Vessel



Show hereon the actual measurements of sheer, draft, erections, breaks in line of floors, &c.

Owners

Address

Fee £

11: 4: 1906


Fee applied for

Received by me

27.4.06

ASCD

APPLIED FOR IN LONDON



© 2021

Lloyd's Register Foundation

11b.
 REIGU
 VING
 "A"
 mber in
 stered L
 n by ship
 th on Lo
 (Rpt. 1
 Port
 Vessel's
 Official
 Port of
 ron or
 Name of
 atutory
 y the C
 accord
 From
 From
 Fr
 In
 W
 W
 Dist
 NOTE
 tom
 ed of
 enoch
 (To be fill
 tement
 ulded D
 eboards
 fee paid
 ructions
 tificate w
 10.01 - T
 al
 Ship
 ling percenta
 12, or 13
 ARD recom
 2.05
 skin planking
 should be repor
 taining an allowa
 height of the R.Q
 ik.