

TUE. FEB. 23. 1915

No. 2567.

No. in
eg. Book

Two sets of compound dynamo coupled directly to the single cylinder automatic
at-off vertical enclosed engine with forced lubrication.
3" dia. 6" stroke 450 R.P.M.

There is Dynamo fixed In the engine room

Position of Main Switch Board In the engine room having switches to groups A, B, C, D & E of lights, &c., as below

positions of auxiliary switch boards and numbers of switches on each 2 in the engine room, 4 on the shell

fuses are fitted on main switch board to the cables of main circuit yes and on each auxiliary switch board to the cables of auxiliary

circuits yes and at each position where a cable is branched or reduced in size yes, and to each lamp circuit yes

vessel is wired on the double wire system are fuses fitted to both flow and return wires or cables of all circuits including lamp circuits. Yes

re the fuses of non-oxidizable metal yes and constructed to fuse at an excess of 100 per cent over the normal current

Are all fuses fitted in easily accessible positions yes Are the fuses of standard dimensions yes If wire fuses are used

are permanent instructions fitted on or near each switch board giving particulars of proper size of fuse for each circuit *yes*

all switches and fuses constructed of incombustible materials and fitted on incombustible bases *Yes, porcelain & marble are used*

total number of lights provided for 160 arranged in the following groups:—

114 lights each of 16 candle power requiring a total current of 52.0 Amperes

13 lights each of 5 candle power requiring a total current of 2.5 Amperes

31 lights each of 32 candle power requiring a total current of 35.0 Amperes

2 lights each of 1,500 candle power requiring a total current of 10.0 Amperes

lights each of _____ candle power requiring a total current of _____ Amperes

2 Must head light with 2 lamps each of 32 candle power requiring a total current of 2.24 Amperes.

7 Side light with 2 lamps each of 32 candle power requiring a total current of 2.24 Amperes

7 Cargo lights of 1,500 + 128 candle power, whether incandescent or arc lights Incandescent.

ure lights, what protection is provided against fire, sparks, &c.

ere are the switches controlling the masthead and side lights placed In the chart room.

DESCRIPTION OF CABLES.

n cable carrying 1700 Amperes, comprised of 2500 wires, each No. 30 S.W.G. diameter, 0.3000 square inches total sectional area

inch cables carrying 19.0 Amperes, comprised of 11 wires, each No. 15 S.W.G. diameter, 0.0773 square inches total sectional area

each cables carrying 14.5 Amperes, comprised of 11 wires, each No. 20 S.W.G. diameter, 0.0110 square inches total sectional area

Is to lamps carrying 0.5 Amperes, comprised of 1 wires, each No. 18 S.W.G. diameter, 0.0018 square inches total sectional area

10 light cables carrying 5.0 Amperes, comprised of 234 wires, each No. 38 S.W.G. diameter, 0.0066 square inches total sectional area

DESCRIPTION OF INSULATION, PROTECTION, ETC.

Conductors are doubly insulated with india rubber and vulcanized fiber and tape. Cables are protected against mechanical & injury & chemical action by steel armoring or lead covering according to the requirements.

ts in cables, how made, insulated, and protected. Mechanical joints are made throughout and protected with water-tight boxes.

all the joints of cables thoroughly soldered, and the flux used not containing acids or other corrosive substances MS *Are all joints in accessible*

positions, none being made in bunkers, cargo spaces, or spaces which may at any time be used for carrying cargo, stores, or baggage *yes*

Are there any joints in or branches from the cable leading from dynamo to main switch board None

are the cables led through the ship, and how protected. Cables are led unconcealed and without any additional protections beside those on the cables themselves.

007078 - 007087 - 0241

07087-0241

DESCRIPTION OF INSULATION, PROTECTION, ETC.—continued.

Are they in places always accessible *They are all in accessible places.*

What special protection has been provided for the cables in open alleyways or where exposed to weather or moisture *Without any additional protections beside those on the cables themselves.*

What special protection has been provided for the cables near gulleys or oil lamps or other sources of heat *as before*

What special protection has been provided for the cables near boiler casings *as before*

What special protection has been provided for the cables in engine room *In some parts where necessary the cables are led through iron pipes*

How are cables carried through beams *Pierced through & wood lined through bulkheads, &c. Pierced through & provided with watertight glands.*

How are cables carried through decks *Pierced and led through iron pipes*

Are any cables run through coal bunkers *Yes or cargo spaces Yes or spaces which may be used for carrying cargo, stores, or baggage Yes*

If so, how are they protected *With lead covering and steel armoring on the cables themselves.*

Are any lamps fitted in coal bunkers or spaces which may at times be used for cargo, coals, or baggage *None*

If so, how are the lamp fittings and cable terminals specially protected

Where are the main switches and fuses for these lights fitted

If in the spaces, how are they specially protected

Are any switches or fuses fitted in bunkers *None*

Cargo light cables, whether portable or permanently fixed *portable* How fixed

In vessels fitted on the single wire system, how is the dynamo terminal fixed to the hull of vessel

How are the returns from the lamps connected to the hull

Are all the joints with the hull in accessible positions

Is the installation supplied with a voltmeter *Yes*, and with an amperemeter *Yes, 2 ammeters fixed on a marble switch board*

VESSELS BUILT FOR CARRYING PETROLEUM.

In vessels built for carrying petroleum, are all switches and fuses fitted in positions not liable to the accumulation of petroleum vapour or gas

Are any switches, fuses, or joints of cables fitted in the pump room or companion

How are the lamps specially protected in places liable to the accumulation of vapour or gas

The copper used is guaranteed to have a conductivity of not less than that of the Engineering Standards Committee's standard, and the wires are protected by tinning from the sulphur compounds present in the insulating material.

Insulation of cables is guaranteed to have a resistance of not less than 600 megohms per statute mile at 60° Fahrenheit after 24 hours' immersion in water, the test being made after one minute's electrification at not less than 500 volts and while the cable is still immersed.

The foregoing statements are a correct description of the Electric Light installation fitted by us on this vessel and we declare that it is at this date in good order and safe working condition.

S. Tada Electrical Engineers Date *18th, 8, 19.*

COMPASSES.

Distance between dynamo or electric motors and standard compass	<i>Dynamo to standard compass</i>	<i>115 ft</i>
	<i>Motor</i>	<i>110 ft</i>
Distance between dynamo or electric motors and steering compass	<i>Dynamo " steering "</i>	<i>105 ft</i>
	<i>Motor " " "</i>	<i>100 ft</i>

The nearest cables to the compasses are as follows:—

A cable carrying	<i>5.6</i>	Amperes	<i>6</i>	feet from standard compass	<i>15</i>	feet from steering compass
A cable carrying	<i>13.5</i>	Amperes	<i>17</i>	feet from standard compass	<i>13</i>	feet from steering compass
A cable carrying		Amperes		feet from standard compass		feet from steering compass

Have the compasses been adjusted with and without the electric installation at work at full power

The maximum deviation due to electric currents, etc., was found to be _____ degrees on _____ course in the case of the standard compass and _____ degrees on _____ course in the case of the steering compass.

Kawasaki Dockyard Co., Ltd.

Builder's Signature. Date *19th Aug. 1919.*

GENERAL REMARKS.

For J. Okakura
Secretary

The installation has been fitted in accordance with the Rules & Regulations, and worked satisfactorily on trial

It is submitted that this vessel is eligible for THE RECORD. Elec. light.

Alexander Watt.

Surveyor to Lloyd's Register of Shipping.

TUE 7-OCT. 1919

Committee's Minute