

11b.

11b.

Preliminary

Index No. 27946  
(For London Office only.)

# Lloyd's Register of Shipping.

## SURVEYS FOR FREEBOARD.—STEAM SHIPS.

PARTICULARS RELATING TO ALL STEAM SHIPS EITHER FLUSH DECKED, OR WITH TOP GALLANT FORECASTLES, SHORT POOPS AND BRIDGE HOUSES DISCONNECTED, OR WITH TOP GALLANT FORECASTLES HAVING LONG POOPS, OR RAISED QUARTER DECKS CONNECTED WITH BRIDGE HOUSES, OR OTHERWISE.

Port of Survey Antwerp  
Date of Survey 11.6.19  
Name of Surveyor

Ship's Name.	Port of Registry and Nationality.	Official Number.	Gross Tonnage.	Date of Build.	Particulars of Classification.
<u>Antwerp Eng. Co. No. 75</u>					<u>100 A1</u>
Number in Register Book					

Registered dimensions from Ship's Register.	LENGTH.	BREADTH.	DEPTH.	UNDER DECK TONNAGE.
		<u>38.2</u>	<u>20.08</u>	<u>1480</u> ✓
Length on LOADLINE.	<u>250</u>	Frame Depth <u>6 1/2</u> Rule „ <u>5</u> = <u>25</u>	Ceiling + <u>20</u> Sheer + <u>48</u> = <u>level tank</u>	Peak Tanks
CORRECTED DIMENSIONS.	<u>250</u>	<u>37.95</u>	<u>20.76</u>	<u>1480</u>

Co-efficient of fineness..... .75  
Any modification necessary {  
[Para. 4 (a) to (e)]\* 6.8.19  
Co-efficient as corrected ..... .73

Sheer { Stem..... 70  
at { Sternpost... 35 }  $105 \div 2 = 52.5$  Mean 36 17.5  
.48  
Sheer at 1/2 of the length from { Stem  
Sternpost assumed gradual }  $\div 2 =$  ...Mean  
Gradual mean Sheer .....  
Standard mean Sheer [Table, Para. 18] ..... 35 ✓ Correction  
Difference.....  $17.5 \div 4 =$   
§ If limited as Para. 18 (f) ..... - 1 1/2

Rise in Sheer { At front of bridge house.....  
from amidships { At after end of forecastle .....  
[Para. 18 (e)]  
Fall in Sheer {  
Para. 18 (d) }  $\div 2 =$   
Length uncovered ..... Correction

ALLOWANCE FOR DECK ERECTIONS :—  
Freeboard, Table C..... 1-9 1/4 ✓  
Correction for Length, if required (Para. 12, 13, and 14) ..... - 1 ✓  
1-8 1/4 ✓  
Freeboard by Table A. corrected for sheer, and for length, {  
if required (Para. 12, 13, and 14) } 3-11 ✓  
Difference ..... 2-2 3/4 ✓  
Percentage as below..... 27.1% ✓  
7.25 ✓  
Correction for R. Q. Dk. if engine and boiler openings not covered by bridge house (Para. 11) }  
Allowance for Deck Erections ..... - 7 1/4 ✓

	Length.	Length allowed.	Height.
Forecastle.....	<u>27.4 1/2</u>	<u>27.37</u>	<u>7.5</u>
Bridge House.....	<u>52.5</u> <u>closed</u>	<u>57.50</u>	<u>7.0</u>
† Raised Qr. Dk.....	<u>5.0</u> <u>overhang a</u>		
Poop.....	<u>22.7 1/2</u>	<u>22.62</u>	<u>7.0</u>
Total .....		<u>107.49</u> ✓	
Length of Ship .....		<u>250</u>	<u>= .43</u> ✓
Corresponding percentage { (Para. 12, 13, or 14) } <u>27.1%</u> ✓			

FREEBOARD recommended amidships from centre of Disc to top of Statutory Deck Line, Wood (Iron) Deck :—  
16.5 19  
Fresh Water Line above centre of Disc .....  
Indian Summer Line „ „ „ .....  
Winter Line below „ „ .....  
Winter North Atlantic Line „ „ „ .....

Moulded Depth as measured..... 22' 3"  
Given  
Addition for Keel below base line for draught record.....inches.

CORRECTION FOR LENGTH.  
Length of Ship on Loadline..... 250 ✓  
Length in Table ..... 267 ✓  
Difference ..... 17 ✓  
Correction for 10ft., Table A. .... 1.2 ✓ Table C. .6 ✓  
× Difference divided by 10 ..... 2.04 (if required.) 1.02 ✓  
If 1/10ths length covered divide by 2 - 2 ✓ - 1 ✓

CORRECTION FOR IRON DECK.  
Proportion covered, if less than 1/10ths length covered ..... .43  
Thickness of usual wood deck, less stringer ..... 3 1/2  
- 1 1/2 ✓

CORRECTION FOR ROUND OF BEAM.  
Breadth at Gunwale amidships..... 38  
Round of Beam ..... 9 1/2  
Normal round..... 9 1/2  
Difference .....  $\div 2 =$  .....  
Proportion of Deck uncovered (Para. 19) .....

Freeboard, Table A ..... 4-5 1/2 ✓  
Correction for Sheer ..... - 4 1/2 ✓  
4-1 ✓  
Correction for Length ..... - 2 ✓  
3-11 ✓  
Allowance for Deck Erections ..... - 7 1/4 ✓  
3-3 3/4 ✓  
Correction for Round of Beam..... ✓  
Correction for fall in Sheer (if any).....  
Correction for Iron Deck (if required) ..... 3-2 1/4 ✓  
Additions for non-compliance with provisions of {  
Para. 11 (d) and (e) † }  
Other Corrections (if any) .....

Winter Freeboard ..... 3-2 1/4  
Summer Freeboard ..... 2-11 ✓  
Indian Summer Freeboard ..... 2-7 3/4 ✓  
N. A. Winter Freeboard ..... 3-4 1/4 ✓  
Correction necessary because clearside amidships, measured in accordance with the Statute is not taken at the intersection of the wood or iron deck with side. 1 1/2 ✓

Winter Freeboard from deck line ..... 3-3 3/4 ✓  
Summer „ „ „ „ ..... 3-0 1/2 ✓  
Indian Summer „ „ „ „ ..... 2-9 1/4 ✓  
N. A. Winter „ „ „ „ ..... 3-5 3/4 ✓  
Correction necessary because clearside amidships, measured in accordance with the Statute is not taken at the intersection of the wood or iron deck with side. 1 1/2 ✓

† If the frames, skin planking, or ceiling are of unusual thickness the breadth of vessel to inside of ceiling should be reported if possible.  
† In vessels obtaining an allowance for deck erections under Para. 11 where the sheer drops abaft amidships the height of the R.Q.D. is to be taken from the level of the top of the amidship beam.  
§ In flush-decked vessels the total standard mean sheer means the sheer measured at the stem and sternpost. In vessels having poops and forecastles, it means the sheer measured at points distant one eighth of the vessel's length from stem and stern-post.

007257-007255-01739

© 2021

Lloyd's Register Foundation