

Lloyd's Register of Shipping.

SURVEYS FOR FREEBOARD.—STEAM SHIPS.

PARTICULARS RELATING TO ALL STEAM SHIPS EITHER FLUSH DECKED, OR WITH TOP GALLANT FORECASTLES, SHORT POOPS AND BRIDGE HOUSES DISCONNECTED, OR WITH TOP GALLANT FORECASTLES HAVING LONG POOPS, OR RAISED QUARTER DECKS CONNECTED WITH BRIDGE HOUSES, OR OTHERWISE.

Port of Survey _____
Date of Survey _____
Name of Surveyor _____

Ship's Name. *Burmeister & Wain*
Proposed Vessel No 10927
Number in Register Book _____
Port of Registry and Nationality. _____
Official Number. _____
Gross Tonnage. _____
Date of Build. _____
Particulars of Classification. *1007.1. **
open shelter deck.

Registered dimensions from Ship's Register.	LENGTH.	BREADTH.	DEPTH.	UNDER DECK TONNAGE.
	<i>371.0'</i>	<i>52.65'</i>	<i>20.15'</i>	<i>2800</i>
Length on LOADLINE.	<i>370.0'</i>	Frame Depth <i>10"</i> Rule Ceiling <i>2" + 2 1/2"</i> Sheer	Peak Tanks	
CORRECTED DIMENSIONS.		<i>Beam increased to 53.0'</i> <i>moulded</i>		

Moulded Depth as measured..... *23'-6"*
Addition for Keel below base line for draught record..... inches.

NOTE.— If the depth is measured when vessel is afloat, the details of measurement should be reported.

CORRECTION FOR LENGTH

Length of Ship on Loadline.....
Length in Table
Difference
Correction for 10ft., Table A. Table C.
× Difference divided by 10 (if required.)
If $\frac{6}{10}$ ths length covered divide by 2

CORRECTION FOR IRON DECK.

Proportion covered, if less than $\frac{7}{10}$ ths length covered
Thickness of usual wood deck, less stringer

CORRECTION FOR ROUND OF BEAM.

Breadth at Gunwale amidships.....
Round of Beam..... *no camber on Upper deck*
Normal round..... *6" camber on Shelter deck*
Difference ÷ 2 =
Proportion of Deck uncovered (Para. 19)

NOTE.— The round of beam should be reported on the full breadth of vessel at the gunwale.

Freeboard, Table A
Correction for Sheer
Correction for Length
Allowance for Deck Erections
Correction for Round of Beam.....
Correction for fall in Sheer (if any).....
Correction for Steel Deck (if required)

Additions for non-compliance with provisions of }
Para. 11 (d) and (e) † }
Other Corrections (if any)

Winter Freeboard
Summer Freeboard
Indian Summer Freeboard
N. A. Winter Freeboard

Correction necessary because clearside amidships, measured }
in accordance with the Statute is not taken at the }
intersection of the wood or steel deck with side. }

Winter Freeboard from deck line
Summer " " " "
Indian Summer " " " "
N. A. Winter " " " "

Co-efficient of fineness..... *.70*
Any modification necessary }
[Para. 4 (a) to (e)]* } *.02*
Co-efficient as corrected *.68*

Sheer { Stem..... *78"*
at { Sternpost .. *54"* } ÷ 2 = ...Mean

Sheer at $\frac{1}{2}$ of the length from { Stem *43"*
Sternpost *30"* } ÷ 2 = ...Mean

Gradual mean Sheer
Standard mean Sheer [Table, Para. 18]
Difference..... ÷ 4 = Correction
§ If limited as Para. 18 (f)

Rise in Sheer from amidships }
[Para. 18 (e)] { At front of bridge house.....
At after end of forecastle

Fall in Sheer }
Para. 18 (d) } ÷ 2 =
Length uncovered Correction

ALLOWANCE FOR DECK ERECTIONS :—

Freeboard, Table C.....
Correction for Length, if required (Para. 12, 13, and 14)
Freeboard by Table A, corrected for sheer, and for length, }
if required (Para. 12, 13, and 14) }
Difference
Percentage as below.....

Correction for R. Q. Dk. if engine and boiler openings not }
covered by bridge house (Para. 11) }
Allowance for Deck Erections

	Length.	Length allowed.	Height.
Forecastle.....	<i>321.9'</i>		<i>8.5'</i>
Bridge House			
† Raised Qr. Dk.....			
Poop.....	<i>43.4'</i>		<i>8.5'</i>
Total			
Length of Ship			
Corresponding percentage } (Para. 11, 12, 13, or 14) }			

FREEBOARD recommended amidships from centre of Disc to top of Statutory Deck Line, Wood (Steel) Deck :—

Fresh Water Line	above centre of Disc
Indian Summer Line	" " "
Winter Line	below " "
Winter North Atlantic Line	" " "

⊛ If the frames, skin planking, or ceiling are of unusual thickness the breadth of vessel to inside of ceiling should be reported if possible.
† In vessels obtaining an allowance for deck erections under Para. 11 where the sheer drops abaft amidships the height of the R.Q.D. is to be taken from the level of the top of the amidship beam.
§ In flush-decked vessels the total standard mean sheer means the sheer measured at the stem and stern-post. In vessels having poops and forecastles, it means the sheer measured at points distant one-eighth of the vessel's length from stem and stern-post.

† State dimensions of freeing port area on back of this form.
‡ The Surveyor should state whether the fall in sheer as reported is measured relatively to the straight line of keel or to the water line. If measured relatively to water line the vessel's draft at time of survey, and also the usual load draft forward and aft should be reported.



007412 - 007421 - 0151

Shelter deck

Do all the Frames extend to the top height in the Poop? as per rule Raised Quarter Deck? Bridge House? Forecastle?

To what height do the Reverse Frames extend?

Has the Poop or Raised Quarter Deck an efficient Iron Bulkhead at the fore end? yes.

Give particulars of the means for closing the openings in Bulkhead no openings

Is the Poop or Raised Quarter Deck connected with the Bridge House? Has the Bridge House an efficient Bulkhead at the fore end?

Give particulars of the means for closing the openings in Bulkhead

What is the thickness of the Bridge Front plating? and Coaming plate?

Give scantlings and spacing of the Stiffeners

Are bracket plates fitted at each end of the Stiffeners? Are hor'l. brackets fitted connecting Bridge Bulk'd. with Bulwarks?

Has the Bridge House an efficient Iron Bulkhead at the after end? yes.

How are the openings closed? Wood in channel bars.

Is the Forecastle at least as high as the main or top-gallant rail? yes Has the Forecastle an efficient Iron or Wood Bulk'd. at after end? Steel

Are the Engine and Boiler openings covered by a Bridge, Poop, Raised Quarter Deck, or enclosed by a Strong Iron or Steel Deckhouse? By the Shelter Deck.

If the openings are not so protected are the exposed parts of the Casings efficiently constructed?

Give thickness of plating; scantlings and spacing of Stiffeners

What is the height of the exposed Casings? Are suitable means provided for closing all openings in them in bad weather?

Are the Weather Deck Hatchways efficiently constructed and at least equal to the requirements of Section 28 of the Rules for 1904-5? Give particulars below:— yes

Position and Size.	No 1 22'-6" x 16'-0"		No 2 23'-4" x 16'-0"		No 3 23'-4" x 16'-0"		No 4 21'-0" x 16'-0"	
Item.	Ship.	Rule.	Ship.	Rule.	Ship.	Rule.	Ship.	Rule.
COAMING.	Height above top of DECK	2'-8"	2'-8"	2'-8"	2'-8"	2'-8"		
	Thickness	Sides.....	.50"	.50"	.50"	.50"		
		Ends.....	.50"	.50"	.50"	.50"		
SHIFTING BEAMS OR WEB PLATES.	Number	3	4	4	3			
	Section and Scantlings	3 1/2" x 3" x .42" 11" ~ .34"	3 1/2" x 3" x .42" 11" ~ .30"	3 1/2" x 3" x .42" 11" ~ .30"	3 1/2" x 3" x .42" 12" ~ .32"			
	Material	6" x 4" x .54"						
* FORE AND AFTERS.	Number	✓	✓	✓	✓			
	Section and Scantlings							
	Material							
HATCHES Thickness	3"	3"	8 1/2"	3"				
Remarks.....								

* The depth of Fore and Afters should be stated from the underside of the hatches in all cases.
 (If the sill of the lowest side scuttle will be less than 6 inches above the Indian Summer Load Line if assigned under the tables, state vertical distance from top of deck at side amidships to lower edge of lowest side scuttle.)

The following information is to be given in all Cases of vessels dealt with under Paras. 11, 12 (under 15 feet Moulded depth) and under Shelter Deck Rules.

What is the thickness of the Bridge Sheerstrake? .62" Strake between Main and Bridge Sheerstrakes? .60"



Delete the words The Crew are not, berthed in the bridge house.
 that do not apply The arrangements to enable them to get backwards and forwards from their quarters are, satisfactory.

Length of Bulwarks in well

Area of Freeing Ports required by Para. 11 (e) each side of vessel = Sq. ft.

Ft.	Tenths.	Ft.	Tenths.	No.	} Freeing Ports (each side of vessel);	= <u> </u> Sq. ft.
×		×				
×		×				

Total deficiency or excess = Sq. ft.



Show hereon line of Floors or Tank Top with position of any Breaks in same; also height of Peak Tank tops, &c., &c.

State any special features in the construction of the Vessel

Builder's name and yard number A/S Burmeister & Wain Ltd. Proposed vessel No.

Names of sister vessels

Owners

Address

Fee £ Received by me