

*and*  
No. 225.

MINIMUM FREEBOARD DESIRED.

---


DIMENSIONS:

Length B.P.	272'0"
Breadth.	41'0"
Depth Moulded.	19'10"
Approx. U.D. Tonnage.	1780 Tons.
Sheer at Stem.	6'0"
" " $\frac{1}{8}$ from Stem.	3'6"
" " Sternpost.	3'6"
" " $\frac{1}{8}$ from Sternpost.	2'0"
Length of Poop.	22'0"
" " Bridge.	78'0"
" " Forecastle.	26'0"

Wash Ports fitted for Minimum Freeboard.

Bridge Front strengthened for Minimum Freeboard.

---



© 2020


Lloyd's Register  
Foundation

007506 - 007517 - 0363



2392

It is recommended that the minimum dimensions suggested for a vessel's freeboard be the same dimensions suggested it will be necessary to have the vessel's freeboard in the same direction as a round hull. It may also be in the same direction.



Bridge front strengthened for minimum freeboard.  
When loads lifted for minimum freeboard.



"	Forecastle.	28'0"
"	Bridge.	18'0"
Length of Load.		22'0"
"	3 ft from Stemboard.	8'0"
"	Stemboard.	2'8"
"	3 ft from Stem.	2'8"
Sheet at Stem.		2'0"
Deck at N.D. Tonnage.		120 tons
Deck at N.D. Tonnage.		12'10"
Deck at N.D. Tonnage.		17'0"
Deck at N.D. Tonnage.		21'0"

MINIMUM FREEBOARD DESIRED

SSS No.