

S.S. Iryo Maru
Lloyd's Register of Shipping,

(MEIKAI BUILDING)

32, AKASHI-MACHI,

KOBE, 8th. August 1930.

This is to Certify that at the request

of Messrs. The Kobe Steel Works, Ltd., Kobe,

Hearth Steel Forgings or Castings named below ~~were~~ examined and
their works on 25th. November 1929 to 26th. July 1930.

and to be as far as could be ascertained, sound and free from defect.

(7) Sets Cast Steel Cross-head pin Brasses. 320 m/m dia.

Examined in finished condition.

and Dropped from a height of 8 feet on to a steel slab,

suspended and hammered without indication of defect.

Test Mark	Tenacity Tons/sq in	Elongation % in 2"	Bend 1" x 1/4" x 120°
60 A	30.3	28	Good
63 C	31.5	26	"
63 D	30.2	29	"
63 E	29.0	30	"
70 D	30.3	27	"

Continued on sheet 2.

The castings are intended for Asano Dockyard Ship No. 270

and ~~has~~ have been stamped as follows:-


TEST MARKS AS ABOVE
LLOYD'S
No. 2590
22-7-30
A.D.M. LR

Yen 49.00

A.D. Morrison

Surveyor to Lloyd's Register.

ificate is issued upon the terms of the Rules and Regulations of the Society, which provide that:-
the Committee use their best endeavours to ensure that the functions of the Society are properly executed, it is to be
that neither the Committee nor the Society are under any circumstances whatever to be held responsible for any inaccuracy
or certificate issued by the Society or its Surveyors, or in any entry in the Register Book or other publication of the
any error of judgment, default, or negligence of the Surveyors, other Officers or Agents of the Society."



Lloyd's Register
Foundation

007553-007562-0244 1/2

S. Lloyd Morris

icate No. 2590.

Sheet No. 2.

Kobe, 8-8-30.

st Mark

Tenacity
Tons/sq. in.

Elongation
% in 2"

Bend
1" x 3/4" x 120°

70 E

31.6

27

Good

70 F

30.1

27

"

46 D

31.0

28

"

46 E

30.9

28

"

473 E

30.4

26

"

46 F

29.9

27

"

473 G

31.0

28

"

473 H

31.6

27

"

370 C

33.9

27

"

S. Morris

SURVEYOR TO LLOYD'S REGISTER.



© 2020

Lloyd's Register
Foundation