

With or Without Disconnected Erections.

STEEL STEAMER.

Date of completion of report
Survey held at

Queensferry, Chester.

Port of

Date, First Survey Oct 9th / 1920

Last Survey Oct 16th

1920

On the

Steel S.S. Foam

Rig Schooner.

TONNAGE under
Tonnage Deck...
Do. between Tonnage Dk. and 3rd and 4th Dk.
Total under Upper Dk.

94.57

CLASS 100 A.1 for
Fishing purposes.

FEET.

Master

Year of appointment

(1) As Master in service of
owner of present vessel:—19
(2) As Master of this
vessel:—19

Built at

Queensferry.

When built

1920

Launched

28.6.19.

By whom built

J. E. Adela Mitchell & Co.

Owners

The Admiralty.

Managers

(Where necessary to be entered in Reg. Book)

Residence

Port belonging to

Register Tonnage

39.44

Destined Voyage

If Surveyed while Building, Afloat, or in Dry Dock Building & afloat

LENGTH on Deck as per Rule	Feet.	Inches.	BREADTH Moulded	Feet.	Inches.	DEPTH, ACTUAL	Feet.	Inches.	No. of Decks with flat laid	No. of Tiers of Beams
86	0		18	6		9	4		one	one
Moulded depth, ft. — ins. — To Bridge Dk. Round of Upper Dk. Beam, Actual 6" ins.										
Moulded depth, ft. 10 ins. 0 To Upper Dk.										

FRAMING.						PILLARS.					
ME, Angles, — E —	Inches in Ship.	Inches in Ship.	Inches in Ship.	Inches in Ship.	Inches in Ship.	PILLARS in 'tween Deck, size and spacing	Inches in Ship.	Inches in Ship.	Inches in Ship.	Inches in Ship.	Inches in Ship.
in peaks	4	3	38	4	3	" " Hold	2 1/2	41	2 1/4	2 1/2	41
in way of Double Bottoms at Solid Floors...	4	3	38	4	3	" " Quarter 'tween Dks.,	—	—	—	—	—
" " at intermdt. Bkts.	—	—	—	—	—	" " in Hold	—	—	—	—	—
ing of Frames from centre to centre amidships	20 1/2	21	20 1/2	21	21	KEELSONS & STRINGERS.					
" " length to Collision bulkhead	4 1/2	3	3 1/2	3	3	CENTRE LINE KEELSON, Vertical Plate above	—	—	—	—	—
" " on engine	3	3	3	3	3	floors, Through Plate, or Intercoastal Plate	—	—	—	—	—
ERSED FRAME, Angles...	3	3	3	3	3	Rider Plate	—	—	—	—	—
in way of Double Bottoms at Solid Floors...	—	—	—	—	—	Flat Plate Keel Angles	12	3 1/2	3 1/2	5	5
" " at intermdt. Bkts.	—	—	—	—	—	Horizontal Plates on Floors	—	—	—	—	—
AMING, depth of girder	—	—	—	—	—	Angles or Bulb Angles	—	—	—	—	—
DOORS, depth and thickness of Floor Plate	14	3	14	3	3	SIDE KEELSONS, Number	—	—	—	—	—
at mid-line for 1/2 length amidships...	ES	3	ES	3	3	Angles or Bulb Angles	—	—	—	—	—
in way of Engine and Boiler Spaces	BS	3	BS	3	3	Plate above floors, for length...	—	—	—	—	—
thickness at the ends of vessel	—	—	—	—	—	Intercoastal Plate, for length	—	—	—	—	—
depth at 1/2 the half breadth, as per Rule	—	—	—	—	—	Attached to outside Plating with Angle...	—	—	—	—	—
height extended at the Bilges	—	—	—	—	—	BILGE KEELSON, Angles	4	3	38	4	3
CORS in Cell. Double Bottoms	—	—	—	—	—	Intercoastal Plate for length	—	—	—	—	—
state if flanged (top & bottom)	—	—	—	—	—	Attached to outside Plating with Angle	4	3	38	4	3
Spacing of Solid floors	—	—	—	—	—	SIDE STRINGERS, Number	—	—	—	—	—
NTRE GIRDER, in Dbl. bottom, dpth. & thcknss.	—	—	—	—	—	Angles	—	—	—	—	—
Angles, Top	—	—	—	—	—	Intercoastal Plate, for length	—	—	—	—	—
" " Bottom	—	—	—	—	—	Attached to outside plating with Angle	—	—	—	—	—
" " to Floors	—	—	—	—	—	Upper Deck Stringer Plate, br'dth & thickness	46	34	32	46	34
Brackets at intermdt. frmg., width & thcknss	—	—	—	—	—	(clear of Bridge)	—	—	—	—	—
DE GIRDERS, number on each side & thickness	—	—	—	—	—	br'dth & thickness	—	—	—	—	—
state if flanged (top and bottom)	—	—	—	—	—	(in way of Bridge)	3	3	3	3	3
Angles (top and bottom)	—	—	—	—	—	Angle (clear of Bridge)	—	—	—	—	—
" " to Floors	—	—	—	—	—	Tie Plate at sides of Hatchways	34	3	34	3	3
MARGIN PLATE, depth (exclusive of flange)	—	—	—	—	—	Deck. Steel, for whole lng.	—	—	—	—	—
and thickness	—	—	—	—	—	Thickness (clear of Bridge)	—	—	—	—	—
Angle to Outside Plating	—	—	—	—	—	(in way of Bridge)	—	—	—	—	—
" " Floors	—	—	—	—	—	Wood Deck, Material & thickness	2 1/2	larch	2 1/2	larch	26
Brackets at intermdt. frmg., width & thcknss	—	—	—	—	—	Second Deck Stringer Plate, br'dth & thickness	—	—	—	—	—
Height of Outside Brackets above at bilge	—	—	—	—	—	Angles on ditto, No.	—	—	—	—	—
INNER BOTTOM PLATING, breadth and thickness of Middle Line Strake	—	—	—	—	—	Tie Plates outside Hatchways	—	—	—	—	—
in Engine and Boiler space	—	—	—	—	—	Deck. Steel, for	26	—	26	—	—
Remainder in Holds	—	—	—	—	—	Wood Deck, Material & thickness	—	—	—	—	—
BEAMS, Upper Deck, Single Angle, Bulb	5	3	34	5	3	Third Deck Stringer Plate, br'dth & thickness	—	—	—	—	—
Angle, Plate, Tee Bulb, or Channel	—	—	—	—	—	Angles on ditto, No.	—	—	—	—	—
In way of Long Bridge	—	—	—	—	—	Tie Plates, outside Hatchways	—	—	—	—	—
" " Spacing	41	4	42	41	4	Deck. Material and thickness	2 1/2	W. Pine	2 1/2	W. Pine	—
BEAMS, Second Deck, Single Angle, Bulb	3	3	3	3	3	Fourth and Fifth Deck Stringer Plate, br'dth & thickness	—	—	—	—	—
Angle, Plate, Tee Bulb, or Channel	—	—	—	—	—	Angles on ditto, No.	—	—	—	—	—
" " Spacing	42	—	42	—	—	Tie Plates outside Hatchways	—	—	—	—	—
BEAMS, Third and Fourth Deck, Single Angle	3	3	3	3	3	Deck. Material & thickness	2 1/2	W. Pine	2 1/2	W. Pine	—
Bulb Angle, Plate, Tee Bulb, or Channel	—	—	—	—	—	Poop Deck Stringer Plate, breadth & thickness	—	—	—	—	—
Angles on upper edge	—	—	—	—	—	Angle on ditto	—	—	—	—	—
" " Spacing	41	—	41	—	—	Tie Plates	—	—	—	—	—
BEAMS, Poop Deck, Angle, Bulb Angle, Plate	3	3	3	3	3	Deck. Material and thickness	—	—	—	—	—
Tee Bulb, or Channel	—	—	—	—	—	Bridge Deck Stringer Plate, br'dth & thickness	—	—	—	—	—
Angles on upper edge	—	—	—	—	—	Angle on ditto	—	—	—	—	—
" " Spacing	20	—	20	—	—	Tie Plates	—	—	—	—	—
BEAMS, Bridge Deck, Angle, Bulb Angle, Plate	—	—	—	—	—	Deck. Material and thickness	—	—	—	—	—
Tee Bulb, or Channel	—	—	—	—	—	Forecastle Deck Stringer Plate, br'dth & th'kns	—	—	—	—	—
Angles on upper edge	—	—	—	—	—	Angle on ditto	—	—	—	—	—
" " Spacing	—	—	—	—	—	Tie Plates	—	—	—	—	—
BEAMS, Forecastle Deck, Angle, Bulb Angle	—	—	—	—	—	Deck. Material and thickness	—	—	—	—	—
Plate, Tee Bulb, or Channel	—	—	—	—	—	* If Iron or Steel Deck, state if whole or part, and if Wood Deck is laid thereon.					
Angles on upper edge	—	—	—	—	—	© 2020 Lloyd's Register Foundation					
" " Spacing	—	—	—	—	—	007590-007607-0055 1/2					

GENERAL REMARKS—(continued).

WEB-FI

WEB-FI

WEB-FI

BRACK
Web I

BULK

W.T.BI

COL
PARTI
LONGI

Are the
Are the

FLAT P
(U Bar
GARBO

State
thick
way of
B.

TR
CL
DE

PO
SI
F

U

SC

PARTICULARS FOR RECORD in the REGISTER BOOK.—Length of Poop ☒ ft., R.Q.D. ☒ ft., Bridge ☒ ft., Forecastle ☒ ft.
(in feet and tenths). When the Poop is joined to the B.D., this should be distinctly stated ☒

No. and Material of Decks (if Iron or Steel) and whether wholly or partially covered with wood, and No. of tiers of Beams (this information is to be given as it should appear in the Register Book) *one deck, (steel), partially wood sheathed.*
Official No. _____; Signal Letters _____

How are the surfaces preserved from oxidation? Inside *Cement on bottom, and elsewhere.* State if Machinery is fitted aft *Yes.* Outside *Paint.*
Bitumastic solution & Oxide

PARTICULARS OF WATER BALLAST.—State whether the Double bottom is constructed on the cellular system or with girders on floors *None.*

Where Fitted.	*Length. Feet.	Water Capacity. Tons.	Where Fitted.	*Length. Feet.	Water Capacity. Tons.
Double bottom, aft,			Fore peak tank,		
Double bottom, under Engines and Boilers,			After peak tank,		
Double bottom, if under Engines only,			Deep tank, aft,		
Double bottom, if under Boilers only,			Deep tank, forward,		
Double bottom, forward,			Other tanks, if fitted,		
			(If necessary, furnish further information by sketch.)		
Total capacity of double bottom					

* The wells are not to be included in the lengths of the tanks. State whether the above have been tested as required by the Rules _____

Order for Special Survey No. ☒
Date ☒
No. *445* in builder's yard.
DATES of Surveys held while building
1918
Oct 9. 17. 30. Nov 15. Feb 12. May 9. Apr 4. 20. May 28. 29. June 28. Aug 29. Dec 17.
1919
Apr 14. 22. May 4. June 3. 10. 22. July 7. 20. Aug 4. 11. 18. Sept 10. 15. 22. 27. Oct 1. 16.
1920
Jan 27. Feb 4. 11. 16. Mar 11. 24. 31.

Surveyor's Signature *Archd. Murray*