

# Lloyd's Register of Shipping,

(MEIKAI BUILDING)

32, AKASHI-MACHI,

KOBE, 15th. January 1930.

Cert. No. 2337.

This is to Certify that at the request

of Messrs. The Kobe Steel Works Ltd., Kobe.

the Open Hearth Steel ~~Engings-or~~ Castings named below <sup>was</sup>~~were~~ examined and tested at their works on 14th. Nov. 1929 to 13th. Jan. 1930 (4 visits) and found to be as far as could be ascertained, sound and free from defect.

One (1) Stern Foot Casting.

Examined in finished condition.

Drop tests: Dropped from a height of 8 feet on to hard ground, then suspended and hammered without indication of defect.

Test Mark	Tenacity Tons/sq in	Elongation % in 2"	Bend 1" x 1/2" x 120°
B 33090	30.5	32	Good.

This Casting is intended for Mitsubishi Zosen Kaisha.

Nagasaki Yard Nos. 471 to 474 and <sup>has</sup>~~have~~ been stamped as follows:-

Fee Yen 25.00

Expenses „ 1.00

B33090  
LLOYDS  
No. 2337  
13-1-30  
A.W. L.R.

Surveyor to Lloyd's Register.

This Certificate is issued upon the terms of the Rules and Regulations of the Society, which provide that:-

"While the Committee use their best endeavours to ensure that the functions of the Society are properly executed, it is to be understood that neither the Committee nor the Society are under any circumstances whatever to be held responsible for any inaccuracy in any report or certificate issued by the Society or its Surveyors, or in any entry in the Register Book or other publication of the Society or for any error of judgment, default, or negligence of the Surveyors, other Officers or Agents of the Society."

APR 18 1930

Lloyd's Register  
Foundation

007679-007687-0198

Handwritten red marks and numbers at the top left of the page.

Lloyd's Register of Shipping

(MEIKAI BUILDING)

32, AKASHI-MACHI,

KOBE, Japan. January 1930.

Cert. No. 2387.

This is to Certify that at the request

of Messrs. The Kobe Steel Works Ltd., Kobe, Japan, Nov. 1929 to Jan. 1930 (4 visits) examined and found to be as far as could be ascertained, sound and free from defect.

One (1) Stern Post Casting, Examined in finished condition. Prepared from a height of 8 feet on to hard ground. Then expanded and hammered without indication of defect.


Test Mark	Tensile Strength in Tons/sq in	Elongation % in 2"	Bend 1" x 1/2" x 180°
33090	30.8	32	Good.

intended for use as a casting in the hull of a ship. This casting has been stamped as follows:-

33090  
LLOYD'S  
No. 2387  
18-1-30  
L.W. I.R.

Surveyor to Lloyd's Register.

The Rules and Regulations of the Society provide that:— The Committee are under any circumstances whatever to be held responsible for any inaccuracy or error of judgment, default or negligence of the Surveyors, other Officers or Agents of the Society.



Lloyd's Register Foundation