


THE BRITISH CORPORATION FOR THE SURVEY AND REGISTRY OF SHIPPING.

PARTICULARS OF HATCH COAMINGS, WEBS, FORE AND AFTERS, &c.

S.S. "ALICE." OF COPENHAGEN.

| NUMBER OF HATCHWAY, counting from Forward, | No. 1. | 2. | 3. | No. 4. | | |
|--|---|------------------------------------|--|--|----------|---------|
| | FORW. | | | AFT | | |
| DIMENSIONS OF HATCHWAY. | 23'-0" x 15'-11 ³ / ₄ " | 28'-9" x 17'-0" | 21'-0" x 15'-11 ³ / ₄ " | 23'-0" x 15'-11 ³ / ₄ " | | |
| COAMINGS. | Height above Steel Deck, - | 2'-9" | 2'-9" | AFT 3'-10" | | |
| | Thickness— | Sides, - - - | .44 | .44 | .42 | Same as |
| | | Ends, - - - | .44 | .44 | .42 | No. 3. |
| HATCH BEAMS. | Number, - - - | 2 | 5 | 3 | 3 | |
| | Spacing, - - - | 7'-8" | 4'-8 ¹ / ₂ " | 5'-3" | 5'-9" | |
| | Scantling and Sketch, - - | 7" 4x3x.44 18x.38 1" 4x3x.44 | 7" 4x3x.44 13x.3 2 1/2" 1 1/2" x 1/2" HOLLOW. | 7" 4x3x.46 13x.3 2 1/2" 1 1/2" x 1/2" HOLLOW. | Same as | |
| | Bearing Surface of Carriers on Coaming, - - - | 3" | 3" | 3" | No. 3 | |
| FORE AND AFTERS. | Number, - - - | | | | | |
| | Spacing, - - - | / | / | / | / | |
| | Unsupported Lengths, - - | / | / | / | / | |
| | Scantlings,* - - - | / | / | / | / | |
| Bearing Surface at Ends, - | / | / | / | / | | |
| * If of wood, state if iron shod at ends, and give dimensions below Hatches. | | | | | | |
| HATCH COVERS. | Thickness, - - - | 2 1/2" | 2 1/2" | 2 1/2" | 2 1/2" | |
| | How Fitted, - - - | THINWARTSHIPS. | LONG 4Y. | Long 4Y. | Long 4Y. | |

* Surveyors are to note that it is recommended that all wood Fore and Afters be iron shod.



© 2021

Lloyd's Register
Foundation

008124-008136-0115

33 ALICE



© 2021

Lloyd's Register
Foundation