

With or Without Disconnected Erections.

STEEL STEAMER.

Received at London Office THU. 19. 11. 1917

Date of completion of report 18. 4. 1917. Port of Hull
Survey held at Hull & Selby Date, First Survey 9. 12. 16 Last Survey 16. 7. 1917
No. 30,054

On the (State if Single, Twin, or Triple Screw) Single Screw Trawler "John Yule"
Tonnage under Tonnage Deck... 284.4
Do. between Tonnage Dk. and 3rd and 4th Dk. ...
Total under Upper Dk. ...
Do. of Poop ...
Do. of R.O. Dk. ...
Do. of Bridge House ...
Do. of Forecastle ...
Do. of Houses on Dk. ...
Do. of excess of Hatchways ...
Do. above Crown of ...
Engine Room ...
Gross Tonnage 324.43
Less Crew Space ...
Less above Crown of ...
Engine Room ...
Tonnage for Fees ...
Engine Room ...
Navigation Spaces ...
Net Tonnage 132.64
Destined Voyage ADMIRALTY SERVICE If Surveyed while Building Afloat, or in Dry Dock YES

CLASS +100 A1
STEAM TRAWLER
Breadth (greatest moulded) 23.62
Depth, at middle of length from top of keel to top of upper deck beams at side 13.50
Transverse Number 34.12
Length on deck from fore part of stem to after part of stern post 138.33
Longitudinal Number 5134.8
Depth "d," at middle of length (See Secs. 2 & 13) 12.16
Proportions—Depths to Length—Upper Deck Beam at side to top of keel 10.24
" " Long Bridge Deck Beam at side to top of keel
Master
Year of appointment
Built at SELBY
When built 1917 Launched 26-3-14
By whom built COCHRANE & SONS, LTD.
Owners BRITISH ADMIRALTY
Managers
Residence
Port belonging to

Length on Deck 138.5
Breadth 23.15
Depth 12.8
Moulded depth, ft. 13 ins. 6 To Bridge Dk. Round of Upper Dk. Beam, Actual 8 ins.
No. of Decks with flat laid ONE
No. of Tiers of Beams ONE

FRAMING.				PILLARS.			
ME, Angles, or Bars amidships	Inches in Ship.	Inches in Ship.	Inches in Ship.	PILLARS, In 'tween Deck, size and spacing	Inches in Ship.	Inches in Ship.	Inches in Ship.
in peaks	4	3	7/16	" " Hold	26"	8	3"
in way of Double Bottoms at Solid Floors	4	3	7/16	" " Quarter 'tween Dks.,			
" " at intermdt. Bkts.				" " in Hold	46	ARRANGED	
ing of Frames from centre to centre amidships	19	TO 21	19	TO 21			
" " " from 1/2 length to Collision bulkhead				SEE PROFILE			
" " " in peaks	2 1/2	2 1/2	25	2 1/2	2 1/2	25	
ERSED FRAME, Angles	DOUBLE IN	E&B SPACES					
in way of Double Bottoms at Solid Floors							
" " at intermdt. Bkts.							
ING, depth of girder	16	37	16	37			
ORS, depth and thickness of Floor Plate at mid-line for 1/2 length amidships	E 50	8 43	E 50	8 43			
in way of Engine and Boiler Spaces							
thickness at the ends of vessel		31		31			
depth at 1/2 the half breadth, as per Rule							
height extended at the Bilges	STRAIGHT ACROSS						
ORS in Cell. Double Bottoms							
state if flanged (top & bottom)							
Spacing of Solid floors							
RE GIRDER, in Dbl. bottom, dpth. & thcknss.							
" Angles, Top							
" " Bottom							
" " to Floors							
Brackets at intermdt. frmng., wdth & thknss							
GIRDERS, number on each side & thickness							
" state if flanged (top and bottom)							
" Angles (top and bottom)							
" " to Floors							
IN PLATE, depth (exclusive of flange) and thickness							
" Angle to Outside Plating							
" " Floors							
Brackets at intermdt. frmng., wdth & thknss							
Height of Outside Brackets above at bilge							
BOTTOM PLATING, breadth and thickness of Middle Line Strake							
" " in Engine and Boiler space							
" " Remainder in Holds							
Upper Deck, Single Angle, Bulb, Angle, Plate, Tee Bulb, or Channel	5	3	50	5	3	50	
In way of Long Bridge							
Spacing							
Second Deck, Single Angle, Bulb, Angle, Plate, Tee Bulb, or Channel							
Spacing							
Third and Fourth Deck, Single Angle, Bulb, Angle, Plate, Tee Bulb, or Channel							
Angles on upper edge							
Spacing							
BEAMS, Poop Deck, Angle, Bulb Angle, Plate, Tee Bulb, or Channel							
Angles on upper edge							
Spacing							
BEAMS, Bridge Deck, Angle, Bulb Angle, Plate, Tee Bulb, or Channel							
Angles on upper edge							
Spacing							
BEAMS, Forecastle Deck, Angle, Bulb Angle, Plate, Tee Bulb, or Channel	4	3	30	4	3	30	
Angles on upper edge							
Spacing							
Upper Deck Stringer Plate, br'dth & thickness (clear of Bridge)	50	30	31	50	30	31	
" " " " (in way of Bridge)	3x3	37	3x3	37			
" " " " Angle (clear of Bridge)	8	37	8	37			
" " " " Tie Plate at sides of Hatchways	35						
" " " " Deck * Iron or Steel, for E 9 B lng.							
" " " " Thickness (clear of Bridge)							
" " " " (in way of Bridge)							
" " " " Wood Deck. Material & thickness P. PINE	5x3		5x3				
Second Deck Stringer Plate, br'dth & thickness							
" Angles on ditto, No.							
" Tie Plates outside Hatchways							
" Deck * Iron or Steel, for lng.							
" Wood Deck. Material & thickness							
Third Deck Stringer Plate, br'dth & thickness							
" Angles on ditto, No.							
" Tie Plates, outside Hatchways							
" Deck * Material and thickness							
Fourth and Fifth Deck Stringer Plate, breadth & thickness							
" " Angles on ditto, No.							
" " " Tie Plates outside Hatchways							
" " " Deck. Material & thickness							
Poop Deck Stringer Plate, breadth & thickness							
" Angle on ditto							
" Tie Plates							
" Deck. Material and thickness							
Bridge Deck Stringer Plate, br'dth & thickness							
" Angle on ditto							
" Tie Plates							
" Deck. Material and thickness							
Forecastle Deck Stringer Plate, br'dth & th'kns	31		31				
" Angle on ditto							
" Tie Plates							
" Deck. Material and thickness STEEL	25		25				

Form No. 1A.

The Survivors are requested not to write on or

GENERAL REMARKS—(continued).

PARTICULARS FOR RECORD in the REGISTER BOOK.—Length of Poop ✓ ft., R.Q.D. 74.66 ft., Bridge ✓ ft., Forecastle 19.33 ft. (in feet and tenths). When the Poop is joined to the B.D., this should be distinctly stated

No. and Material of Decks (if Iron or Steel) and whether wholly or partially covered with wood, and No. of tiers of Beams (this information is to be given *per cent* should appear in the Register Book) 104 *line of*

Official No.; Signal Letters State if Machinery is fitted aft *yes*
How are the surfaces preserved from oxidation? Inside *CEMENT & PAINT, (BUNKERS BITUMASTIC)* Outside *PAINT.*

PARTICULARS OF WATER BALLAST.—State whether the Double bottom is constructed on the cellular system or with girders on floors.

Where Fitted.	*Length. Feet.	Water Capacity. Tons.
Double bottom, aft,		
Double bottom, under Engines and Boilers,		
Double bottom, if under Engines only,		
Double bottom, if under Boilers only,		
Double bottom, forward,		
Total capacity of double bottom		

Where Fitted.	*Length. Feet.	Water Capacity. Tons.
Fore peak tank,		
After peak tank,		
Deep tank, aft,		
Deep tank, forward,		
Other tanks, if fitted,		
(If necessary, furnish further information by sketch.)		

Order for Special Survey No.

Date _____

No. **803**. in builder's yard.

DATES of Surveys
held while building

1916: Dec 9. 1917: Jan 2 10. 15 Feb 2. 8. 15 23. 28. Mar 9. 14. 23 28 Apr 5 13 17
May 2. 9. Jun 25 Jul 7. 13. 16

Total No. of Visits *23* *PEP*

Surveyor's Signature *W.A. Roberts, P. Fitzgerald*