

# Lloyd's Register of Shipping.

## SURVEYS FOR FREEBOARD.

(COMPUTATION FOR STEAMER, SAILING SHIP, TANKER.)

Enslaved 21472<sup>A</sup>

Ship's Name <b>T.R.V. 1.</b>	Official Number ✓	Nationality and Port of Registry ✓	Gross Tonnage ✓	Date of Build <b>1942</b>	Port of Survey <b>Grimsey</b>
Moulded Dimensions: Length <b>96.75</b> Breadth <b>20.83</b> Depth <b>9'0" 9'-1" amidship</b> To centre of rudder stock = <b>97.25</b>					Date of Survey <b>26/3.14 @ 18/6/42</b>
Moulded displacement at moulded draught = 85 per cent. of moulded depth <b>322</b> tons					Surveyor's Signature <b>J. L. Palmer</b>
Coefficient of fineness for use with Tables <b>.721</b>					Particulars of Classification <b>100A1</b> "for Government Service" (Contemplated)

Depth for Freeboard (D).	Depth correction.	Round of Beam correction.
Moulded depth ... <b>9.08</b>	(a) Where D is greater than Table depth <b>96.75</b> (D - Table depth) $\frac{R}{15} = \frac{9.11 - 9.08}{15} = \frac{.03}{15} = +.002$	Moulded Breadth (B) <b>20.83</b>
Stringer plate ... <b>.025</b>	(b) Where D is less than Table depth (if allowed) (Table depth - D) $\frac{R}{130} = \frac{9.11 - 9.08}{130} = \frac{.03}{130} = +.00023$	Standard Round of Beam = $\frac{B \times 12}{50} = \frac{20.83 \times 12}{50} = 5.00$
Sheathing on exposed deck $T \left( \frac{L-S}{L} \right) =$	✓	Ship's Round of Beam = <b>5.00</b>
Depth for Freeboard (D) = <b>9.11</b> <b>9.085</b>	If restricted by superstructures	Difference <b>Nil</b>
		Restricted to
		Correction = $\frac{\text{Diff}^2}{4} \times \left( 1 - \frac{S_1}{L} \right) = \text{Nil.}$

## DEDUCTION FOR SUPERSTRUCTURES.

	Mean Covered Length (S)	Equivalent Enclosed Length (S <sub>1</sub> )	Height	Height Correction	Effective Length (E)	
Poop enclosed <b>to centre of rudder stock</b>	<b>43.67</b>	<b>43.67</b>	<b>7.0</b>	✓	<b>43.67</b>	Standard Height of Superstructure <b>6.0</b>
.. overhang						" " R.Q.D. ✓
R.Q.D. enclosed						Deduction for complete superstructure <b>15.73</b>
.. overhang						Percentage covered $\frac{S}{L} = \frac{62.90}{62.00} = 1.0161$
Bridge enclosed						" " $\frac{S_1}{L} = \frac{62.00}{62.00} = 1.0000$
.. overhang aft						" " $\frac{E}{L} = \frac{62.00}{62.00} = 1.0000$
.. overhang forward						Percentage from Table, Line A. <b>0.6</b> <b>49.40</b>
Fore enclosed	<b>15.75</b>	<b>15.75</b>	<b>6.5</b>	✓	<b>15.75</b>	(corrected for absence of forecastle (if required)) ✓
.. overhang	<b>1.75</b>	<b>.88</b>			<b>.88</b>	Percentage from Table, Line B. ✓
Trunk aft						(corrected for absence of forecastle (if required)) ✓
.. forward						Interpolation for bridge less than 2L (if required) ✓
Tonnage opening aft						Deduction = <b>15.73 x .4940 = 7.77</b>
.. forward						
Total	<b>61.17</b>	<b>66.30</b>			<b>60.30</b>	

## SHEER CORRECTION.

Station	Standard Ordinate	S	M	Product	Actual Ordinate	Effective Ordinate	S	M	Product	
A.P. ...	<b>19.73</b>	1		<b>19.73</b>	<b>5.00</b>	<b>5.00</b>	1		<b>5.00</b>	Mean actual sheer aft = Mean standard sheer aft = } Deficient
1/2 L from A.P. ...	<b>8.88</b>	4		<b>35.52</b>	<b>1.25</b>	<b>1.25</b>	4		<b>5.00</b>	
1/4 L " ...	<b>2.15</b>	2		<b>4.30</b>	<b>-.75</b>	<b>-.75</b>	2		<b>-1.50</b>	Mean actual sheer forward = Mean standard sheer forward = } Deficient
Amidships ...		4					4			
1/2 L from F.P. ...	<b>4.30</b>	2		<b>8.60</b>	<b>4.00</b>	<b>4.00</b>	2		<b>8.00</b>	Length of enclosed superstructure forward of amidships = " " aft of " = } Deficient
1/4 L " ...	<b>5.55</b>	4		<b>22.20</b>	<b>13.00</b>	<b>13.00</b>	4		<b>52.00</b>	
F.P. ...	<b>17.36</b>	1		<b>17.36</b>	<b>26.00</b>	<b>26.00</b>	1		<b>26.00</b>	
Total				<b>178.58</b>					<b>90.50</b>	

Correction =  $\frac{\text{Difference between sums of products}}{18} \left( \frac{75 - S}{2L} \right) = \frac{87.08}{18} \left( \frac{75 - 31.00}{2L} \right) = +2.13"$   
If limited on account of midship superstructure.

Deduction for Tropical Freeboard.	Deduction for Fresh Water.	TABULAR FREEBOARD corrected for Fresh Deck (if required)	
Addition for Winter and Winter North Atlantic Freeboard.	Displacement in salt water at summer load water line	Correction for coefficient	<b>7.3</b> <b>9.50</b> <b>10.02</b>
Depth to Freeboard Deck = <b>9.11</b>	$\Delta =$ <b>367</b>	Depth Correction ...	<b>1.96</b>
Summer freeboard = <b>.52</b>	Tons per inch immersion at summer load water line	Deduction for superstructures ...	<b>7.77</b>
Moulded draught (d) = <b>8.59</b>	$T =$ <b>4.28</b>	Sheer correction ...	<b>2.13</b>
Deduction for Tropical freeboard and addition for Winter freeboard = $\frac{d}{4}$ inches = <b>2.14 = 2 1/4"</b>	Deduction = $\frac{\Delta}{40T}$ inches = <b>2.14</b>	Round of Beam correction ...	<b>-</b>
Addition for Winter North Atlantic Freeboard (if required) =	<b>- 2 1/4"</b>	Correction for Thickness of Deck amidships ...	<b>-</b>
		Other corrections, scantlings, etc. ...	<b>-</b>
		Summer Freeboard = <b>6.34</b>	

## SUMMER FREEBOARD amidships from Centre of Disc to top of Deck Line, Wood, Steel, Deck:

Tropical Fresh Water Line above Centre of Disc	...	...	...	...	...
Fresh Water Line	...	...	...	...	...
Tropical Line	...	...	...	...	...
Winter Line	below	...	...	...	...
Winter North Atlantic Line	...	...	...	...	...

13. JUL 1942

© 202 and only when engaged on Government Service

Lloyd's Register Foundation

RECEIVED 14/8/42



A new form should be prepared if any alterations that affect the freeboard have been made. If no such alterations have been made, the Surveyor should endorse the form on this side with his signature and the date.

Trade of ship

Names of sister ships *"T.R.V. 2,"* *Wren Rowledge Ironworks Co Ltd. Yd No S. 605.*

Builder's name and yard number *J. S. Waterson (Gainsborough) Ltd. No 1527.*

Owners *The Admiralty.*

Fee £ *4-0-0*



© 2021

Lloyd's Register  
Foundation