

LLOYD'S REGISTER

Recd. 22 DEC. 1925

LLOYD'S REGISTER OF SHIPPING

AND

MEIKAI BUILDING

LONDON

No. 32, AKASHI MACHI,

KOBE, 26th November, 1925.

TELEGRAMS: "REGISTER" KOBE

TELEPHONE: 2530 SANNOMIYA

The Secretary,

Transverse No **LONDON**

Depth "a" 18'8"

Framing: Tab. No.

Description Bulk angle frame

Dear Sir,

Longitudinal No. s/s "TSUKUSHI MARU" - Kobe Report No.4985

In reply to the classing letter of the above

steamer dated October 30th, 1925, I have to state that

the thickness of the bridge deck plating, as fitted, is

30", the butts of the bridge side plating are treble

riveted instead of double riveted as erroneously stated

in first entry report, and in accordance with the approved

plans; the spacing of the solid floors is, 30" under en-

gines, 27" forward of 3/5 length, 90" elsewhere, and all

in accordance with the Rules & approved plans.

+ 100 A1 (SU) I am, dear Sir,

Yours faithfully,

H.D. Buchanan

1 dk (80)

all D.B. 236 4765, FR

FK, 17&H, 14 Am, 14y

B 60' F 88'



© 1919

DEC 23 1925

Lloyd's Register Foundation

008608-008617-0352

the bridge side plating is as approved and was held in accordance with the approved plans

LLOYD'S REGISTER
LONDON

LLOYD'S REGISTER OF SHIPPING

MEKKA BUILDING

No. 22, AKASHI MACHI

KOBE

20th November, 1925.

The Secretary,

LONDON

Dear Sir,

3's "TAIKUNSHI MARU" - Kobe Report No. 4987

In reply to the classing letter of the above steamer dated October 30th, 1925, I have to state that the thickness of the bridge deck plating as fitted is 30", the butts of the bridge side plating are treble riveted instead of double riveted as erroneously stated in first entry report, and in accordance with the approved plans, the spacing of the solid floors is 30" under main, 27" forward of 3/4 length, 30" elsewhere, and all in accordance with the Rules & approved plans.

I am, dear Sir,

Yours faithfully,

Referred to the Chief Ship Surveyor,

RAM,

22 DEC 1925

Handwritten signatures and initials



© 2019

Lloyd's Register Foundation