

REPORT ON ELECTRIC FITTINGS.

(OTHER THAN FOR THE PROPULSION OF THE VESSEL)

Received at London Office 28 JAN 1926

Date of writing Report 15 January 1926 When handed in at Local Office

Port of AMSTERDAM

No. in Survey held at AMSTERDAM

Date, First Survey 20 Sept 25 Last Survey 15 January 1926

Reg. Book.

35230 on the Steel Screw Steamer "TJISAROE" (Number of Visits 4)

Tons Gross 7089

Net 4394

Built at Amsterdam

By whom built Ned. Scheepsbouw My.

Yard No. 179

When built 1926

Owners Java-China-Japan Lijn

Port belonging to Batavia

Electric Light Installation fitted by

Mijnssen & Co.

Contract No.

When fitted 1926

System of Distribution

Direct current Double wire System

Pressure of supply for Lighting

110

volts, Heating

volts, Power

110

volts.

Direct or Alternating Current, Lighting

Direct current

Power

If alternating current system, state frequency of periods per second

Has the Automatic Governor been tested and found efficient when the whole load is suddenly thrown on or off Yes

Generators, do they comply with the requirements regarding overload Yes

are they compound wound Yes

are they over compounded 5 per cent. Yes

if not compound wound state distance between each generator

Where more than one generator is fitted are they arranged to run in parallel or Separately is an adjustable regulating resistance fitted in series with each shunt field Yes

Are all terminals accessible and clearly marked Yes

are they so spaced or shielded that they cannot be accidentally earthed,

or short circuited Yes

Are the lubricating arrangements of the generators as per Rule Yes

Position of Generators

Engine room

is the ventilation in way of the generators satisfactory Yes

are they clear of all inflammable material Yes

if situated near unprotected woodwork or other combustible material, state distance of same horizontally from or vertically above the generators

and are the generators protected from mechanical injury and damage from water, steam or oil Yes

are their axis of rotation fore and aft Yes

Earthing, are the bedplates and frames of the generating plant efficiently earthed Yes

are the prime movers and

their respective generators in metallic contact Yes

Main Switch Boards, where placed

Engine room

If the generators and main switchboard are not placed in the same compartment, is each generator provided with a fuse on each insulated pole as near as possible to the terminals of the generator, additional to that provided on the main switchboard Same compartment

Switchboards, are they placed in accessible positions, free from inflammable gases and acid fumes Yes

are they protected from mechanical injury and damage from water, steam or oil Yes, if situated near unprotected

woodwork or other combustible material, state distance of same horizontally from or vertically above the switchboards and

are they constructed wholly of durable, incombustible non-absorbent materials Yes, is all insulation of high dielectric strength and of

permanently high insulation resistance Yes, if semi-insulating material is used, are all conducting parts connected to one pole

insulated from the slab with mica or micamite and the slab similarly insulated from its framework and is the

frame effectively earthed Yes. Are the following fittings as per Rule, viz.:— spacing or shielding of live parts

Yes, accessibility of all parts Yes, absence of fuses on back of board Yes, proportion of omnibus

bars Yes, individual fuses to voltmeter, pilot or earth lamp Yes, connections of switches Yes

Main Switchgear, description of switchgear for each generator and each outgoing circuit, and arrangement of equalizer switches

Main circuit double pole, main fuses double pole, main distribution double pole, omnibus omnibus bars as per Rule


Instruments on main switchboard 2 ammeters 2 voltmeters

synchronising device for paralleling purposes.

Earth Testing, state what means are provided at the main switchboard for indicating the state of the insulation of the system 2 indicator lamps

Switches, Circuit Breakers and Fusible Cut-outs, do these comply with the requirements of the Rules Yes

Section and Distribution Boards, is the construction, protection, insulation, material, and position of these as per rule Yes



© 2021

Lloyd's Register Foundation

Insulation of Cables, state type of cables, single or twin *Single* are the cables insulated and protected as per Tables III or IV of the Rules *Yes*
Fall of Pressure, state maximum between bus bars and any point of the installation under maximum load *Not exceeding 1 1/2 lbs*
Cable Sockets and other connections, are the ends of all cables having a sectional area of 0.007 square inch and above provided with soldering sockets *Yes*

Paper Insulated Cables. If cables are paper covered, is the dielectric at the exposed ends of the conductor protected from moisture by being suitably sealed with insulating compound *Yes*

Cable Runs, are the cables fixed as far as possible in accessible positions not exposed to drip or accumulation of water or oil, or to high temperature from boilers, steam pipes, uptakes or other hot objects, or to avoidable risk of mechanical damage *Yes*

Support and Protection of Cables, state how the cables are supported and protected *Lead cables supported by lugs*
Clips and screws, wire covered sheet iron armour, complete galvanised
If cables are run in wood casings, are the casings and caps secured by screws *Yes*, are the cap screws of brass *and paper*, are the cables run in separate grooves *Yes*. If armoured and lead covered cables are secured by metal clips, are the clips spaced as per Table VI *Yes*

Refrigerated Chambers, if lights are fitted, are the cables and fittings in accordance with the special requirements *Yes*

Joints in Cables, state if any, and how made, insulated, and protected *No joints*

Watertight Glands and Deck Tubes, are all cables passing through decks and watertight bulkheads provided with deck tubes or watertight glands *Yes*

Bushes in Beams and Non-watertight Positions, where unarmoured cables pass through beams and non-watertight partitions, are the holes efficiently bushed *Yes* state the material of which the bushes are made *Lead*

Earthing Connections, state what earthing connections are fitted and their respective sectional areas *No earthing connections*
are their connections made as per Rule

Alternative Lighting, are the groups of lights in the propelling machinery space arranged as per Rule *Yes*

Emergency Supply, state position and method of control of the emergency supply and how the generator is driven *Yes*

Navigation Lamps, are these separately wired *Yes*, controlled by separate switch and separate fuses *Yes*
are the fuses double pole *Yes*, are the switches and fuses grouped in a position accessible only to the officers on watch *Yes*
has each navigation lamp an automatic indicator as per Rule *Yes*, are separate screens provided for the use of oil and electric side lights *Yes*
are separate oil lanterns provided for the mast head lights and side lights *Yes*

Fittings, are all fittings on weather decks, in storerooms and engine rooms and wherever exposed to drip or condensed moisture, watertight *Yes*
are any fittings placed in spaces in which goods are liable to be stacked in close proximity to them; if so, how are they protected *protected by iron*
Case
are any fittings placed in spaces where inflammable or explosive dust or gases are liable to be present, if so, how are they protected *No*
how are the cables led

where are the controlling switches situated *Yes*

Searchlight Lamps, No. of *Yes*, whether fixed or portable *Yes*, are their fittings as per Rule *Yes*

Arc Lamps, other than searchlight lamps, No. of *Yes*, are their live parts insulated from the frame or case *Yes*, are their fittings as per Rule *Yes*

Motors, are their working parts readily accessible *Yes*, are the coils self-contained and readily removable for replacement *Yes*
are the brushes, brush holders, terminals and lubricating arrangements as per Rule *Yes*, are the motors placed in well-ventilated compartments in which inflammable gases cannot accumulate and clear of all inflammable material *Yes*
are they protected from mechanical injury and damage from water, steam or oil *Yes*, are their axis of rotation fore and aft *Yes*
if situated near unprotected woodwork or other combustible material, are the motors of the totally enclosed, pipe ventilated, forced draught, drip or flame proof type *Yes*
if not of this type, state distance of the combustible material horizontally or vertically above the motors *Yes* and *Yes*

Control Gear and Resistances, are the generator field and motor speed regulators, starters and controllers constructed as per Rule *Yes*

Lightning Conductors, where lightning conductors are required, are these fitted as per Rule *None*

Ships carrying Oil having a Flash Point less than 150° F. Have the special requirements of the Rules been complied with regarding switches, joint boxes, section and distribution boards, protection of cables, method of distribution, lead of cables, lights and fittings *Yes*

If portable lamps for use in dangerous spaces are supplied, are they of a type approved by the Home Office *Yes*

PARTICULARS OF GENERATING PLANT.

DESCRIPTION OF GENERATOR.	No. of	RATED AT				DRIVEN BY.	WHERE DRIVEN BY AN INTERNAL COMBUSTION ENGINE.	
		Kilowatts.	Volts.	Ampères.	Revs. per Min.		Fuel Used.	Flash Point of Fuel.
MAIN	1	55	110	500	350	Steam		
AUXILIARY	1	33	110	300	350	Do		
EMERGENCY								
ROTARY TRANSFORMER								

LIGHTING AND HEATING CONDUCTORS.

Ref. No.	DESCRIPTION.	No. of Conductors.	Effective Area of each Conductor. Sq. Ins.	COMPOSITION OF STRAND.		Total Maximum Current. Amperes.	Approximate Length. (Lead and Return.) Feet.	Insulated with	HOW PROTECTED.
				No.	Diameter.				
	MAIN GENERATOR...	2	4x 7/16	0.0713	0.089	500	40	rubber	Shander, galvanised
	AUXILIARY GENERATOR	2	4x 7/16	0.0713	0.089	300	40		Do.
	EMERGENCY GENERATOR								
	ROTARY TRANSFORMER...								
	AUXILIARY SWITCHBOARDS								
	ENGINE ROOM	2	4x 7/16	0.0713	0.089	10	40		
	BOILER ROOM	2	4x 7/16	0.0713	0.089	5	120		
	Navigation	2	4x 7/16	0.0713	0.089	6	240		
	Boiler, both	2	4x 7/16	0.0713	0.089	14	180		
	Boiler, both m.s.	2	4x 7/16	0.0713	0.089	15	180		
	Shelter, both	2	4x 7/16	0.0713	0.089	8	420		
	on aft	2	4x 7/16	0.0713	0.089	10	300		
	Mid deck	2	4x 7/16	0.0713	0.089	16	200		
	Fore m.s.	2	4x 7/16	0.0713	0.089	8	185		
	on O.S.	2	4x 7/16	0.0713	0.089	4	300		
	WIRELESS	2	4x 7/16	0.0713	0.089	25	220		
	SEARCHLIGHT	2	5/16	0.024	0.054	3	240		
	MASTHEAD LIGHT...	2	5/16	0.024	0.054	3	60		
	SIDE LIGHTS	2	5/16	0.024	0.054	3	60		
	COMPASS LIGHTS	2	5/16	0.024	0.054	3	60		
	POOP LIGHTS								
	CARGO LIGHTS	2	4x 7/16	0.0713	0.089	25	250		
	ARC LAMPS								
	HEATERS								

MOTOR CONDUCTORS.

Ref. No.	DESCRIPTION.	No. of Motors.	Effective Area of each Conductor. Sq. Ins.	COMPOSITION OF STRAND.		Total Maximum Current. Amperes.	Approximate Length. (Lead and Return.) Feet.	Insulated with	HOW PROTECTED.
				No.	Diameter.				
	BALLAST PUMP								
	MAIN BILGE LINE PUMPS								
	GENERAL SERVICE PUMP								
	EMERGENCY BILGE PUMP								
	SANITARY PUMP	2	4x 7/16	0.0713	0.089	60	90		
	CIRC. SEA WATER PUMPS								
	CIRC. FRESH WATER PUMPS								
	AIR COMPRESSOR								
	FRESH WATER PUMP								
	ENGINE TURNING GEAR								
	ENGINE REVERSING GEAR								
	LUBRICATING OIL PUMPS								
	OIL FUEL TRANSFER PUMP								
	WINDLASS								
	WINCHES, FORWARD								
	WINCHES, AFT								
	STEERING GEAR								
	WORKSHOP MOTOR	2	4x 7/16	0.0713	0.089	60	90		
	VENTILATING FAN	2	4x 7/16	0.0713	0.089	65	365		
	for	2	4x 7/16	0.0713	0.089	65	300		
	sid.	2	4x 7/16	0.0713	0.089	65	320		
	for fan	2	4x 7/16	0.0713	0.089	40	120		
	9.5	2	4x 7/16	0.0713	0.089	40	120		
	Clayton	2	4x 7/16	0.0713	0.089	80	150		



© 2021

Lloyd's Register Foundation

All Conductors are of annealed copper conforming to British Standard Specification No. 7.

The Insulated Conductors are guaranteed to withstand the immersion and resistance tests specified in the Rules.

The foregoing is a correct description.



[Signature]

Electrical Engineers.

Date *Jan 20th 1926*

COMPASSES.

Distance between electric generators or motors and standard compass *100 ft*

Distance between electric generators or motors and steering compass *100 ft*

The nearest cables to the compasses are as follows:—

A cable carrying *10* Ampères *20* feet from standard compass *25* feet from steering compass.

A cable carrying Ampères feet from standard compass feet from steering compass.

A cable carrying Ampères feet from standard compass feet from steering compass.

Have the compasses been adjusted with and without the electric installation at work at full power *Yes*

Has the effect of switching on and off circuits, motors and other electro-magnetic apparatus within the vicinity of the compasses been noted *Yes*

The maximum deviation due to electric currents was found to be *2 1/2* degrees on *←* course in the case of the standard compass, and *←* degrees on *←* course in the case of the steering compass.

NEDERLANDSCHE SCHEEPSBOUW-MAATSCHAPPIJ

[Signature]

Builder's Signature.

Date

Is this installation a duplicate of a previous case *←* If so, state name of vessel *←*

General Remarks (State quality of workmanship, opinions as to class, &c.)

The installation has been fitted in accordance with the Rules, workmanship good. The whole has been tested under full working conditions and found good and efficient.

It is submitted that
this vessel is eligible for
THE RECORD. Elec. light.

[Signature]
4/2/26

Total Capacity of Generators *88* Kilowatts

The amount of Fee ... *£ 340.80* :
Travelling Expenses (if any) £ :
When applied for, 19...
When received, *29.1.1926*

[Signature]
Surveyor to Lloyd's Register of Shipping.

Committee's Minute

Assigned

Im 24. Transfer.
(The Surveyors are requested not to write on or below the space for Committee's Minute.)



© 2021

Lloyd's Register
Foundation