

Dear Sir,

U.S.S.R. Ice Breaker "SEDOV".
(2531 x 36 11)

m 236

shipment & free

VESSEL'S NAME S. S. "GEORGY SEDOV"
(EX. BEOTHIC.)Report ANTWERP No. 25617

THICKNESSES OF PLATING ascertained by drilling, and comparison of same with the original thicknesses.

The thicknesses are in DECIMALS of an inch.

STRAKE.	AMIDSHIP.						FORWARD.						AFT.						REMARKS.
	Original Thickness.	Thickness by drilling.		Diminution if any.		Original Thickness.	Thickness by drilling.		Diminution if any.		Original Thickness.	Thickness by drilling.		Diminution if any.					
		Port.	Std.	Port.	Std.		Port.	Std.	Port.	Std.		Port.	Std.	Port.	Std.	Port.	Std.		
WELTER SHEER STRAKE.	J	.45	.48	.48	-	-	.40	.44	.	.	-	Ⓡ	Ⓡ	-	-	PLATES Ⓡ were marked for renewal in Owner's specification and were not drill tested before renewal. J.M.			
Strake below	H	.45	.44	Ⓡ	+	-	.38	.38	.	.	-	Ⓡ	Ⓡ	-	-				
SHEER STRAKE	G	.60	.63	Ⓡ	-	-	.40	.56	.56	-	-	.40	.41	.41	+				
st Strake below	F	1.00	.87	Ⓡ	.13	-	1.20	1.00	1.02	.20	.18	.75	.70	.71	.05		.04		
nd "	E	1.00	Ⓡ	Ⓡ	-	-	1.25	1.00	1.00	.25	.25	.75	.63	.71	.12		.04		
rd "	D	.50	Ⓡ	.63	-	-	1.25	1.00	.98	.25	.27	.75	.63	.63	.12		.12		
4th "	C	.50	Ⓡ	Ⓡ	-	-	1.25	STEALER	-	-	-	.55	.48	.50	.07		.05		
5th "	B	.50	Ⓡ	Ⓡ	-	-	1.20	.93	.92	.27	.28	.55	Ⓡ	Ⓡ	-		-		
6th "	A	.55	Ⓡ	Ⓡ	-	-	1.20	.94	.92	.26	.28	.60	Ⓡ	Ⓡ	-		-		
7th "	KEEL	.70	Ⓡ	Ⓡ	-	-	1.10	Ⓡ	-	-	-	.60	Ⓡ	-	-		-		
8th "																			
9th "																			
10th "																			
11th "																			
12th "																			

Drillings at ends made in the vicinity of the peak bulkheads.

008711 - 008719 - 0091

TENS NOT FITTED