

# Lloyd's Register of Shipping.

## SURVEYS FOR FREEBOARD.

(COMPUTATION FOR STEAMER, SAILING SHIP, TANKER.)

Ship's Name <b>KENRYU. MARU.</b>	Official Number	Nationality and Port of Registry <b>JAPAN.</b> <b>KOBE.</b>	Gross Tonnage	Date of Build <b>/951.</b>	Port of Survey
Moulded Dimensions: Length <b>115.000</b> Breadth <b>16.500</b> Depth <b>9.016</b>					Date of Survey <b>3-10-51</b>
Moulded displacement at moulded draught = 85 per cent. of moulded depth _____ tons					Surveyor's Signature
Coefficient of fineness for use with Tables <b>.737</b>					Particulars of Classification <b>+100 A1</b> <b>conformable</b>

DEPTH FOR FREEBOARD (D).	DEPTH CORRECTION.	ROUND OF BEAM CORRECTION.
Moulded depth ... ..	(a) Where D is greater than Table depth (D—Table depth) R = <b>+ 330. mfm.</b>	Moulded Breadth (B)
Stringer plate ... ..	(b) Where D is less than Table depth (if allowed) (Table depth—D) R = <b>✓</b>	Standard Round of Beam = $\frac{B \times 12}{50} =$
Sheathing on exposed deck $T \left( \frac{L-S}{L} \right) =$	If restricted by superstructures <b>✓</b>	Ship's Round of Beam =
Depth for Freeboard (D) = <b>9.032.</b>		Difference
		Restricted to
		Correction = $\frac{\text{Diff.}}{4} \times \left( 1 - \frac{S_1}{L} \right) = \text{Nil.}$

## DEDUCTION FOR SUPERSTRUCTURES.

	Mean Covered Length (S)	Equivalent Enclosed Length (S <sub>1</sub> )	Height	Height Correction	Effective Length (E)
Poop enclosed ... ..					
" overhang ... ..					
R.Q.D. enclosed ... ..					
" overhang ... ..					
Bridge enclosed ... ..					
" overhang aft ... ..					
" overhang forward ... ..					
F'cle enclosed ... ..					
" overhang ... ..					
Trunk aft ... ..					
" forward ... ..					
Tonnage opening aft ... ..					
" " forward ... ..					
Total ... ..	<b>58.270</b>	<b>57.658.</b>			<b>57.658.</b>

Standard Height of Superstructure \_\_\_\_\_  
" " R.Q.D. \_\_\_\_\_

Deduction for complete superstructure **1028. ✓**

Percentage covered  $\frac{S}{L} = 50.67.$

" "  $\frac{S_1}{L} = 50.14.$

" "  $\frac{E}{L} = 69.33. ✓$

Percentage from Table, Line A, **TIMBER.** **69.33. ✓**  
(corrected for absence of forecastle (if required))

Percentage from Table, Line B. **—**  
(corrected for absence of forecastle (if required)) **—**

Interpolation for bridge less than .2L (if required) **—**

Deduction = **1028. + 6933. = 713 mfm. ✓**

## SHEER CORRECTION.

Station	Standard Ordinate	S	Product	Actual Ordinate	Effective Ordinate	S	Product
A.P. ... ..		1				1	
$\frac{1}{2}L$ from A.P. ... ..		4				4	
$\frac{2}{3}L$ " ... ..		2				2	
Amidships ... ..		4				4	
$\frac{2}{3}L$ from F.P. ... ..		2				2	
$\frac{1}{2}L$ " ... ..		4				4	
F.P. ... ..		1				1	
Total ... ..							

Mean actual sheer aft =  
Mean standard sheer aft =

Mean actual sheer forward =  
Mean standard sheer forward =

Length of enclosed superstructure forward of amidships =  
" " aft of " =

Correction =  $\frac{\text{Difference between sums of products}}{18} \left( .75 - \frac{S}{2L} \right) = \text{Nil.}$   
If limited on account of midship superstructure.

If limited to maximum allowance of  $1\frac{1}{2}$  ins. per 100 ft.

Deduction for Tropical Freeboard.	Deduction for Fresh Water.	TABULAR FREEBOARD corrected for Flush Deck (if required)	
Addition for Winter and Winter North Atlantic Freeboard.	Displacement in salt water at summer load water line	Correction for coefficient $\frac{1.417}{1.36.}$	<b>1640. ✓</b> <b>1709. ✓</b>
Depth to Freeboard Deck = <b>9.032</b>	$\Delta =$	Depth Correction ... ..	<b>330</b>
TIMBER. Summer freeboard = <b>1.326</b>	Tons per inch immersion at summer load water line	Deduction for superstructures ... ..	<b>713. ✓</b>
Moulded draught (d) = <b>7.706</b>	T =	Sheer correction ... ..	<b>✓</b>
TIMBER. Deduction for Tropical freeboard and addition for	Deduction = $\frac{\Delta}{40 T}$ inches	Round of Beam correction ... ..	<b>✓</b>
Winter freeboard = $\frac{d}{48}$ inches = <b>161 mfm</b>	= <b>162 mfm</b>	Correction for Thickness of Deck amidships ... ..	<b>✓</b>
TIMBER. Addition for Winter North Atlantic Freeboard (if required) = $\frac{d}{36} = 214 mfm$		Other corrections, scantlings, etc. ... ..	<b>✓</b>
		Summer Freeboard = <b>1326. ✓</b>	

TIMBER. SUMMER FREEBOARD amidships from Centre of Disc to top of Deck Line, Steel, Deck :-

TIMBER.	Tropical Fresh Water Line above Centre of Disc	...	664 mfm	TIMBER	Tropical Fresh Water Freeboard	...	1003
"	Fresh Water Line	"	503	"	Fresh Water	"	1164
"	Tropical Line	"	502	"	Tropical	"	1165
"	Winter Line	"	127	"	Winter	"	1540
"	Winter North Atlantic Line	"	153	"	Winter North Atlantic	"	1820
"	SUMMER. FREEBOARD. ABOVE	"	341	"		"	