

## REPORT ON ELECTRICAL EQUIPMENT.

(OTHER THAN FOR THE PROPULSION OF THE VESSEL)

Received at London Office

10 FEB 1937

Date of writing Report 23rd Jan. 1937. When handed in at Local Office 1. 2. 1937 Port of Glasgow

No. in Survey held at Port Glasgow Glasgow. Date, First Survey 14. 12. 36 Last Survey 27. 1. 1937  
Reg. Book. (Number of Visits.....)87974 on the S.S. "DARLENY" Tons { Gross 5205  
Net 3126

Built at Port Glasgow. By whom built Wm Hamilton &amp; Co Ltd Yard No. 427 When built 1937

Owners Carrick Shipping Co. Ltd Port belonging to Glasgow.

Electric Light Installation fitted by W. Muir Goodfellows &amp; Co Ltd Contract No. 427 When fitted 1937

Is the Vessel fitted for carrying Petroleum in bulk ho.

## System of Distribution

Two wire ✓

Pressure of supply for Lighting

110

volts, Heating

volts, Power

volts.

Direct or Alternating Current, Lighting

Direct ✓

Power

If alternating current system, state frequency of periods per second

Has the Automatic Governor been tested and found efficient when the whole load is suddenly thrown on or off Yes ✓

Generators, do they comply with the requirements regarding temperature rise Yes ✓

are they compound wound Yes ✓

are they over compounded 5 per cent. Yes ✓, if not compound wound state distance between each generator

Where more than one generator is fitted are they arranged to run in parallel

series with each shunt field Yes ✓ Have certificates of test results for machines under 100 kw. been submitted and

approved Yes ✓ Have machines over 100 kw. been inspected by the Surveyors during manufacture and testing

Are all terminals accessible, clearly marked, and furnished with sockets Yes ✓, are they so spaced or shielded that they cannot be accidentally earthed,

short circuited, or touched Yes ✓ Are the lubricating arrangements of the generators as per Rule Yes ✓

## Position of Generators

In main Engine Room.

in way of the generators satisfactory Yes ✓

are they clear of all inflammable material Yes ✓

is the ventilation

woodwork or other combustible material, state distance of same horizontally from or vertically above the generators

are the generators protected from mechanical injury and damage from water, steam or oil Yes ✓

are their axes of rotation fore and aft Yes ✓

Earthing, are the bedplates and frames of the generating plant efficiently earthed Yes ✓

are the prime movers and their respective generators

in metallic contact Yes ✓ Main Switch Boards, where placed

In Engine Room near generator.

If the generators and main switchboard are not placed in the same compartment, is each generator provided with

a fuse on each insulated pole as near as possible to the terminals of the generator, additional to that provided on the main switchboard

Switchboards, are they placed in accessible positions, free from inflammable gases and acid fumes Yes ✓, are they protected from mechanical

injury and damage from water, steam or oil Yes ✓, if situated near unprotected woodwork or other combustible material, state distance of same

horizontally from or vertically above the switchboards and, are they constructed wholly of durable, non-ignitable non-absorbent

materials Yes ✓, is all insulation of high dielectric strength and of permanently high insulation resistance Yes ✓

is it of an approved type Yes ✓, if semi-insulating material is used, are all conducting parts insulated from the slab with mica or micanite or other

non-hygroscopic insulating material, and the slab similarly insulated from its framework Yes ✓, is the non-hygroscopic insulating material of an approved

type Yes ✓, and is the frame effectively earthed Yes ✓ Are the fittings as per Rule regarding:— spacing or shielding of live parts

Yes ✓, accessibility of all parts Yes ✓, absence of fuses on back of board Yes ✓, temperature rise of

omnibus bars Yes ✓, individual fuses to voltmeter, pilot or earth lamp Yes ✓, are moving parts of switches alive in the

"off" position ho ✓ are all screws and nuts securing connections effectively locked Yes ✓ are any fuses fitted on the live side of

switches ho ✓ Main Switchgear, description of switchgear for each generator and each outgoing circuit, and arrangement of equalizer switches

D.P. switch &amp; fuses for generators, S.P. switch &amp; D.P. fuses for each outgoing circuit.

Are turbine driven generators fitted with emergency trip switch as per rule

Are cupboards or compartments containing switchboards composed of

fire-resisting material or lined with approved material

Instruments on main switchboard

ammeter

voltage synchronising device for paralleling purposes. For compound machines is the ammeter connected on the opposite pole to equaliser connection

Earth Testing, state what means are provided at the main switchboard for indicating the state of the insulation of the system

Earth Lamps

Switches, Circuit Breakers and Fusible Cut-outs,


do these comply with the requirements of the Rules

Yes

are the fusible cutouts of an approved type

Yes

have the reversed



Lloyd's Register Foundation



PARTICULARS OF GENERATING PLANT.

DESCRIPTION OF GENERATOR.	No. of	RATED AT				DRIVEN BY	WHERE DRIVEN BY AN INTERNAL COMBUSTION ENGINE.	
		Kilowatts.	Volts.	Amperes.	Revs. per Min.		Fuel Used.	Flash Point of Fuel.
MAIN	ONE	8	110	73	600	Steam Engine		
AUXILIARY								
EMERGENCY								
ROTARY TRANSFORMER								

GENERATOR, LIGHTING AND HEATING CONDUCTORS.

DESCRIPTION.	CONDUCTORS.		COMPOSITION OF STRAND.		TOTAL MAXIMUM CURRENT.		Approximate Length. (Lead and Return.) Feet.	Insulated with	HOW PROTECTED.
	No. per Pole.	Total Nominal Area per Pole Sq. Ins.	No.	Diameter.	Circuit.	Rule.			
MAIN GENERATOR	1	.06	19	.064	73	83	60	Rubber.	L.C.A.
EQUALISER CONNECTIONS									
AUXILIARY GENERATOR									
EMERGENCY GENERATOR									
ROTARY TRANSFORMER									
ENGINE ROOM	1	.007	7	.036	20	24	60	"	" "
BOILER ROOM									
AUXILIARY SWITCHBOARDS									
ACCOMMODATION									
SAILOON ACCOMMODATION DB	1	.0145	7	.052	12.5	37	320	"	" "
ENGINEERS "	DB	.007	7	.036	6.5	24	120	"	" "
NAVIGATION DB	1	.007	7	.036	6.0	24	360	"	" "
WIRELESS	1	.007	7	.036	5.0	24	360	"	" "
SEARCHLIGHT	1	.0015	1	.044	.36	6.1	1-240, 1-550	"	" "
MASTHEAD LIGHT	1	.0015	1	.044	.36	6.1	180	"	L.C.
SIDE LIGHTS	1	.0015	1	.044	.18	6.1	100	"	L.C.
COMPASS LIGHTS	DB	.0145	7	.052	10	37	420	"	L.C.A.
POOP LIGHTS	DB	.007	7	.036	11	24	120	"	L.C.A.
CARGO LIGHTS									
ARC LAMPS									
HEATERS									

MOTOR CONDUCTORS.

DESCRIPTION.	No. of Motors.	CONDUCTORS.		COMPOSITION OF STRAND.		TOTAL MAXIMUM CURRENT.		Approximate Length. (Lead and Return.) Feet.	Insulated with	HOW PROTECTED.
		No. Per Pole.	Total Nominal Area per Pole Sq. Ins.	No.	Diameter.	In Circuit.	Rule.			
BALLAST PUMP										
MAIN BILGE LINE PUMPS										
GENERAL SERVICE PUMP										
EMERGENCY BILGE PUMP										
SANITARY PUMP										
CIRC. SEA WATER PUMPS										
CIRC. FRESH WATER PUMPS										
AIR COMPRESSOR										
FRESH WATER PUMP										
ENGINE TURNING GEAR										
ENGINE REVERSING GEAR										
LUBRICATING OIL PUMPS										
OIL FUEL TRANSFER PUMP										
WINDLASS										
WINCHES, FORWARD										
WINCHES, AFT										
STEERING GEAR—										
(a) MOTOR GENERATOR										
(b) MAIN MOTOR										
WORKSHOP MOTOR										
VENTILATING FANS										

current protection devices been tested under working conditions

Joint Boxes, Section and Distribution Boards, is the

construction, protection, insulation, material, and position of these as per rule

Cables: Single, twin, concentric, or multicore *Single - Twin* are the cables insulated and protected as per Tables IV, V, X or XI of the Rules

If the cables are insulated otherwise than as per Rule, are they of an approved type

Fall of Pressure, state maximum between bus bars and

any point of the installation under maximum load

Cable Sockets, are the ends of all cables having a sectional

area of 0.04 square inch and above provided with soldering sockets

Paper Insulated and Varnished Cambric Insulated Cables,

If conductors are paper or varnished cambric insulated, is the dielectric at the exposed ends of the conductor protected from moisture by being suitably sealed with insulating compound, or waterproof insulating tape

Cable Runs, are the cables fixed as far as possible in accessible positions

not exposed to drip or accumulation of water or oil, or to high temperature from boilers, steam pipes, uptakes or other hot objects, or to avoidable risk of mechanical damage

Support and Protection of Cables, state how the cables are supported and protected *Main. L.C.A. clipped to steel bays run through lower decks. Machinery space. L.C.A. Accommodation L.C. clipped direct to steel & woodwork.*

If cables are run in wood casings, are the casings and caps secured by screws, are the cap screws of brass, are the cables run in separate grooves, If armoured and lead covered cables are secured by metal clips, are the clips spaced as per Table VIII

Refrigerated Chambers, are the cables and fittings in accordance with the special requirements

Joints in Cables, state if any, and how made, insulated, and protected

Watertight Glands and Deck Tubes, are all cables passing through decks and watertight bulkheads provided with deck tubes or watertight glands

Bushes in Beams and Non-watertight Partitions, where unarmoured cables pass through beams and non-watertight partitions, are the holes efficiently bushed, state the material of which the bushes are made

Earthing Connections, state what earthing connections are fitted and their respective sectional areas *Lead covering and armoured of cables efficiently bonded & earthed.*

Alternative Lighting, are the groups of lights in the propelling machinery space arranged as per Rule, Emergency Supply, state position and method of control of the emergency supply and how the generator is driven

Navigation Lamps, are these separately wired, controlled by separate switch and separate fuses, are the fuses double pole, are the switches and fuses grouped in a position accessible only to the officers on watch

has each navigation lamp an automatic indicator as per Rule, Secondary Batteries, are they constructed and fitted as per Rule

Fittings, are all fittings on weather decks, in storeholds and engine rooms and wherever exposed to drip or condensed moisture, watertight, are any fittings placed in spaces in which goods are liable to be stacked in close proximity to them; if so, how are they protected

are any fittings placed in spaces where inflammable or explosive dust or gases are liable to be present, if so, how are they protected

where are the controlling switches situated, are all fittings suitably ventilated, are all switches and lampholders constructed wholly of non-ignitable, non-absorbent materials

Heating and Cooking Appliances, are they constructed and fitted as per Rule, are air heaters constructed and fitted as per Rule

Searchlight Lamps, No. of, whether fixed or portable, are their fittings as per Rule

Arc Lamps, other than searchlight lamps, No. of, are their live parts insulated from the frame or case, are their fittings as per Rule

Motors, are their working parts readily accessible, are the coils self-contained and readily removable for replacement

are the brushes, brush holders, terminals and lubricating arrangements as per Rule, are the motors placed in well-ventilated compartments in which inflammable gases cannot accumulate and clear of all inflammable material

water, steam or oil, are they protected from mechanical injury and damage from

material, are the motors of the totally enclosed, pipe ventilated, forced draught, drip or flame proof type, if situated near unprotected woodwork or other combustible material, are the motors of the totally enclosed, pipe ventilated, forced draught, drip or flame proof type, if not of this type, state distance of the combustible material horizontally or vertically above the motors

have machines of over 100 BHP been inspected by the Surveyors during manufacture and testing, Control Gear and Resistances, are the generator field and motor speed regulators, starters and controllers constructed and fitted as per Rule

are required, are these fitted as per Rule, Ships carrying Oil having a Flash Point less than 150 F. Have the special requirements of the Rules been complied with regarding switches, joint boxes, section and distribution boards, protection of cables, method of distribution, lead of cables, lights and fittings

are all fuses of the filled cartridge type, are they of an approved type

If portable lamps for use in dangerous spaces are supplied, are they of a self-contained, battery-fed type approved by the Home Office

Spare Gear, if the vessel is for open sea service have spares been supplied as per Rule



All Conductors are of annealed copper conforming to British Standard Specification No. 7 (or International Electro-technical Commission Publication No. 28).

The Insulated Conductors are guaranteed to withstand the immersion and resistance tests specified in the Rules.

The foregoing is a correct description.

For W. MUIR GOODFELLOW & COMPANY, LTD.

Electrical Engineers.

Date 29. 1. 37.

COMPASSES.

Distance between electric generators or motors and standard compass

80 ft

Distance between electric generators or motors and steering compass

75 ft.

The nearest cables to the compasses are as follows:—

A cable carrying 18 Ampères 14 ft. feet from standard compass 6 feet from steering compass.

A cable carrying 18 Ampères 6 feet from standard compass 14 ft. feet from steering compass.

A cable carrying 6 Ampères 10 feet from standard compass 6 feet from steering compass.

Have the compasses been adjusted with and without the electric installation at work at full power

Yes

Has the effect of switching on and off circuits, motors and other electro-magnetic apparatus within the vicinity of the compasses been noted

Yes

The maximum deviation due to electric currents was found to be 1/2 degrees on any course in the case of the standard compass, and 1/2 degrees on any course in the case of the steering compass.

For WILLIAM HAMILTON & CO., LTD.

Builder's Signature.

Date 30/1/37.

Is this installation a duplicate of a previous case No If so, state name of vessel

General Remarks (State quality of workmanship, opinions as to class, etc.)

The electrical equipment of this vessel has been fitted on board under special survey, tested under full working conditions and found satisfactory. The materials and workmanship were found good and sound.

30/1/37

Total Capacity of Generators 8 Kilowatts.

The amount of Fee ... £ 8 : 0 : 0 at 4%.

Travelling Expenses (if any) £

3/-

When applied for,

at 4%.

When received,

25/1/37

L. Haffner  
Surveyor to Lloyd's Register of Shipping.

Committee's Minute GLASGOW 9-FEB 1937

Assigned

SEE ACCOMPANYING MACHINERY REPORT.



© 2021

Lloyd's Register  
Foundation