

Rpt. 12.

Copy

# FREEBOARD VERIFICATION FORM FOR STEAMERS.

(When received in London Office)

Port

Vessel's Name

Bacardi I

Official No.

No. in Reg. Book

Port of Registry (For Foreign Vessels)

Santiago de Cuba

Iron or Steel

State whether Classed by Lloyd's Register

So

Name of Owners

Date of Verification 14 January 1921

I have to report that the Freeboard from the centre of disc to the top of the statutory deck line, and the lines in connection therewith, as given below, assigned by the Committee to this vessel, have been correctly marked on the vessel's sides, in accordance with the printed instructions:—

From centre of disc to top of statutory deck line 5 ft. 0 ins.

For all Seasons

From centre of disc to top of statutory deck line }  
at awning or part-awning deck . . . } ft. ins.

Fresh water line above centre of disc . . . 2 ins.

Indian Summer line above centre of disc . . . - ins.

Winter line below centre of disc . . . - ins.

Winter North Atlantic line below centre of disc . . . - ins.

Distance between the top of statutory deck line on vessel's side and the intersection of the continuation of upper side of }  
steel wood or iron deck with the vessel's side } at main, spar or upper dk. 1 ins.  
at awning or pt.-awning dk. ins.

NOTE.—It should be clearly shown whether the statutory deck line is set off from a wood or iron deck.

58 Jas. W. Stuart

Surveyor.

(To be filled up in London Office.)

Statement No. Date of Committee's Minute 31. 12. 20

Particulars for Record in Register Book {  
Moulded Depth . . . 14 ft. 1 ins.  
Freeboard . . . 5 ft. 0 ins.  
Corresponding Draught . . . 9 ft. 2 ins.

Freeboards compared and found correct by date

Is fee paid? Form for Certificate

Instructions date

Certificate written Noted for posting

3m, 7, 10. —T.

Condition of class

008938-008952-0087

MS, Poop Deck, Angle, Bulb Angle, Plate, Tee Bulb, or Channel Angles on upper edge

Bridge Deck Stringer Plate, br'dth & thickness Angle on ditto

es.  
h flat l  
beams  
per  
stual  
80x5  
500  
70  
350  
50  
65  
50  
80  
80  
1.2  
60x  
1.0  
70x  
50x