

Lloyd's Register of Shipping.

SURVEYS FOR FREEBOARD.

(COMPUTATION FOR STEAMER, SAILING SHIP, TANKER.)

Ship's Name S.H.W.R. 1662	Official Number	Nationality and Port of Registry	Gross Tonnage	Date of Build	Port of Survey
Moulded Dimensions: Length 180 Breadth 40 Depth 15					Date of Survey 22-6-40
Moulded displacement at moulded draught = 85 per cent. of moulded depth _____ tons					Surveyor's Signature
Coefficient of fineness for use with Tables .70					Particulars of Classification +100A1 with for Ferry (with limiting part 1).

Depth for Freeboard (D). Moulded depth 15.00 Stringer plate03 Sheathing on exposed deck $T \left(\frac{L-S}{L} \right) =$ Depth for Freeboard (D) = 15.03	Depth correction. (a) Where D is greater than Table depth (D - Table depth) R = $(15.03 - 12.00) \times 1.385 = + 4.20$ (b) Where D is less than Table depth (if allowed) (Table depth - D) R = If restricted by superstructures	Round of Beam correction. Moulded Breadth (B) 40 Standard Round of Beam = $\frac{B \times 12}{50} = 9.60$ Ship's Round of Beam = 3.00 Difference 6.60 Restricted to Correction = $\frac{\text{Diff}}{4} \times \left(1 - \frac{S_1}{L}\right) = \frac{6.60}{4} = + 1.65$
---	---	--

DEDUCTION FOR SUPERSTRUCTURES.

	Mean Covered Length (S)	Equivalent Enclosed Length (S ₁)	Height	Height Correction	Effective Length (E)
Poop enclosed					
„ overhang					
R.Q.D. enclosed					
„ overhang					
Bridge enclosed					
„ overhang aft					
„ overhang forward					
F'cle enclosed					
„ overhang					
Trunk aft					
„ forward					
Tonnage opening aft					
„ „ forward					
Total					

Flush Deck

Standard Height of Superstructure **6.0**
 „ „ R.Q.D. _____
 Deduction for complete superstructure **20**
 Percentage covered $\frac{S}{L} =$
 „ „ $\frac{S_1}{L} =$
 „ „ $\frac{E}{L} =$
 Percentage from Table, Line A.
 (corrected for absence of forecastle (if required))
 Percentage from Table, Line B.
 (corrected for absence of forecastle (if required))
 Interpolation for bridge less than 2L (if required)
 Deduction = **Nil**

SHEER CORRECTION.

Station	Standard Ordinate	S	M	Product	Actual Ordinate	Effective Ordinate	S	M	Product
A.P.	28.00	1			2		1		2
$\frac{1}{8}L$ from A.P.		4					4		
$\frac{2}{8}L$ „		2					2		
Amidships		4					4		
$\frac{3}{8}L$ from F.P.		2					2		
$\frac{1}{8}L$ „		4					4		
F.P.		1			3		1		3
Total				252.00					5

Correction = $\frac{\text{Difference between sums of products}}{18} \left(\frac{.75 - S}{2L} \right) = \frac{247}{18} \times .75 = + 10.29$
 If limited on account of midship superstructure. If limited to maximum allowance of $\frac{1}{4}$ ins. per 100 ft.

Deduction for Tropical Freeboard. Addition for Winter and Winter North Atlantic Freeboard. Depth to Freeboard Deck = 15.03 Summer freeboard = 3.25 Moulded draught (d) = 11.78 Deduction for Tropical freeboard and addition for Winter freeboard = $\frac{d}{4}$ inches = Addition for Winter North Atlantic Freeboard (if required) =	Deduction for Fresh Water. Displacement in salt water at summer load water line $\Delta =$ Tons per inch immersion at summer load water line $T =$ Deduction = $\frac{\Delta}{40T}$ inches =	TABULAR FREEBOARD corrected for Flush Deck (if required) Correction for coefficient $\frac{19.80 + 2.70}{1.36} = \frac{22.50}{1.36} = 16.54$ <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td>Depth Correction</td> <td>4.20</td> <td>-</td> </tr> <tr> <td>Deduction for superstructures</td> <td>-</td> <td>-</td> </tr> <tr> <td>Sheer correction</td> <td>10.29</td> <td>-</td> </tr> <tr> <td>Round of Beam correction</td> <td>1.65</td> <td>-</td> </tr> <tr> <td>Correction for Thickness of Deck amidships</td> <td>-</td> <td>-</td> </tr> <tr> <td>Other corrections, scantlings, etc.</td> <td>-</td> <td>-</td> </tr> <tr> <td>Summer Freeboard =</td> <td>38.99</td> <td></td> </tr> </table>	Depth Correction	4.20	-	Deduction for superstructures	-	-	Sheer correction	10.29	-	Round of Beam correction	1.65	-	Correction for Thickness of Deck amidships	-	-	Other corrections, scantlings, etc.	-	-	Summer Freeboard =	38.99	
Depth Correction	4.20	-																					
Deduction for superstructures	-	-																					
Sheer correction	10.29	-																					
Round of Beam correction	1.65	-																					
Correction for Thickness of Deck amidships	-	-																					
Other corrections, scantlings, etc.	-	-																					
Summer Freeboard =	38.99																						

SUMMER FREEBOARD amidships from Centre of Disc to top of Deck Line, Wood, Steel, Deck:

Tropical Fresh Water Line above Centre of Disc	Tropical Fresh Water Freeboard
Fresh Water Line „ „	Fresh Water „ „
Tropical Line „ „	Tropical „ „
Winter Line below „ „	Winter „ „
Winter North Atlantic Line „ „	Winter North Atlantic „ „