

REPORT ON ELECTRIC FITTINGS.

(OTHER THAN FOR THE PROPULSION OF THE VESSEL)

Received at London Office 23 JUL 1930

Date of writing Report

19

When handed in at Local Office

21 JULY 1930

Port of

LIVERPOOL

No. in Survey held at *Saltney, Chester.*

Date, First Survey

1/5/30

Last Survey

11/7/

1930

Reg. Book.

(Number of Visits.....)

on the

M. S. "SIR CHARLES ORR"

Tons

Gross 214.58

Net 90.26

Built at *SALTNEY SHIPYARD, CHESTER*

by whom built

J. CRICHTON & CO LTD

Yard No.

497

When built

1930.

Owners *THE ELEUTHERA SHIPPING CO LTD*

Port belonging to

*INCORPORATED IN THE BAHAMAS.*Electric Light Installation fitted by *J. CRICHTON & CO LTD CHESTER*

Contract No.

497

When fitted

1930.

Is the Vessel fitted for carrying Petroleum in bulk

NO.

System of Distribution

2 WIRE

Pressure of supply for Lighting

110

volts, Heating

volts, Power

volts.

Direct or Alternating Current, Lighting

DIRECT

Power

If alternating current system, state frequency of periods per second

Has the Automatic Governor been tested and found efficient when the whole load is suddenly thrown on or off

YES.

Generators, do they comply with the requirements regarding rating

YES

, are they compound wound

YES.

are they over compounded 5 per cent.

YES.

, if not compound wound state distance between each generator

Where more than one generator is fitted are they arranged to run in parallel

YES.

, is an adjustable regulating resistance fitted in

series with each shunt field

Are all terminals accessible, clearly marked, and furnished with sockets

YES.

, are they so spaced or shielded that they cannot be accidentally earthed,

short circuited, or touched

YES

Are the lubricating arrangements of the generators as per Rule

YES

Position of Generators

ON ENGINE ROOM BOTTOM PLATFORM

is the ventilation in way of the generators satisfactory

YES

, are they clear of all inflammable material

YES.

if situated near unprotected woodwork or other combustible material, state distance of same horizontally from or vertically above the generators

and

are the generators protected from mechanical injury and damage from water, steam or oil

YES.

are their axes of rotation fore and aft

YES.

Earthing, are the bedplates and frames of the generating plant efficiently earthed

YES.

are the prime movers and

their respective generators in metallic contact

YES.

Main Switch Boards, where placed

ENGINE ROOM, ALONGSIDE GENERATOR

If the generators and main switchboard are not placed in the same compartment, is each generator provided with

a fuse on each insulated pole as near as possible to the terminals of the generator, additional to that provided on the main switchboard

Switchboards, are they placed in accessible positions, free from inflammable gases and acid fumes

YES.

are they protected from mechanical injury and damage from water, steam or oil

YES.

, if situated near unprotected

woodwork or other combustible material, state distance of same horizontally from or vertically above the switchboards

are they constructed wholly of durable, non-ignitable non-absorbent materials

YES.

, is all insulation of high dielectric strength and of

permanently high insulation resistance

YES

, if semi-insulating material is used, are all conducting parts insulated from the slab

with mica or micanite or other non-hygroscopic insulating material, and the slab similarly insulated from its framework

and is the frame effectively earthed

YES.

Are the fittings as per Rule regarding:— spacing or shielding of live parts

YES

, accessibility of all parts

YES.

, absence of fuses on back of board

YES.

, proportion of omnibus

bars

YES.

, individual fuses to voltmeter, pilot or earth lamp

YES.

, connections of switches

YES.

Main Switchgear, description of switchgear for each generator and each outgoing circuit, and arrangement of equalizer switches

ONE D.P. CHANGE OVER

SWITCH, ONE D.P. SWITCH WITH D.P. FUSES FOR GENERATOR, 5 D.P. SWITCHES WITH D.P. FUSES FOR CIRCUITS. VOLT-METER, AMMETER, PILOT LAMP AND EARTH LAMP WITH D.P. FUSES.

Instruments on main switchboard

ONE

ammeters

ONE

voltmeters

synchronising device for paralleling purposes.

Earth Testing, state what means are provided at the main switchboard for indicating the state of the insulation of the system


EARTH LAMP

Switches, Circuit Breakers and Fusible Cut-outs, do these comply with the requirements of the Rules

YES

Joint Boxes Section and Distribution Boards, is the construction, protection, insulation, material, and position of these as per rule

YES.



© 2021

Lloyd's Register Foundation

009050 - 009057 - 0246

Cables: Single, twin, concentric, or multicore **SINGLE** are the cables insulated and protected as per Tables IV or V of the Rules **YES**.

Fall of Pressure, state maximum between bus bars and any point of the installation under maximum load **5 VOLTS**.

Cable Sockets and other connections, are the ends of all cables having a sectional area of 0.04 square inch and above provided with soldering sockets **YES**.

Paper Insulated Cables. If cables are paper covered, is the dielectric at the exposed ends of the conductor protected from moisture by being suitably sealed with insulating compound **YES**.

Cable Joints, are the cables fixed as far as possible in accessible positions not exposed to drip or accumulation of water or oil, or to high temperature from boilers, steam pipes, uptakes or other hot objects, or to avoidable risk of mechanical damage **YES**.

Support and Protection of Cables, state how the cables are supported and protected **SADDLES TO STRUCTURE OR TO STEEL TRAYS. LEAD COVERED THROUGHOUT.**

If cables are run in wood casings, are the casings and caps secured by screws **—**, are the cap screws of brass **—**, are the cables run in separate grooves **—**. If armoured and lead covered cables are secured by metal clips, are the clips spaced as per Table VIII **YES**.

Refrigerated Chambers, if lights are fitted, are the cables and fittings in accordance with the special requirements **—**.

Joints in Cables, state if any, and how made, insulated, and protected **NONE**.

Watertight Glands and Deck Tubes, are all cables passing through decks and watertight bulkheads provided with deck tubes or watertight glands **YES**.

Bushes in Beams and Non-watertight Partitions, where unarmoured cables pass through beams and non-watertight partitions, are the holes efficiently bushed **YES**. state the material of which the bushes are made **LEAD**.

Earthing Connections, state what earthing connections are fitted and their respective sectional areas **YES**.

Alternative Lighting, are the groups of lights in the machinery spaces arranged as per Rule **YES**.

Emergency Supply, state position and method of control of the emergency supply and how the generator is driven **YES**.

Navigation Lamps, are these separately wired **YES**, controlled by separate switch and separate fuses **YES**, are the fuses double pole **YES**.

are the switches and fuses grouped in a position accessible only to the officers on watch **YES**.

has each navigation lamp an automatic indicator as per Rule **YES**.

Secondary Batteries, are they installed and fitted as per Rule **YES**.

Fittings, are all fittings on weather decks, in stokeholds and engine rooms and wherever exposed to drip or condensed moisture, watertight **YES**.

are any fittings placed in spaces in which goods are liable to be stacked in close proximity to them; if so, how are they protected **—**.

are any fittings placed in spaces where inflammable or explosive dust or gases are liable to be present, if so, how are they protected **No**.

how are the cables led **—**.

where are the controlling switches situated **YES**.

Searchlight Lamps, No. of **NONE**, whether fixed or portable **—**, are their fittings as per Rule **—**.

Are Lamps, other than searchlight lamps, No. of **—**, are their live parts insulated from the frame or case **—**, are their fittings as per Rule **—**.

Motors, are their running parts readily accessible **—**, are the coils self-contained and readily removable for replacement **—**.

are the brushes, brush holders, commutators and lubricating arrangements as per Rule **—**, are the motors placed in well-ventilated compartments in which

inflammable gases cannot accumulate and clear of all inflammable material **—**.

are they protected from mechanical injury and damage from water, steam or oil **—**, are their axes of rotation fore and aft **—**.

if situated near unprotected woodwork or other combustible material, are the motors of the totally enclosed, pipe ventilated, forced draught, drip or flame proof type **—**.

if of this type, state distance of the combustible material horizontally or vertically above the motors **—** and **—**.

Control Gear and Resistances, are the generator field and motor speed regulators, starters and controllers constructed and fitted as per Rule **—**.

Lightning Conductors, where lightning conductors are required, are these fitted as per Rule **YES**.

Ships carrying Oil having a Flash Point less than 150° F. Have the special requirements of the Rules been complied with regarding switches, joint boxes, section and distribution boards, protection of cables, method of distribution, lead of cables, lights and fittings **—**.

If portable lamps for use in dangerous spaces are supplied, are they of a type approved by the Home Office **—**.

PARTICULARS OF GENERATING PLANT.


DESCRIPTION OF GENERATOR.	No. of	RATED AT				DRIVEN BY	WHERE DRIVEN BY AN INTERNAL COMBUSTION ENGINE.	
		Kilowatts.	Volts.	Ampères.	Revs. per Min.		Fuel Used.	Flash Point of Fuel.
MAIN	ONE	2	110	18.2	1400	6 B.H.P. SEMI DIESEL		NOT LESS THAN 150° F.
AUXILIARY						ENGINE THROUGH		
EMERGENCY						DOUBLE "WHITTLE"		
ROTARY TRANSFORMER						LEATHER BELT.		

GENERATOR, LIGHTING AND HEATING CONDUCTORS.

DESCRIPTION.	CONDUCTORS.		COMPOSITION OF STRAND.		TOTAL MAXIMUM CURRENT AMPERES.		Approximate Length. (Lead and Return.) Feet.	Insulated with	HOW PROTECTED.
	No. per Pole.	Total Effective Area per Pole Sq. Ins.	No.	Diameter.	In Circuit.	Rule.			
MAIN GENERATOR	2	.004	7	.029	17.5	18.2	18'-0"	V.I.R.	LEAD COVERED
EQUALISER CONNECTIONS									
AUXILIARY GENERATOR									
EMERGENCY GENERATOR									
ROTARY TRANSFORMER									
ENGINE ROOM									
BOILER ROOM									
AUXILIARY SWITCHBOARDS									
ACCOMMODATION									
WIRELESS	2	.003	3	.036	12	12	8'-0"	V.I.R.	LEAD COVERED
SEARCHLIGHT	2	.003	3	.036	5	12	212'-0"	V.I.R.	LEAD COVERED
MASTHEAD LIGHT	4	.003	3	.036	1	12	92'-0"	V.I.R.	Do Do
SIDE LIGHTS	2	.003	3	.036	2	12	10'-0"	V.I.R.	Do Do
COMPASS LIGHTS	2	.003	3	.036	2	12	54'-0"	V.I.R.	Do Do
POOP LIGHTS	2	.003	3	.036	1	12	100'-0"	V.I.R.	Do Do
CARGO LIGHTS	2	.003	3	.036	1	12	100'-0"	V.I.R.	Do Do
ARC LAMPS	NONE								
HEATERS	NONE								

MOTOR CONDUCTORS.

DESCRIPTION.	No. of Motors.	CONDUCTORS.		COMPOSITION OF STRAND.		TOTAL MAXIMUM CURRENT AMPERES.		Approximate Length. (Lead and Return.) Feet.	Insulated with	HOW PROTECTED.
		No. per Pole.	Total Effective Area per Pole Sq. Ins.	No.	Diameter.	In Circuit.	Rule.			
BALLAST PUMP										
MAIN BILGE LINE PUMPS										
GENERAL SERVICE PUMP										
EMERGENCY BILGE PUMP										
SANITARY PUMP										
CIRC. SEA WATER PUMPS										
CIRC. FRESH WATER PUMPS										
AIR COMPRESSOR										
FRESH WATER PUMP										
ENGINE TURNING GEAR										
ENGINE REVERSING GEAR										
LUBRICATING OIL PUMPS										
OIL FUEL TRANSFER PUMP										
WINDLASS										
WINCHES, FORWARD										
WINCHES, AFT										
STEERING GEAR—										
(a) MOTOR GENERATOR										
(b) MAIN MOTOR										
WORKSHOP MOTOR										
VENTILATING FANS										



© 2021

Lloyd's Register Foundation

All Conductors are of annealed copper conforming to British Standard Specification No. 7. YES.

The Insulated Conductors are guaranteed to withstand the immersion and resistance tests specified in the Rules. YES.

The foregoing is a correct description. YES.

For J. CRICHTON & CO., LTD.

William Hill
MANAGING DIRECTOR.

Electrical Engineers.

Date *2nd July 1930*

COMPASSES.

Distance between electric generators or motors and standard compass

26'-0"

Distance between electric generators or motors and steering compass

19'-0"

The nearest cables to the compasses are as follows:—

A cable carrying *6.5* Amperes *5* feet from standard compass *ONE* feet from steering compass.

A cable carrying *.02* Amperes *5* feet from standard compass *ONE* feet from steering compass.

A cable carrying *.02* Amperes *5* feet from standard compass *ONE* feet from steering compass.

Have the compasses been adjusted with and without the electric installation at work at full power YES.

Has the effect of switching on and off circuits, motors and other electro-magnetic apparatus within the vicinity of the compasses been noted YES.

The maximum deviation due to electric currents was found to be *NIL* degrees on course in the case of the standard

compass, and *NIL* degrees on course in the case of the steering compass.

For J. CRICHTON & CO., LTD.

William Hill
MANAGING DIRECTOR.

Builder's Signature.

Date *2nd July 1930*

Is this installation a duplicate of a previous case

No.

If so, state name of vessel

General Remarks (State quality of workmanship, opinions as to class, &c.)

This installation has been satisfactorily fitted on board & is in accordance with the Rules. It has been examined under full working conditions & found satisfactory and is eligible in my opinion for record of Elec Light in Register book.

It is submitted that this vessel is eligible for THE RECORD Elec Light.

J. Milton
24/7/30

Total Capacity of Generators *2* Kilowatts.

The amount of Fee ...

£ 5 : 0 : 0

When applied for, *22 JULY 1930*

Travelling Expenses (if any) £

✓

When received, *11-8-30*

J. Milton

Surveyor to Lloyd's Register of Shipping.

Committee's Minute

LIVERPOOL 22 JULY 1930

Assigned

Elec. Light.

11/11



© 2021

Lloyd's Register
Foundation