

Norwegian. 1909 Rules.

Index No. **26031**
(For London Office only.)

Lloyd's Register of Shipping.

SURVEYS FOR FREEBOARD.—STEAM SHIPS.

PARTICULARS RELATING TO ALL STEAM SHIPS ~~WITH FLUSH DECKED, OR WITH TOP GALLANT FORECASTLES, SHORT POOPS AND BRIDGE HOUSES DISCONNECTED, OR WITH TOP GALLANT FORECASTLES HAVING LONG POOPS, OR RAISED QUARTER DECKS CONNECTED WITH BRIDGE HOUSES, OR OTHERWISE.~~

Port of Survey Rotterdam
Date of Survey 15th Sept 1932
Name of Surveyor _____

ALASKA

(altered to Alaska 29.1.37)

Ship's Name.	Port of Registry and Nationality.	Official Number.	Gross Tonnage.	Date of Build.	Particulars of Classification.
PEEL <u>COUNTY</u>	<u>Haugesund</u>	<u>—</u>	<u>5681</u>	<u>1918/7</u>	<u>+ 100 A. 1.</u>
Number in Register Book	<u>Norwegian</u>				

Registered dimensions from Ship's Register.	LENGTH.	BREADTH.	DEPTH.	UNDER DECK TONNAGE.
	<u>410.5</u>	<u>54.1</u>	<u>27.5</u>	<u>5129.55</u>
Length on LOADLINE.	<u>410.0</u>	Frame Depth ¹⁰ / ₄ Rule <u>53.44</u> x2 = <u>106.88</u> Spanning fitted.	Ceiling <u>fitted</u> Sheer <u>+1.38</u> Drop in tank <u>4" = +.16</u> Depth to tank <u>fitted</u> <u>27.16</u>	Peak Tanks } <u>inc.</u> Rise in <u>08</u> frid <u>+1.84</u>
CORRECTED DIMENSIONS.	<u>410.0</u>	<u>53.44</u>	<u>28.70</u>	<u>5131.39</u>

Co-efficient of fineness..... .816
Any modification necessary }
[Para. 4 (a) to (e)]* } .02
Co-efficient as corrected796

Sheer { Stem..... 141 } 212 ÷ 2 = 106 ...Mean
at { Sternpost ... 71 }
Sheer at $\frac{1}{8}$ of the length from { Stem 70.0 } 111 ÷ 2 = 55.5 ...Mean
{ Sternpost 41.0 }
Gradual mean Sheer 100.9 ÷ 55 = 100.9
Standard mean Sheer [Table, Para. 18] 51.0 Correction
Difference..... 49.9 ÷ 4 = 12.475
§ If limited as Para. 18 (f) -12.47

Rise in Sheer { At front of bridge house..... ✓
from amidships {
[Para. 18 (e)] { At after end of forecastle ✓

Fall in Sheer }
Para. 18 (d) } ÷ 2 = ✓
Length uncovered Correction

ALLOWANCE FOR DECK ERECTIONS:—

Freeboard, Table C..... 52.15
Correction for Length, if required (Para. 12, 13, and 14) + 4.24
56.39
Freeboard by Table A, corrected for sheer, and for length, if required (Para. 11, 12, 13, and 14) ¹⁰/₁₀ } 86.53
Difference 30.14
Percentage as below..... 32.096%
9.67

Correction for R. Q. Dk. if engine and boiler openings not covered by bridge house (Para. 11) ✓
Allowance for Deck Erections - 9.67

	Length.	Length allowed.	Height.
Forecastle.....	<u>47.00</u>	<u>47.00</u>	<u>8.0</u>
Bridge House	<u>114.75</u>	<u>114.75</u>	<u>8.5</u>
† Raised Qr. Dk.			
Poop.....	<u>43.75</u>	<u>43.75</u>	<u>7.75</u>
Total		<u>205.50</u>	<u>5012</u>
Length of Ship	<u>410</u>		
Corresponding percentage { (Para. 11, 12, 13, or 14) } <u>32.096%</u>			

Moulded Depth as measured..... 29'-9"
Addition for Keel below base line for draught record.....inches.

NOTE.— If the depth is measured when vessel is afloat, the details of measurement should be reported.

29'-9"
30'-10"
3'-8"
27'-2"

CORRECTION FOR LENGTH.

Length of Ship on Loadline..... 410.0
Length in Table 357.0
Difference 53.0
Correction for 10ft., Table A. 1.5 Table C. .8
× Difference divided by 10 + 7.95 (if required.) + 4.24
If $\frac{1}{10}$ ths length covered divide by 2

CORRECTION FOR IRON DECK.

Proportion covered, if less than $\frac{1}{10}$ ths length covered 5012
Thickness of usual wood deck, less stringer 3 1/2
= - 1.75"

CORRECTION FOR ROUND OF BEAM.

Breadth at Gunwale amidships..... 54.0
Round of Beam 13.50
Normal round..... 13.50
Difference ✓ ÷ 2 = ✓
Proportion of Deck uncovered (Para. 19)

NOTE.— The round of beam should be reported on the full breadth of vessel at the gunwale.

Freeboard, Table A 91.05"
Correction for Sheer - 12.47
78.58
Correction for Length + 7.95
86.53
Allowance for Deck Erections - 9.67
76.86
Correction for Round of Beam..... ✓
Correction for fall in Sheer (if any)..... ✓
Correction for Steel Deck (if required) - 1.75
75.11
Additions for non-compliance with provisions of }
Para. 11 (d) and (e) † } ✓
Other Corrections (if any) ✓

Winter Freeboard 6'-3"
Summer Freeboard (4 1/2' : 6) = 5 1/4' 5-9 3/4"
Indian Summer Freeboard 5-4 1/2"
~~N. A. Winter Freeboard~~ ✓

Correction necessary because clearside amidships, measured in accordance with the Statute is not taken at the intersection of the wood or steel deck with side.

Winter Freeboard from deck line
Summer " " " "
Indian Summer " " " "
N. A. Winter " " " "

assumed **SUMMER FREEBOARD** amidships from Centre of Disc to top of Deck Line, ~~Wood~~, Steel, Deck:— 5'-10" = 1778 ^{mm}
Tropical Fresh Water Line above Centre of Disc 11 1/2" = 292 ^{mm} Tropical Fresh Water Freeboard 4'-10 1/2" = 1486 ^{mm}
Fresh Water Line " " 6" = 152 ^{mm} Fresh Water 5'-4" = 1626 ^{mm}
Tropical Line " " 5 1/2" = 140 ^{mm} Tropical 5'-4 1/2" = 1638 ^{mm}
Winter Line below " " 5" = 127 ^{mm} Winter 6'-3" = 1905 ^{mm}
~~Winter North Atlantic Line~~ " " ~~Winter North Atlantic~~ " "

6 OCT 1932

Lloyd's Register
Marking Form
No. 4/10/32