

Lloyd's Register of Shipping.

SURVEYS FOR FREEBOARD.

(COMPUTATION FOR STEAMER, SAILING SHIP, TANKER.)

12 SEP 1945

Ship's Name "EMPIRE CONSEQUENCE" (EX GERMAN VESSEL "FRIEDRICH BISCHOFF")	Official Number 180707	Nationality and Port of Registry BRITISH LONDON	Gross Tonnage 1998	Date of Build	Port of Survey NEWCASTLE-ON-TYNE
Moulded Dimensions: Length 291'3" Breadth 43'3" Depth 17'9" <small>TO FREE BOARD DK.</small>				Date of Survey SEPTEMBER 1945	
Moulded displacement at moulded draught = 85 per cent. of moulded depth 3860 tons				Surveyor's Signature H. Little	
Coefficient of fineness for use with Tables 711.711				Particulars of Classification GERM. LLOYD + 100 A (E)	

DEPTH FOR FREEBOARD (D). Moulded depth ... 17'75" Stringer plate ... 07" Sheathing on exposed deck $T \left(\frac{L-S}{L} \right) =$ Depth for Freeboard (D) = 17'82"	DEPTH CORRECTION. (a) Where D is greater than Table depth (D-Table depth) R = ✓ (b) Where D is less than Table depth (if allowed) (Table depth-D) R = ✓ $(19.42 - 17.82) \times 2.24 = -3.58$ If restricted by superstructures ✓	ROUND OF BEAM CORRECTION. Moulded Breadth (B) 43'25" Standard Round of Beam = $\frac{B \times 12}{50} = 10.38$ Ship's Round of Beam NIL = 11" AT SUPERSTRUCTURE DECK Difference 10.38 NO CAMBER AT F&P DK. Restricted to Correction = $\frac{\text{Diff}^a}{4} \times \left(1 - \frac{S_1}{L} \right) = \frac{10.38}{4} \times 0.056 = +0.05$
---	--	--

DEDUCTION FOR SUPERSTRUCTURES.

	Mean Covered Length (S)	Equivalent Enclosed Length (S ₁)	Height	Height Correction	Effective Length (E)
Poop enclosed ...	34'6"	34'50"	10'6"-10'10"	✓	34'50"
" overhang ...	✓				
R.Q.D. enclosed ...	✓				
" overhang ...	✓				
Bridge enclosed ...	252'2"	252'17"	7'6"	✓	252'17"
" overhang aft ...	✓				
" overhang forward ...	✓				
F'cle enclosed ...	✓				
" overhang ...	✓				
Trunk aft ...	✓				
" forward ...	✓				
Tonnage opening aft ...	4'7"		7'6"-10'10"		
" " forward ...	✓				
Total ...	286'67"	286'67"			286'67"

Standard Height of Superstructure **6.412**

" " R.Q.D. **✓**

Deduction for complete superstructure **34.75**

Percentage covered $\frac{S}{L} =$

" " $\frac{S_1}{L} =$ **98.44.**

" " $\frac{E}{L} =$

Percentage from Table, Line A. **✓**
(corrected for absence of forecastle (if required)) **✓**

Percentage from Table, Line B. **98.08**
(corrected for absence of forecastle (if required)) **✓**

Interpolation for bridge less than 2L (if required) **✓**

Deduction = $34.75 \times 98.08 = -34.08$

SHEER CORRECTION.

Station	Standard Ordinate	S M	Product	Actual Ordinate	Effective Ordinate	S M	Product
A.P. ...	39.12	1	39.12	48"	48.00	1	48.00
$\frac{1}{8}$ L from A.P. ...	17.41	4	69.64	20"	20.00	4	80.00
$\frac{3}{8}$ L " ...	4.30	2	8.60	3"	3.00	2	6.00
Amidships ...	-	4	-	-	-	4	-
$\frac{5}{8}$ L from F.P. ...	8.61	2	17.22	20"	20.00	2	40.00
$\frac{7}{8}$ L " ...	34.82	4	139.28	53"	53.00	4	212.00
F.P. ...	78.25	1	78.25	93"	93.00	1	93.00
Total ...			352.11				479.00

Mean actual sheer aft =

Mean standard sheer aft =

Mean actual sheer forward =

Mean standard sheer forward =

Length of enclosed superstructure forward of amidships = **✓**

" " aft of " = **✓**

Correction = $\frac{\text{Difference between sums of products}}{18} \left(75 - \frac{S}{2L} \right) = \frac{126.89}{18} \left(75 - \frac{49.22}{2578} \right) = -1.82$

If limited on account of midship superstructure. **✓** If limited to maximum allowance of $1\frac{1}{2}$ ins. per 100 ft.

Deduction for Tropical Freeboard.

Addition for Winter and Winter North Atlantic Freeboard.

Depth to Freeboard Deck = **17'82"**

Summer freeboard = **25"**

Moulded draught (d) = **17'57"**

Deduction for Tropical freeboard and addition for

Winter freeboard = $\frac{d}{4}$ inches = $4.39 = 4\frac{1}{2}$

Addition for Winter North Atlantic Freeboard (if required) = $4\frac{1}{4} + 2 = 6\frac{1}{4}$

Deduction for Fresh Water.

Displacement in salt water at summer load water line

$\Delta = 4625$

Tons per inch immersion at summer load water line

T = **225.9**

Deduction = $\frac{\Delta}{40 T}$ inches = $4.46 = 4\frac{1}{2}$

TABULAR FREEBOARD corrected for Flush Deck (if required)

Correction for coefficient $\frac{711 + 68}{136} = 1.391$

Depth Correction ... **3.58**

Deduction for superstructures ... **34.08**

Sheer correction ... **1.82**

Round of Beam correction ... **05**

Correction for Thickness of Deck amidships ... **-**

Other corrections, scantlings, etc. ... **-**

Summer Freeboard = **2.81**SUMMER FREEBOARD amidships from Centre of Disc to top of Deck Line, ~~Wood~~ Steel Deck :-

Tropical Fresh Water Line above Centre of Disc ... **5 1/2" 139**

Fresh Water Line " " ... **4 1/2" 114**

Tropical Line " " ... **1" 25**

Winter Line below " " ... **4 1/4" 108**

Winter North Atlantic Line " " ... **6 1/4" 159**

Tropical Fresh Water Freeboard ... **MINUS 0' - 2 1/2" 63"**

Fresh Water " " ... **MINUS 0' - 1 1/2" 38"**

Tropical " " ... **(LIMITED) 0' - 2" 51"**

Winter " " ... **0' - 7 1/4" 184"**

Winter North Atlantic " " ... **0' - 9 1/4" 235"**

A new form should be prepared if any alterations that affect the freeboard have been made. If no such alterations have been made, the Surveyor should endorse the form on this side with his signature and the date.

Trade of ship

Names of sister ships

Builder's name and yard number LÜBECKER MASCHINENBAU GESELLSCHAFT LÜBECK

Owners THE MINISTRY OF WAR TRANSPORT

Fee £11-0-0



© 2020

Lloyd's Register
Foundation