







PARTICULARS OF LONGITUDINAL FRAMING.

GENI

FRAMING.	AMIDSHIPS.			ENDS.			AMIDSHIPS.			ENDS.			RIVETING.				
	In Ship.			In Ship.			Per Rule or as approved.			Per Rule or as approved.			Rivets in Longitudinal Frames. Diam. Speng.	Spacing of Rivets on each side of Transverses and Bulkheads. Inches.	Rivets in Brackets to Bulkheads.		
	Ins.	Ins.	Ins.	Ins.	Ins.	Ins.	Ins.	Ins.	Ins.	Ins.	Ins.	Number.			Diameter. Inches.		
Framing of  or 																	
Frames in Bridge 'tween Decks ...																	
Frames from Uppermost Continuous Deck																	
No. 1	6x3 1/2 x 3 1/2	34		6x3 1/2 x 3 1/2	34		6x3 1/2 x 3 1/2	34		6x3 1/2 x 3 1/2	34	1	5 1/2		5 1/2	8	7/8
" 2	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"
" 3	7x3 1/2 x 3 1/2	40		7x3 1/2 x 3 1/2	40		7x3 1/2 x 3 1/2	40		7x3 1/2 x 3 1/2	40	"	"	"	"	"	"
" 4	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"
" 5	10x3 1/2 x 3 1/2	37 1/2		10x3 1/2 x 3 1/2	37 1/2		10x3 1/2 x 3 1/2	37 1/2		10x3 1/2 x 3 1/2	37 1/2	1	5 1/2		5 1/2	"	"
" 6	"	"	"	"	"	"	"	"	"	"	"	"	"	"	4 1/2	10	"
" 7	"	"	"	"	"	"	"	"	"	"	"	"	"	"	4 1/2	10	"
" 8	"	"	"	"	"	"	"	"	"	"	"	"	"	"	4 1/2	11	"
" 9	"	"	"	"	"	"	"	"	"	"	"	"	"	"	3 1/2	11	"
" 10	12x3 1/2 x 3 1/2	45		12x3 1/2 x 3 1/2	45		12x3 1/2 x 3 1/2	45		12x3 1/2 x 3 1/2	45	"	"	"	3 1/2	11	"
" 11	"	"	"	"	"	"	"	"	"	"	"	"	"	"	3 1/2	11	"
" 12	14x3 1/2 x 3 1/2	43 1/2		14x3 1/2 x 3 1/2	43 1/2		14x3 1/2 x 3 1/2	43 1/2		14x3 1/2 x 3 1/2	43 1/2	"	"	"	3 1/2	16	"
" 13	18x5 1/2 x 6 1/2	62 1/2		18x5 1/2 x 6 1/2	62 1/2		18x5 1/2 x 6 1/2	62 1/2		18x5 1/2 x 6 1/2	62 1/2	"	"	"	3 1/2	20	"
" 14	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	20	"
" 15	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	20	"
" 16	"	"	"	"	"	"	"	"	"	"	"	"	"	"	"	20	"
Spacing of Longitudinal Frames																	
Amidships																	
At Ends																	
Double Bottoms  or 																	
Tank Top Longitudinals																	
Bottom																	
Spacing of Longitudinals																	
Amidships																	
At Ends																	
Transverses.																	
In Bridge 'tween Decks																	
Depth and Thickness																	
Face Angles																	
Lugs to Shell																	
In Awning, Shelter or Upper 'tween Decks.																	
Depth and Thickness																	
Face Angles																	
Lugs to Shell																	
In Hold.																	
Depth and Thickness																	
Face Angles																	
Lugs to Shell																	
Brackets																	
Spacing of Transverse Frames																	
State if joggled or lapped.																	
Longitudinal Beams of  or 																	
Bridge Deck																	
Shltr. Dk.																	
Upper																	
Second																	
Third																	

The particulars of framing in peaks (if ordinary), Floors, Centre Girder, Side Girders and Margin Plate and their angle attachments, etc., to be entered in their respective places provided for on the Report Forms.

NOTE:—This slip to be pasted on the fourth page of the Report, and reference to same to be made under framing, etc., on the first page.

5c.4.10.—T.

PARTICULARS FOR RECORD in the REGISTER BOOK.—Length of Poop ft., R.Q.D. ft., Bridge ft., Forecastle ft. (in feet and tenths). When the Poop is joined to the B.D., this should be distinctly stated.

No. and Material of Decks (if Iron or Steel) and whether wholly or partially covered with wood, and No. of tiers of Beams (this information is to be given as it should appear in the Register Book) Shelter deck. Electric light. Submarine signalling. Wireless. Longitudinal framing.

Official No. 221269; Signal Letters M.C.S.Q. State if Machinery is fitted aft Yes

How are the surfaces preserved from oxidation? Inside Outside Paints

PARTICULARS OF WATER BALLAST.—State whether the Double bottom is constructed on the cellular system or with girders on floors Cellular system

Where Fitted.	*Length. Feet.	Water Capacity. Tons.	Where Fitted.	*Length. Feet.	Water Capacity. Tons.
Double bottom, aft,			Fore peak tank,	25'-3"	257.85
Double bottom, under Engines and Boilers,	67'-6"	198.88	After peak tank,	24'-11"	142.27
Double bottom, if under Engines only,			Deep tank, aft,		
Double bottom, if under Boilers only,			Deep tank, forward,	54'-0"	646
Double bottom, forward,			Other tanks, if fitted,		
			(If necessary, furnish further information by sketch.)		

* The wells are not to be included in the lengths of the tanks.

State whether the above have been tested as required by the Rules Yes

Order for Special Survey No. _____

Date _____

No. 48 in builder's yard.

DATES OF SURVEYS held while building 1920 Jan 3. 8. 18 Aug 2. 10. 22 25 Sep. 20 Oct 7 Nov. 1. 8. 10. 13. 19. 20. 26. 29 Dec. 11. 16. 24. 27. 29. 30 1921 Jan 4. 5. 14. 26. 27. 28. 29 Feb. 7. 14. 18. 28 Mar. 9. 15. 22. 23. 25. 29 Apr. 1. 4. 6. 7. 8. 9. 11. 13. 14. 15. 16. 18. 20. 22. 23. 25. 26. 28 May 3. 4. 5. 6. 7. 9. 10. 11. 12. 17. 19. 24. 27 June 13

Surveyor's Signature John Mac Lachlan

Total No. of Visits _____

Lloyd's Register Foundation