

# Lloyd's Register of Shipping.

## SURVEYS FOR FREEBOARD.

 Index. No. \_\_\_\_\_  
 (For London Office only.)

Computation of Freeboard for Steamer, Sailing Ship, Tanker

having C. S. S.

(Type of Superstructures.)

Ship's Name Nakslov. Nationality and Port of Registry Yard No 178. Official Number ✓ Gross Tonnage ✓ Date of Build ✓

Moulded Dimensions: Length 390 Breadth 57 Depth 27.50

Moulded displacement at moulded draught = 85 per cent. of moulded depth

Coefficient of fineness for use with Tables 74. (assumed) tons

Port of Survey \_\_\_\_\_

Date of Survey \_\_\_\_\_

Name of Surveyor \_\_\_\_\_

Particulars of Classification \_\_\_\_\_

Depth for Freeboard (D)		Depth correction		Round of Beam correction	
Moulded depth	27.50	(a) Where D is greater than Table depth	1.53	Moulded Breadth (B)	
Stringer plate	.03	(D-Table depth) R =	(27.53 - 26.00) = 1.53	Standard Round of Beam = $\frac{B \times 12}{50}$	=
Sheathing on exposed deck		(b) Where D is less than Table depth (if allowed)		Ship's Round of Beam	= Standard
$T \left( \frac{L-S}{L} \right) =$		(Table depth-D) R =	4.59	Difference	
Depth for Freeboard (D) =	27.53	If restricted by superstructures	✓	Restricted to	
				Correction = $\frac{\text{Diff}^2}{4} \times \left( 1 - \frac{S_1}{L} \right)$	= Nil

## DEDUCTION FOR SUPERSTRUCTURES.

	Mean Covered Length (S)	Equivalent Enclosed Length (S <sub>1</sub> )	Height	Height Correction	Effective Length (E)
Poop enclosed ...					
" overhang ...					
R.Q.D. enclosed ...					
" overhang ...					
Bridge enclosed ...					
" overhang aft ...					
" overhang forward ...					
F'cle enclosed ...					
" overhang ...					
Trunk aft ...					
" forward ...					
Tonnage opening aft ...					
" " forward ...					
Total ...					

Standard Height of Superstructure 7.40

" " R.Q.D. ✓

Deduction for complete superstructure 41.33

Percentage covered  $\frac{S}{L} =$

" "  $\frac{S_1}{L} =$

" "  $\frac{E}{L} =$  } 100%

Percentage from Table, Line A.  
(corrected for absence of forecastle (if required))

Percentage from Table, Line B.  
(corrected for absence of forecastle (if required))

Interpolation for bridge less than 2L (if required)

Deduction = -41.33

## SHEER CORRECTION.

Station	Standard Ordinate	S	M	Product	Actual Ordinate	Effective Ordinate	S	M	Product
A.P. ...		1			+7.2"		1		
$\frac{1}{2}L$ from A.P. ...		4					4		
$\frac{3}{8}L$ " ...		2					2		
Amidships ...		4					4		
$\frac{3}{8}L$ from F.P. ...		2					2		
$\frac{1}{2}L$ " ...		4					4		
F.P. ...		1					1		
Total ...					+7.20"				

Correction =  $\frac{\text{Difference between sums of products}}{18} \left( .75 - \frac{S}{2L} \right) = - .60"$

If limited on account of midship superstructure. ✓

If limited to maximum allowance of  $1\frac{1}{2}$  ins. per 100 ft. ✓

## Deduction for Tropical Freeboard.

## Addition for Winter and Winter North Atlantic Freeboard.

Depth to Freeboard Deck = 27.53 Ft.

Summer freeboard = 2.84

Moulded draught (d) = 24.69

Deduction for Tropical freeboard and addition for Winter freeboard =  $\frac{d}{4}$  inches =

Addition for Winter North Atlantic Freeboard (if required) =

## Deduction for Fresh Water.

Displacement in salt water at summer load water line

Tons per inch immersion at summer load water line

Deduction =  $\frac{\Delta}{40T}$  inches

## TABULAR FREEBOARD corrected for Flush Deck (if required)

Correction for coefficient

Depth Correction ...

Deduction for superstructures ...

Sheer correction ...

Round of Beam correction ...

Correction for Thickness of Deck amidships ...

Other corrections, scantlings, etc. ...

Summer Freeboard = 34.08

## SUMMER FREEBOARD amidships from Centre of Disc to top of Deck Line, Wood, Steel, Deck:-

Tropical Fresh Water Line above Centre of Disc ...

Fresh Water Line " " ...

Tropical Line " " ...

Winter Line below " " ...

Winter North Atlantic Line " " ...

Tropical Fresh Water Freeboard ...

Fresh Water " " ...

Tropical " " ...

Winter " " ...

Winter North Atlantic " " ...

Summer Moulded Draft = 24.69 Ft.