

DISCLOSED SECTION NO 321

LLOYD'S REGISTER OF SHIPPING.

(CLASSIFICATION SOCIETY RECOGNISED BY THE JAPANESE GOVERNMENT)

SURVEY FOR FREEBOARD.

Ship's Name "HAKUBASAN MARU"	Port of Registry --	Official No. --	No. in R.B. --	Gross Tonnage about 6500	Tonnage under Fbd. Deck = V 5921.94	Date of Launch 29th Sept. 1928	Date when Built --	Report Number 53
Owners Nippon Yusen Kaisha.		Builders Mitsui Bussan Kaisha.			Yard No. 150	Port of Survey Kobe.		
Type of vessel Decked with upper Bridge & Fo'c'sle	Particulars of Classification * 100 A.1. full scantling.		Position of Freeboard Deck Upper deck		Date of Survey While Building			
					Name of Surveyor W. Kimber and H.J. Cox.			

PRINCIPAL DIMENSIONS.

Length between perpendiculars 435 ft.	Breadth Moulded = B ₀ 56.5 ft.	Depth Moulded to Fbd. deck = D ₀ 33.0 ft.
Length on Load Line 435 ft.	Thickness of Side plating in ins. x 3/12°68 + .17 ft.	Round of Beam 1.17 ft.
Length for Freeboard = L 435 ft.	Breadth for Freeboard = B 56.67 ft.	Depth from base line to top of inner bottom plating or ordinary floors 3.79 ft.
		Depth for Tonnage Coef. (Art. 39) = 30.38 ft.

CORRECTION TO TONNAGE (Art. 39)

Correction to Tonnage between top of ceiling on double bottom or ordinary floors as fitted and standard level of top of ceiling (v) = **- 3.73** tons.

DEPTH OF DOUBLE BOTTOM (Art. 39)

Depth of Actual Double Bottom (including plating) or Ordinary Floors	45.52 ins.
Depth of Standard Double Bottom (including plating) or Ordinary Floors	45.52 ins.
Difference	0
x 1/12 =	0 = d.

SHEER (Arts. 39 and 60-63)

Ordinate	Height of Sheer in inches.	S.M.	Products
1 A.P.	60.00	1	60.00
2	29.52	4	118.08
3	7.98	2	15.96
4	0.00	4	0.00
5	15.00	2	30.00
6	55.70	4	222.80
7	114.00	1	114.00
Sum of Products =			560.84
Mean Height of Sheer = S = $\frac{\text{Sum of Products}}{18}$ =			31.16 ins.
Standard Mean Height = S ₀ = $\frac{1}{3}(L/10 + 10)$ =			17.83 ins.
Difference $13.33 \times \frac{1}{12}$ =			1.11 ft. = d ₁
Correction (Arts. 60-63) = $\frac{3}{4}(1-e)(S_0 - S)$ =			-7.25 ins.

FRAMING (Art. 39)

Between Frames	Length in ft.	Depth of Frame in ins.	Thickness of Sparring in inches	Total depth in inches	Products ft. x inches
0 - 10	20.00	6.5	-	6.5	130
10 - 33	63.25	9.0	2	11.0	695.75
33 - 66	90.75	12	2	14.0	1270.50
66 - 95	79.75	12	-	12	957.00
95 - 129	93.50	12	2	14.0	1309.00
129 - 139	22.50	11	2	13	292.50
139 - 158	42.75	12	2	14.0	598.50
158 - R.P.	22.50	8	0	8.0	180.00
Sum of Products =				12.49	5433.25
Sum of Products = Actual Mean Depth of framing				12.49	ins.
Length of Ship				8.50	ins.
Standard " " " "				3.99	ins.
Difference $3.99 \times \frac{2}{12}$ =				.67	= 2b

COEFFICIENT OF FINENESS (Art. 37 or 43)

$$\frac{100(V + v)}{L(B - 2b)(D + d + d_1) + n} = \frac{35 \times \Delta}{L \times B_0 \times d_0} + 0.04$$

= $\frac{591821}{435 \times 56 \times (30.38 + 0 + 1.11)} = .77$ = $\frac{35 \times 12.49}{3700 \times 25} + 0.04 = .77$

See plans.

Sketch showing arrangement and height of double bottom or ordinary floors and of superstructures (unless complete plans are submitted).

2 1/2" Ceiling on Battens throughout except in Machy. Space and Deep Tank.

Standard depth of C.d.b. = 45.52 + 2.5 = 48.02
 Actual " " " = 45.52 + 3.0 = 48.52

No Ceiling in Machy. Space & D. Tank.
 $\frac{13800 \times .04}{100} = + 5.52$ $\frac{3700 \times .25}{100} = -9.25$
 Net correction - 3.73.

Sketch of deck erections showing openings in end bulkheads and position and arrangement of closing appliances. Hatchways, and Engine and Boiler openings also to be shown. Extent and thickness of wood deck or composition to be shown in red ink, and extent and thickness of ceiling (and battens) on tank top to be given.



本證明書發行條件

WOOD DECK (Arts. 5 and 6)			
	Mean Length in ft.	Thickness in ins.	Products
Forecastle	33.75	1	
Bridge	121.00	3.5-.40	575.83
Poop or R.Q.D.	31.00	3.1	
Open Deck, ford.			
.. .. aft.			
Total length = l =		Sum of Products = 575.83	
Sum of Products = t =		ins. ; Sum of Products = t ₁ = 1.32 ins.	

CORRECTION FOR DEPTH & CORRECTION FOR FREEBOARD.
 If no sheathing fitted amidships = t₁ = ± 1.32 ins. (Arts. 6 and 57 p. 1)
 If sheathing is fitted amidships = (t - t₁) = ± 0 ins. (Arts. 6 and 57 p. 2)
 * Note: Use the upper sign in correction for depth and the lower sign in correction for freeboard.

DEPTH TO USE IN FREEBOARD TABLE.			
Depth moulded	33 ft. 0	ins.	
Thickness of Stringer Plate	.40		
Thickness of Wood Deck Amidships	33.0.40		
Correction for partial wood deck	± 1.32		
Depth to use in Freeboard Tables	33 ft. 1.72	ins. = D ₁ = 33.14 ft.	

SUPERSTRUCTURES.				
HEIGHT (Arts. 46-48)				
Standard Height = (0.018 L + 1.2) ft. = 7.5 feet.				
	Complete Superstructure	Forecastle	Bridge	Poop or R.Q.D.
Actual		7.39	7.65	7.39
Standard		7.5	7.5	7.5

CLOSING APPLIANCES (Arts. 50 and 54)				
	Forecastle	Bridge		Poop or Raised Quarter Deck
	Hinged Doors	Forward End. Intact	After End. Hinged Doors	Hinged W.T. Steel Doors
Corresponding Class	II	I	II	I

EFFECTIVE LENGTH (Arts. 55 and 56)				
	Mean Length	Coef. Art. 56	Height Coef.	Products.
Forecastle closed part	33.75	1	.99	33.41
.. open part	121.00	1	1.00	121.00
Bridge closed part				
.. open part ford.				
.. .. aft.				
Poop closed part	31.00	1	.99	30.69
.. open part				
Total Effective Length =		185.10		

$\frac{\text{Total Effective Length}}{\text{Length of Vessel}} = r = .43$
 Corresponding Coef. in Table (Art. 49) = e = .275
 Reduction for Complete Superstructure = 39.00 ins.
 Product = 10.73 ins.
 Correction for Superstructures = 10.73 ins.

EFFECTIVE LENGTH (Shelter Deck Vessels Arts. 87-92)
 $l + \frac{1}{2}(1-p)(L-l) =$ ft.
 (* See Art. 90)

CORRECTION FOR PROPORTIONS L/D (Art. 58)
 When D₁ is less than 35 ft. = $\frac{D_1 + 16}{300} (1 - e/2) (L - 12 D_1)$
 greater than 35 ft. = $0.17 (1 - e/2) (L - 12 D_1)$
 [Note e = 1.0 if more than 9/10 covered] = $\frac{49.14 \times .862 \times 37.32}{300} = +5.27$ ins.

Are the Engine and Boiler openings covered by a Bridge, Poop, Raised Quarter Deck or enclosed by a strong steel deck house? **Bridge**
 If openings are not so protected give thickness of plating and scantlings and spacing of stiffeners of Casings **--**
 Are suitable means provided for closing all openings in them in bad weather? **Yes**
 State the vertical distance from base line at top of keel to lower edge of lowest side scuttle **Above freeboard deck.**
 State if there are any cargo ports or scuppers through sides of vessel below upper deck **No.**
 State any special features in the construction of the vessel **--**
 Sister vessels **--**
 Fee, Yen.; Depth of Keel ins.; Draught (btm. keel) ft. ins.

CORRECTION FOR ROUND OF BEAM (Art. 59)
 Standard Round of Beam = $\frac{\text{Length of Beam in ins.}}{50} = 13.34$ ins.
 Correction = $\frac{1}{4} (\text{Standard Round of Beam} - \text{Actual Round of Beam})$
 = $\frac{1}{4} (13.34 - 14.00) = -.17$ ins.

CORRECTION FOR FREEING PORTS
 (in vessels less than 15 ft. Depth Art. 64)
 Length of bulwark in feet each side **--** ft.
 Area of Freeing ports each side **--** sq. ft.
 Area of Freeing ports required by Table **--** sq. ft.
 Correction 1.2 (r - 0.5) D₁ = + **--** ins.

CORRECTION FOR ACCESS TO CREW'S QUARTERS (Arts. 65-67)
 Are Crew berthed in Bridge House or Forecastle? **--**
 Height and breadth of gangway **--**
 Correction = $-.012 (80 - l) D_1$ or $1.2 (r - 0.5) D_1$ **-- = + --** ins.

SUMMARY.		
Freeboard by Tables	99.04	ins.
Correction for Sheer	+ 7.25	
.. .. Partial Wood Deck	1.32	
.. .. Superstructures	10.73	
.. .. Proportions L/D	5.27	
.. .. Round of Beam	.17	
.. .. Freeing Ports	-	
.. .. Access to Crew's Quarters	-	
Totals	5.27	19.47
Net Correction		14.20
Geometric Freeboard		84.84
Corresponding Geometric Draught (mid.)		25.97
Moulded Draught limited by $\frac{\text{form transverse strength}}{\text{longitudinal strength}}$ to $\frac{\text{position of side scuttles}}{\text{position of side scuttles}}$		25.97
Corresponding Freeboard (Summer)		84.8

Winter Freeboard (Art. 22) = $\frac{1}{4} (D_1 - 10) + \frac{r}{45} (59 - D_1)$
 = $\frac{1}{4} (23.14 - 10) + \frac{.43}{45} (59 - 23.14) = +6.03$ ins.
 Tropical Freeboard (Art. 24) do. do. = -6.03 ins.

Winter North Atlantic Fbd. (Art. 23) Vessels 330 ft. and below.
 Ratio of effective length of superstructures to length of vessel
 Additional Freeboard + -- ins.

Fresh Water Freeboard (Art. 27)
 $\frac{1}{4}$ " per foot of Summer Draught = -6.49 ins.

FREEBOARD TO BE ASSIGNED.
 Vertical distance from upper edge of horizontal line indicating the freeboard deck to the centre of the disc. (Summer Line) 84.8 ins.
 Fresh Water Load Line above centre of disc. 6.5 ins.
 Tropical Load Line above " " " 6.0 ins.
 Winter Load Line below " " " 6.0 ins.
 Winter N.A. Load Line below " " " -- ins.
 Vertical distance from the point of intersection of the extended line of the upper surface of **stl. str.** of the upper deck at mid length of the vessel with the outside of shell plating to the upper edge of the horizontal line indicating the freeboard deck 0.00 ins.

DETAILS OF CONSTRUCTION OF WEATHER DECK HATCHWAYS.

	No. 1	No. 2 & 6	No. 3 & 5	No. 4	No. 5	No. 6
Length and Breadth	31'6" x 22'	27'6" x 22'	30'3" x 22'	16'0" x 22'		
Height above deck and thickness of side and end coaming	37" x .44	37" x .44	37" x .44	24" x .44		
Shifting Beams	5 Steel 20 x .38 5x3 1/2 x .44	4 Steel 20.5 x .38 5x3 1/2 x .44	5 steel 19 x .36 5x3 1/2 x .44	2 steel 15 x .34 5x3 1/2 x .44		
*Fore and Afters	None	None	None	None		
Thickness of hatches		All 3"				
Remarks	* When the fore and afters are of wood the depth should be stated from the underside of hatches.					

LONGITUDINAL MODULUS.											
BELOW ASSUMED AXIS.						ABOVE ASSUMED AXIS.					
Item	Scantlings	Area	Lever	Moment	Mt. of Inertia	Item	Scantlings	Area	Lever	Moment	Mt. of Inertia
Flat Keel						Top Deck Str.					
Centre Girder					 Plating					
C.G. btm. ang.					 "					
C.G. top angles					 Str. Ang.					
T.T. Cr. Strake						2nd Deck Str.					
T.T. plating					 Plating					
.. .. "					 "					
.. .. "					 Str. Ang.					
Margin Plate						3rd Deck Str.					
.. .. "					 Plating					
.. Angle					 "					
Shell Strake A					 "					
.. .. B					 Str. Ang.					
.. .. C						Sheerstrake					
.. .. D						Strake below					
.. .. E						Shell Strake					
.. .. F					 "					
.. .. G					 "					
Totals below assumed axis						Totals above assumed axis					
.. above assumed axis						Neutral Axis above assumed axis (x) =					
Sum or Difference						Correction = (Total Area x x ² x 2) =					
						Moment of Inertia about Neutral Axis					
						Distance from Neutral Axis to top of Strength deck beam at side =					
						Keel					
						MODULUS OF SECTION =					
						Actual Modulus =					
						f. B ₀					

DRAUGHT PERMITTED BY LONGITUDINAL STRENGTH (Arts. 81-86) = $\frac{\text{Actual Modulus}}{f. B_0} =$

TRANSVERSE MODULUS.
 Minimum Side Plating (Art. 77) $\frac{0.105 \times +17}{100} =$; Standard Frame Spacing (Art. 78) = $-.025 \times +17 =$
 Actual Side Plating = ; Actual Frame Spacing =
 If actual frame spacing exceeds the standard $\sqrt{\frac{\text{Actual frame spacing}}{\text{Standard frame spacing}}} t =$
 Moulded Geometric Draught (d) = H = **PULL SCANTLING VESSEL**
 t = K = $\frac{H}{K} =$
 d - t = $\frac{H}{K} =$
 Standard $I/y = \frac{s(d-t)(f_1 + f_2)}{1000} =$
 Frame in ship = at spacing, $I/y =$
DRAUGHT PERMITTED BY TRANSVERSE STRENGTH = $\frac{I/y \times 1000}{s(f_1 + f_2)} + t =$

