

# REPORT ON ELECTRIC LIGHTING INSTALLATION. No. 1896

Port of Montreal Date of First Survey Jan 7 Date of Last Survey May 3 No. of Visits 9  
 No. in Reg. Book on the Iron or Steel S. S. "CANADIAN LEADER" Port belonging to Montreal  
 Built at Montreal By whom Canadian Dick's Ltd. When built 1921  
 Owners Canadian Government Merchant Marine Owners' Address St James St. Montreal  
 Yard No. 80 Electric Light Installation fitted by Builders When fitted 1921

## DESCRIPTION OF DYNAMO, ENGINE, ETC.

1- 13 1/2 Kw BTM dynamo direct coupled to Ashworth Parker fuel lubrication single cylinder engine

Capacity of Dynamo 122.7 Amperes at 110 Volts, whether continuous or alternating current continuous.

Where is Dynamo fixed Engine room bottom platform Whether single or double wire system is used single

Position of Main Switch Board " " " " having switches to groups A-B-C-D-E of lights, &c., as below

Positions of auxiliary switch boards and numbers of switches on each Distribution boxes fitted. 1 in Engine room 1 in below pantry, 1 in Engineers pantry 1 in crew quarters 1 in chart room 1 in carpenter's cabin 1 in Engine casing & 1 on upper deck

If fuses are fitted on main switch board to the cables of main circuit Yes and on each auxiliary switch board to the cables of auxiliary circuits Yes and at each position where a cable is branched or reduced in size Yes and to each lamp circuit Yes

If vessel is wired on the double wire system are fuses fitted to both flow and return wires or cables of all circuits including lamp circuits Yes

Are the fuses of non-oxidizable metal Yes and constructed to fuse at an excess of 80 per cent over the normal current

Are all fuses fitted in easily accessible positions Yes Are the fuses of standard dimensions Yes If wire fuses are used are permanent instructions fitted on or near each switch board giving particulars of proper size of fuse for each circuit Best fuse used

Are all switches and fuses constructed of incombustible materials and fitted on incombustible bases Yes

Total number of lights provided for arranged in the following groups :-

A. <u>Food Accommodation</u>	<u>76</u> lights each of <u>2-16cp 3-15W 12-25W</u> <sup>59-40W</sup> candle power requiring a total current of <u>25.6</u> Amperes
B. <u>Aft</u>	<u>24</u> lights each of <u>2-1cp 1-16cp 15-40W</u> <sup>6-25W</sup> candle power requiring a total current of <u>7.5</u> Amperes
C. <u>Navigation</u>	<u>31</u> lights each of <u>10-2cp 8-16cp 6-8cp</u> <sup>2-32cp 5-40W</sup> candle power requiring a total current of <u>10.5</u> Amperes
D. <u>Engine &amp; Boiler Room</u>	<u>46</u> lights each of <u>5-16cp 4-32cp 37-40W</u> candle power requiring a total current of <u>20.0</u> Amperes
E. <u>Large space &amp; cluster</u>	lights each of <u>41-32cp 8-40W</u> candle power requiring a total current of <u>45.5</u> Amperes
<u>2</u> Must head light with <u>2</u> lamps each of <u>16</u> candle power requiring a total current of <u>1.08</u> Amperes	
<u>2</u> Side light with <u>2</u> lamps each of <u>P. 16 S 32</u> candle power requiring a total current of <u>1.56</u> Amperes	
<u>5</u> Cargo lights of <u>6</u> lights each <u>32</u> candle power, whether incandescent or arc lights <u>Incandescent</u>	

If arc lights, what protection is provided against fire, sparks, &c. ✓

Where are the switches controlling the masthead and side lights placed On indicator in Wheel house

## DESCRIPTION OF CABLES.

Main cable carrying 122.7 Amperes, comprised of 19 wires, each .084" S.W.G. diameter, .105 square inches total sectional area

Branch cables carrying 22.5 Amperes, comprised of 7 wires, each .0613" S.W.G. diameter, .02 square inches total sectional area

Branch cables carrying 31.7 Amperes, comprised of 7 wires, each .048" S.W.G. diameter, .0129 square inches total sectional area

Leads to lamps carrying 5 Amperes, comprised of 7 wires, each .024" S.W.G. diameter, .0032 square inches total sectional area

Cargo light cables carrying 6 Amperes, comprised of 27 wires, each .01 S.W.G. diameter, .002 square inches total sectional area

## DESCRIPTION OF INSULATION, PROTECTION, ETC.


Rubber insulated, lead covered & Armoured cables. 30% pure para rubber used. Lead covering 1/32 thick on sizes to .25" diam & proportionately thicker on larger sizes.

Joints in cables, how made, insulated, and protected None

Are all the joints of cables thoroughly soldered, and the flux used not containing acids or other corrosive substances ✓ Are all joints in accessible positions, none being made in bunks, cargo spaces, or spaces which may at any time be used for carrying cargo, stores, or baggage ✓

Are there any joints in or branches from the cable leading from dynamo to main switch board No.

How are the cables led through the ship, and how protected blipped to decks & bulkheads by double ended clips. In bunks covered with sheet steel casing.



**DESCRIPTION OF INSULATION, PROTECTION, ETC.—continued.**

Are they in places always accessible *Yes except for a short run through bunkers (bridge space)*

What special protection has been provided for the cables in open alleyways or where exposed to weather or moisture *Lead covered and armored*

What special protection has been provided for the cables near galleys or oil lamps or other sources of heat *ditto.*

What special protection has been provided for the cables near boiler casings *ditto.*

What special protection has been provided for the cables in engine room *ditto.*

How are cables carried through beams *in lead bushings* through bulkheads, &c. *WT glands*

How are cables carried through decks *WT deck tubes.*

Are any cables run through coal bunkers *No* or cargo spaces *Yes* or spaces which may be used for carrying cargo, stores, or baggage *Yes*

If so, how are they protected *By steel steel galvanized plating & conduit.*

Are any lamps fitted in coal bunkers or spaces which may at times be used for cargo, coals, or baggage *Yes*

If so, how are the lamp fittings and cable terminals specially protected *Lamps in heavy cast guards & cable in conduit.*

Where are the main switches and fuses for these lights fitted *In distribution box in E.R.*

If in the spaces, how are they specially protected

Are any switches or fuses fitted in bunkers *No.*

Cargo light cables, whether portable or permanently fixed *Permanent to WT switchboard* How fixed *Flush to structure.*

In vessels fitted on the single wire system, how is the dynamo terminal fixed to the hull of vessel

How are the returns from the lamps connected to the hull

Are all the joints with the hull in accessible positions

Is the installation supplied with a voltmeter *Yes*, and with an amperemeter *Yes*, fixed *On main switchboard*

**VESSELS BUILT FOR CARRYING PETROLEUM.**

In vessels built for carrying petroleum, are all switches and fuses fitted in positions not liable to the accumulation of petroleum vapour or gas

Are any switches, fuses, or joints of cables fitted in the pump room or companion

How are the lamps specially protected in places liable to the accumulation of vapour or gas

The copper used is guaranteed to have a conductivity of not less than that of the Engineering Standards Committee's standard, and the wires are protected by tinning from the sulphur compounds present in the insulating material.

Insulation of cables is guaranteed to have a resistance of not less than *1500* megohms per statute mile at 60° Fahrenheit after 24 hours' immersion in water, the test being made after one minute's electrification at not less than 500 volts and while the cable is still immersed.

The foregoing statements are a correct description of the Electric Light installation fitted by us on this vessel and we declare that it is at this date in good order and safe working condition.

*M. Miller*

Electrical Engineers

Date

**COMPASSES.**

Distance between dynamo or electric motors and standard compass *107 feet*

Distance between dynamo or electric motors and steering compass *98 feet*

The nearest cables to the compasses are as follows:—

A cable carrying <i>10.5</i> Amperes	<i>12</i> feet from standard compass	<i>5</i> feet from steering compass
<i>No single wire is run within 12 ft of compasses.</i>	feet from standard compass	feet from steering compass
A cable carrying _____ Amperes	feet from standard compass	feet from steering compass
A cable carrying _____ Amperes	feet from standard compass	feet from steering compass

Have the compasses been adjusted with and without the electric installation at work at full power

The maximum deviation due to electric currents, etc., was found to be \_\_\_\_\_ degrees on \_\_\_\_\_ course in the case of the standard compass and \_\_\_\_\_ degrees on \_\_\_\_\_ course in the case of the steering compass.

*M. Miller*

Builder's Signature.

Date

**GENERAL REMARKS.**

*This installation has been fitted on board and tried out under varying loads with satisfactory results. The materials and workmanship are good.*

*It is submitted that*

*this vessel is eligible for*

*THE RECORD. See light*  
*Recd 17/6/21*

*N. J. Alderson*

Surveyor to Lloyd's Register of Shipping.

Committee's Minute *FRI. 17 JUN. 1921*

*Per. J. H. H. 20/6/21 \$67.00*

1m. 7.10.—Transfer.



© 2020

Lloyd's Register Foundation

THE SURVEYORS ARE REQUESTED NOT TO WRITE ACROSS THIS MARGIN.