

**REPORT ON ELECTRICAL EQUIPMENT.**

(OTHER THAN FOR THE PROPULSION OF THE VESSEL)

19 FEB 1949

Received at London Office

Date of writing Report 1<sup>st</sup> DEC 1948 When handed in at Local Office 1<sup>st</sup> DEC 1948 Port of NEW YORK NY.  
 No. in Survey held at HOBOKEN N.J. Date, First Survey 25<sup>th</sup> OCT Last Survey 19<sup>th</sup> NOV 1948  
 Reg. Book. 25055 on the SS HADIDTIS EX NIKI Tons { Gross 7240 Net 4390  
 Built at JACKSONVILLE FLA By whom built ST JOHN'S RIVER SHIP CO Yard No. 80 When built 1945  
 Owners KASSOS STEAM NAVIGATION CO Port belonging to SYRA  
 Electric Light Installation fitted by ✓ Contract No. ✓ When fitted ✓  
 Is the Vessel fitted for carrying Petroleum in bulk No

System of Distribution TWO WIRE DIRECT CURRENT  
 Pressure of supply for Lighting 120 volts, Heating - volts, Power 120 volts,  
 Direct or Alternating Current, Lighting DIRECT Power DIRECT  
 If alternating current system, state frequency of periods per second -  
 Has the Automatic Governor been tested and found efficient when the whole load is suddenly thrown on or off YES  
 Generators, do they comply with the requirements regarding temperature rise AIEE STANDARDS 40°C RISE A, are they compound wound YES  
 are they over compounded 5 per cent. No, if not compound wound state distance between each generator ✓  
 Where more than one generator is fitted are they arranged to run in parallel YES, is an adjustable regulating resistance fitted in series with each shunt field YES Have certificates of test results for machines under 100 kw. been submitted and approved ✓ Have machines over 100 kw. been inspected by the Surveyors during manufacture and testing ✓  
 Are all terminals accessible, clearly marked, and furnished with sockets YES, are they so spaced or shielded that they cannot be accidentally earthed, short circuited, or touched YES Are the lubricating arrangements of the generators as per Rule YES  
 Position of Generators IN ENGINE ROOM, STARBOARD SIDE ON FIRST LEVEL GRATING, is the ventilation in way of the generators satisfactory YES are they clear of all inflammable material YES if situated near unprotected woodwork or other combustible material, state distance of same horizontally from or vertically above the generators ✓ and ✓  
 are the generators protected from mechanical injury and damage from water, steam or oil YES, are their axes of rotation fore and aft YES  
 Earthing, are the bedplates and frames of the generating plant efficiently earthed YES are the prime movers and their respective generators in metallic contact YES Main Switch Boards, where placed IN ENGINE ROOM ON GENERATOR FLAT  
 If the generators and main switchboard are not placed in the same compartment, is each generator provided with a fuse on each insulated pole as near as possible to the terminals of the generator, additional to that provided on the main switchboard ✓  
 Switchboards, are they placed in accessible positions, free from inflammable gases and acid fumes YES, are they protected from mechanical injury and damage from water, steam or oil YES, if situated near unprotected woodwork or other combustible material, state distance of same horizontally from or vertically above the switchboards ✓ and ✓, are they constructed wholly of durable, non-ignitable non-absorbent materials EBONY ASBESTOS, is all insulation of high dielectric strength and of permanently high insulation resistance YES  
 is it of an approved type YES, if semi-insulating material is used, are all conducting parts insulated from the slab with mica or micanite or other non-hygroscopic insulating material, and the slab similarly insulated from its framework ✓, is the non-hygroscopic insulating material of an approved type YES, and is the frame effectively earthed YES Are the fittings as per Rule regarding:—spacing or shielding of live parts AIEE STANDARDS, accessibility of all parts YES, absence of fuses on back of board YES, temperature rise of omnibus bars YES, individual fuses to voltmeter, pilot or earth lamp. NO, EACH GENERATOR VOLTMETER AND PILOT LIGHT ON SAME FUSE, are moving parts of switches alive in the "off" position No are all screws and nuts securing connections effectively locked YES are any fuses fitted on the live side of switches No Main Switchgear, description of switchgear for each generator and each outgoing circuit, and arrangement of equalizer switches EACH GENERATOR, 175 AMP D.P. BREAKER WITH OVERLOAD AND REVERSE CURRENT TRIP AND A THREE POLE ISOLATING SWITCH. OUTGOING CIRCUITS, D.P. LINKED SWITCHES AND FUSES.  
 Are turbine driven generators fitted with emergency trip switch as per rule ✓ Are cupboards or compartments containing switchboards composed of fire-resisting material or lined with approved material YES Instruments on main switchboard 3 ammeters 3 volt-meters ✓ synchronizing device for paralleling purposes. For compound machines is the ammeter connected on the opposite pole to equalizer connection YES Earth Testing, state what means are provided at the main switchboard for indicating the state of the insulation of the system EARTH LAMPS ALSO VOLTMETER SELECTOR SWITCH WIRED TO GIVE GROUND READINGS, Circuit Breakers and Fusible Cut-outs, do these comply with the requirements of the Rules AIEE STANDARDS are the fusible cutouts of an approved type AIEE STANDARDS have the reversed



current protection devices been tested under working conditions.....YES Joint Boxes, Section and Distribution Boards, is the construction, protection, insulation, material, and position of these as per Rule ALIEE STANDARDS

Cables: Single, twin, ~~concentric~~, or multicore YES are the cables insulated and protected as per Tables IV, V, X or XI of the Rules ALIEE STANDARDS

If the cables are insulated otherwise than as per Rule, are they of an approved type YES Fall of Pressure, state maximum between bus bars and any point of the installation under maximum load 3 VOLTS Cable Sockets, are the ends of all cables having a sectional area of 0.04 square inch and above provided with soldering sockets.....YES Paper Insulated and Varnished Cambric Insulated Cables.

If conductors are paper or varnished cambric insulated, is the dielectric at the exposed ends of the conductor protected from moisture by being suitably sealed with insulating compound.....YES, or waterproof insulating tape.....YES Cable Runs, are the cables fixed as far as possible in accessible positions not exposed to drip or accumulation of water or oil, or to high temperature from boilers, steam pipes, uptakes or other hot objects, or to avoidable risk of mechanical damage.....YES Are cables in machinery spaces, galleys, laundries, bathrooms and lavatories lead covered or run in conduit LEAD COVERED

Support and Protection of Cables, state how the cables are supported and protected CLIPPED IN STEEL SUPPORTS IN ACCOMMODATION AND HOLDS. PROTECTED BY SHEET METAL GUARDS IN HOLD SPACES

If cables are run in wood casings, are the casings and caps secured by screws.....YES, are the cap screws of brass.....YES, are the cables run in separate grooves.....YES If armoured and lead covered cables are secured by metal clips, are the clips spaced as per Table VIII ALIEE STANDARDS

Refrigerated Chambers, are the cables and fittings in accordance with the special requirements YES

Joints in Cables, state if any, and how made, insulated, and protected IN JUNCTION BOXES

Watertight Glands and Deck Tubes, are all cables passing through decks and watertight bulkheads provided with deck tubes or watertight glands YES Bushes in Beams and Non-watertight Partitions, where unarmoured cables pass through beams and non-watertight partitions, are the holes efficiently bushed ARMOURD state the material of which the bushes are made CABLES ALL

Earthing Connections, state what earthing connections are fitted and their respective sectional areas CABLES EFFECTIVELY EARTHED

....., are their connections made as per Rule YES

Alternative Lighting, are the groups of lights in the propelling machinery space arranged as per Rule YES Emergency Supply, state position and method of control of the emergency supply and how the generator is driven YES

Navigation Lamps, are these separately wired YES controlled by separate switch and separate fuses YES are the fuses double pole NO. ALIEE STANDARDS

are the switches and fuses grouped in a position accessible only to the officers on watch IN WHEEL HOUSE

has each navigation lamp an automatic indicator as per Rule YES Secondary Batteries, are they constructed and fitted as per Rule YES

Fittings, are all fittings on weather decks, in stokeholds and engine rooms and wherever exposed to drip or condensed moisture, watertight YES

are any fittings placed in spaces in which goods are liable to be stacked in close proximity to them; if so, how are they protected CAST METAL GUARDS

are any fittings placed in spaces where inflammable or explosive dust or gases are liable to be present, if so, how are they protected YES

....., how are the cables led YES

where are the controlling switches situated YES

are all fittings suitably ventilated YES are all switches and lampholders constructed wholly of non-ignitable, non-absorbent materials YES

Heating and Cooking Appliances, are they constructed and fitted as per Rule YES are air heaters constructed and fitted as per Rule YES

Searchlight Lamps, No. of ONE whether fixed or portable YES are their fittings as per Rule YES

Are Lamps, other than searchlight lamps, No. of YES are their live parts insulated from the frame or case.....YES are their fittings as per Rule YES

Motors, are their working parts readily accessible YES are the coils self-contained and readily removable for replacement YES

are the brushes, brush holders, terminals and lubricating arrangements as per Rule YES are the motors placed in well-ventilated compartments in which inflammable gases cannot accumulate and clear of all inflammable material YES are they protected from mechanical injury and damage from water, steam or oil YES are their axes of rotation fore and aft WHERE POSSIBLE if situated near unprotected woodwork or other combustible material, are the motors of the totally enclosed, pipe ventilated, forced draught, drip or flame proof type DRIP PROOF

....., if not of this type, state distance of the combustible material horizontally or vertically above the motors.....YES and YES

have machines of over 100 BPH been inspected by the Surveyors during manufacture and testing YES Control Gear and Resistances, are the generator field and motor speed regulators, starters and controllers constructed and fitted as per Rule ALIEE STANDARDS

Lightning Conductors, where lightning conductors are required, are these fitted as per Rule YES Ships carrying Oil having a Flash Point less than 150°F. Have the special requirements of the Rules been complied with regarding switches, joint boxes, section and distribution boards, protection of cables, method of distribution, lead of cables, lights and fittings.....YES are all fuses of the filled cartridge type YES are they of an approved type YES

If portable lamps for use in dangerous spaces are supplied, are they of a self-contained, battery-fed type approved by the Home Office YES

Spare Gear, if the vessel is for open sea service have spares been supplied as per Rule YES

PARTICULARS OF GENERATING PLANT.										
DESCRIPTION OF GENERATOR.	No. of	RATED AT				DRIVEN BY	WHERE DRIVEN BY AN INTERNAL COMBUSTION ENGINE.			
		Kilowatts.	Volts.	Amperes.	Revs. per Min.		Fuel Used.	Flash Point of Fuel.		
MAIN ... ..	3	20	120	167	400	STEAM RECIPROCATING				
AUXILIARY ... ..										
EMERGENCY ... ..										
ROTARY TRANSFORMER										
GENERATOR, LIGHTING AND HEATING CONDUCTORS.										
DESCRIPTION.	CONDUCTORS.		COMPOSITION OF STRAND.		TOTAL MAXIMUM CURRENT. AMPERES.		Approximate Length. (Lead and Return.) Feet.	Insulated with	HOW PROTECTED	
	No. per Pole.	Total Nominal Area per Pole Sq. Ins.	No.	Diameter.	Circuit.	Rule.				
MAIN GENERATOR ... ..	1	.1969	37	.082	167	✓ 233	52	RUBBER	LC & BASKET WEAVE ARMOURD	
EQUALISER CONNECTIONS ... ..	1	.0324	7	.077	-	75	25	V.C.	" " " "	
AUXILIARY GENERATOR ... ..										
EMERGENCY GENERATOR ... ..										
ROTARY TRANSFORMER (MOTOR ... ..)										
BOILER ROOM LIGHTING ... ..	1	.0521	7	.097	58	✓ 74*	40	RUBBER	" " " "	
BOILER ROOM ... ..										
AUXILIARY SWITCHBOARDS ... ..										
SALINITY INDICATOR ... ..	1	.002	-	-	1	10*	80	"	" " " "	
MIDSHIP ACCOMMODATION ... ..	1	.0521	7	.097	48	✓ 74*	180	"	" " " "	
AFT ACCOM. ... ..	1	.0521	7	.097	25	✓ 74*	440	"	" " " "	
BOAT DECK ACCOM. ... ..	1	.0829	19	.074	48	✓ 100*	190	"	" " " "	
WHEELHOUSE ... ..	1	.020	7	.061	16	✓ 41*	240	"	" " " "	
GYRO COMPASS ... ..	1	.013	7	.048	15	✓ 41*	200	V.C.	" " " "	
WIRELESS ... ..	1	.020	7	.061	22	✓ 41*	290	RUBBER	" " " "	
SEARCHLIGHT ... ..	1	.008	7	.038	5	✓ 23*	420	"	" " " "	
MASTHEAD LIGHT ... ..	1	.0032	7	.024	42	✓ 11.5*	440	"	" " " "	
SIDE LIGHTS ... ..	1	.0032	7	.024	42	✓ 11.5*	110	"	" " " "	
COMPASS LIGHTS ... ..	1	.0032	7	.024	2	✓ 11.5*	100	"	" " " "	
BRIDGE DECK LIGHTS ... ..	1	.0829	19	.074	50	✓ 100*	200	"	" " " "	
CARGO LIGHTS FORWARD ... ..	1	.0521	7	.097	25	✓ 74*	420	"	" " " "	
ARC LAMP MIDSHIP ... ..	1	.0829	19	.074	57	✓ 100*	190	"	" " " "	
HEATERS " AFT ... ..	1	.0521	7	.097	23	✓ 74*	270	"	" " " "	
MOTOR CONDUCTORS.										
DESCRIPTION.	No. of Motors.	CONDUCTORS.		COMPOSITION OF STRAND.		TOTAL MAXIMUM CURRENT. AMPERES.		Approximate Length. (Lead and Return.) Feet.	Insulated with	HOW PROTECTED
		No. per Pole.	Total Nominal Area per Pole Sq. Ins.	No.	Diameter.	In Circuit.	Rule.			
BALLAST PUMP ... ..										
MAIN BILGE LINE PUMPS ... ..										
GENERAL SERVICE PUMP ... ..										
EMERGENCY BILGE PUMP ... ..										
SANITARY PUMP ... ..										
CIRC. SEA WATER PUMPS ... ..										
CIRC. FRESH WATER PUMPS ... ..										
AIR COMPRESSOR ... ..										
FRESH WATER PUMP ... ..										
ENGINE TURNING GEAR ... ..										
ENGINE REVERSING GEAR ... ..										
LUBRICATING OIL PUMPS ... ..										
OIL FUEL TRANSFER PUMP ... ..										
WINDLASS ... ..										
WINCHES, FORWARD ... ..										
WINCHES, AFT ... ..										
STEERING GEAR—										
(a) MOTOR GENERATOR ... ..										
(b) MAIN MOTOR ... ..										
WORKSHOP MOTOR ... ..										
VENTILATING FANS ... ..										
REFRIG. COMP. ... ..	1	1	.0658	19	.066	59	✓ 87*	200	RUBBER	LC & BASKET WEAVE ARMOURD
X AMERICAN INSTITUTE OF ELECTRICAL ENGINEERS. CURRENT RATING FOR TWO AND THREE CONDUCTOR CABLES. TABLE N° 9.										



All Conductors are of annealed copper conforming to British Standard Specification No. 7 (or International Electro-technical Commission Publication No. 28).

The Insulated Conductors are guaranteed to withstand the immersion and resistance tests specified in the Rules.

The foregoing is a correct description.

✓  
Electrical Engineers.

Date ✓

#### COMPASSES.

Distance between electric generators or motors and standard compass 26 FEET

Distance between electric generators or motors and steering compass 20 FEET

The nearest cables to the compasses are as follows:—

A cable carrying 2 Ampères .75 feet from standard compass .75 feet from steering compass.

A cable carrying 1 Ampères 4 feet from standard compass 7 feet from steering compass.

A cable carrying ✓ Ampères ✓ feet from standard compass ✓ feet from steering compass.

Have the compasses been adjusted with and without the electric installation at work at full power YES

Has the effect of switching on and off circuits, motors and other electro-magnetic apparatus within the vicinity of the compasses been noted YES

The maximum deviation due to electric currents was found to be NIL degrees on ANY course in the case of the standard compass, and NIL degrees on ANY course in the case of the steering compass.

✓  
Builder's Signature.

Date ✓

Is this installation a duplicate of a previous case YES If so, state name of vessel SS VIKDAL (RPTN° 47695)

General Remarks (State quality of workmanship, opinions as to class, &c.)

The electrical installation to the requirements of the American Bureau of Shipping has been in operation since 1945. The plans attached to the above mentioned Report are in accordance with A.I.E.E. Marine Standards & generally in accordance with the Rules.

The materials and workmanship are good and the installation has been examined under working conditions and found to be satisfactory.

The dimensions in this Report have been taken from the A.B.S. approved plans. These dimensions have been checked as far as possible on the ship and found correct.

In our opinion the electrical installation is such as could be accepted by the Committee for Classification.

Noted. ✓ 24/3/49.

Total Capacity of Generators 60 ✓ Kilowatts.

The amount of Fee ... £ \$100.00. : { When applied for, Feb 9 1949  
Traveling Expenses (if any) £ : : { When received, 19

W. Bloomfield + W. W. W. W.  
Surveyor to Lloyd's Register of Shipping.

Committee's Minute NEW YORK FEB 2 - 1949

Assigned ELEC. LIGHT



© 2021

Lloyd's Register  
Foundation