



BEAMS

BEAMS CUT AND BRACKETED TO CYL. TANKS, WHERE CLOSED CONV. ANGLE CANNOT BE EFFICIENTLY RIVETED, SET BRACKETS ARE FITTED AS SHOWN IN DETAIL.

BEAMS 6x3x.30x23.0\" CHAM. FITTED ON EVERY FRAME.

BREADTH	54.00
DEPTH	32.75
TRANSVERSE NUMBER	86.75
LENGTH	401.00
LONGITUDINAL NUMBER	34786.75

EQUIPMENT

EQUIPMENT: 54x32.75x401.0 = 34786.75

POOP 98.0, BRIDGE 27.0, FORE 81.0

126.0xHT 75 = 1276.00x.75 = 957.00

TANK 225x725x2 = 816.00

CASING 72.0x7.50x2 = 1270.00

36829.00

3 BOWER ANCHORS, STOCKLESS 63x CWTs (112 LBS)

1 STREAM DO. EXCLUDING STOCK 17x CWTs

1 KEDGE " " 7x

270 FATHOMS 2x 5/8\"/>

SECTION BETWEEN CYLINDRICAL TANKS

DIMENSIONS - 401'-0\"/>

CONTR 2338-35-350
341-2-3-4-5

G. 66x70x50

DOUBLE BATS TO BE FITTED AT SHORT BRACKETS AT SIDES OF TANKS AND FORWARD OF LENGTH.

ABOUT 75x.44 FOR 1/2 L. 50 AT ENDS. BUTTS QUADRUPLE RIVETED TREBLE AT ENDS.

Midship Section
S.L. "Silverbrook"



009815-009826-0160



© 2021

Lloyd's Register
Foundation