

# Awning or Shelter Deck, or Pt. Awning Deck.

# STEEL STEAMER.

THU. JUL. 22 1920

No. 19897

19912

State if Report is also sent on the Machinery of the Vessel.

Port of **NEWPORT, MON.** Date of completion of Report

Received at London Office

Survey held at **CHEPSTOW, MON.**

Date, First Survey **5th. November 1918**

Last Survey **14 July 1920**

On the **S.S. "WAR LLIAD" now renamed "SILE"**

Rig **Fore & aft Schooner**

TONNAGE under Tonnage Deck... **6261.20**

CLASS **+100A1 Shelter Deck.** FEET.

Master **Francesco Guli**

Do. between Tonnage Dk. and 3rd, 4th, or Awning Dk.

Breadth (greatest moulded) **55.46**

Year of Appointment (1) As Master in service of owner of present vessel: 1920 (2) As Master of this vessel: 1920

Total under Upper Dk.

Depth, at middle of length from top of keel to top of beams at side of uppermost Continuous Deck **38.04**

Built at **CHEPSTOW, MON.**

Do. of Poop

Deduct height of 'tween deck when this does not exceed 8ft. **30.04**

When built **1920 - 7mo** Launched **17th. July 1920**

Do. of Bridge House

Transverse Number **85.50**

By whom built **The Monmouth Shipbuilding Co. Ltd.**

Do. of Forecastle (House in) **9.10**

Length on deck from fore part of stem to after part of sternpost **411.50**

Owners **Soc. Nav. Italiana**

Do. of Houses on Deck **226.40**

Longitudinal Number **35183**

Managers **Gen. ...**

Do. of excess of Hatchways **42.04**

Depth "d" at middle of length. See Secs. 2 & 13 **25.10**

Port belonging to **London**

Do. above Crown of Engine Room **12.61**

Proportions, Depths to Length, Uppermost Continuous Deck at side to top of keel **10.81**

Residence **London**

Gross Tonnage **6551.35**

Destined Voyage **?**

If Surveyed while Building, Afloat, or in Dry Dock **Building**

Less Crew Space **250.38**

Upper Deck at side to top of keel **14.36**

Less above Crown of Engine Room **12.61**

Deck at side to top of keel **10.81**

TONNAGE FOR FEES... **6288.36**

Less Engine Room **2096.43**

Less Navigation Spaces **164.33**

Less above Crown of Engine Room **12.61**

Crew Space **250.38**

Register Tonnage **4040.19**

LENGTH on Deck as per Rule	Ft.	Ins.	BREADTH Moulded	Ft.	Ins.	DEPTH, ACTUAL Do.	Top of Floors to top of Awning or Shelter Dk. Beams	Ft.	Ins.	No. of Decks with flat laid	Two	No. of Tiers of Beams	Two
411	6		55	5 1/2		38	0 1/2	25	6 1/4				

Dimensions of Ship per Register, Length **412.4** breadth **55.8** depth **25.1** Upper Deck. Moulded depth, ft. **38** ins. **0 1/2** To Awning or Shelter Dk. Round up of Uppermost Dk. Beam, Actual **38** ins. **7 3/4** To Upper Dk. **Nil** ins.

FRAMING.				FORGINGS AND CASTINGS.			
Inches in Ship	Inches in Ship	Inches in Ship	Inches per Rule Or as Approved	Inches in Ship	Inches in Ship	Inches per Rule Or as Approved	Inches per Rule Or as Approved
FRAME, Angles or L or E Dk., amidships				KEEL, Bar, depth and thickness			
9	4	48	9 4 48	STEM, moulding and thickness			
Do. in peaks	9	4	48	STERN POST for Rudder do. do.			
Do. in way of Double Bottoms at Solid Floors	3 1/2	3 1/2	42 40	" " for Propeller			
Spacing of Frames from centre to centre amidships	35		35	RUDDER-A x D Table 22 Speed 11 kts.			
" length to collision bulkhead	28		28	" Main Piece, diameter at head			
" of Frames from centre to centre in peaks	24 1/2		24 1/2	" " " " at heel			
REVERSED FRAME, Angles	9	4	48	RUDDER, how constructed Single Plate (1.18") with arms shrunken & keyed at each pulley.			
FRAMING, depth of girder	14 1/2		14 1/2	Can the Rudder be unshipped afloat? Yes			
FLOORS, depth and thickness of Floor Plate at mid line for 1 length amidships	4 1/2	ES. 40; 85.50	4 1/2 ES. 40 85.50	KEELSONS AND STRINGERS.			
" in way of Engine and Boiler spaces	4 1/2	ES. 40; 85.50	4 1/2 ES. 40 85.50	CENTRE LINE KEELSON, Vertical Plate above floors, Through Plate, or Intercoastal Plate			
" thickness at the ends of vessel	4 1/2	ES. 40; 85.50	4 1/2 ES. 40 85.50	" Rider Plate			
" depth at 1/2 the half bath as per Rule	4 1/2	ES. 40; 85.50	4 1/2 ES. 40 85.50	" Flat Keel Plate Angles			
" height extended at the Bilges	4 1/2	ES. 40; 85.50	4 1/2 ES. 40 85.50	" Horizontal Plates on Floors			
FLOORS & BRACKETS, in Cell Dble Bottoms state if flanged (top & bottom) spacing	4 1/2	ES. 40; 85.50	4 1/2 ES. 40 85.50	" Angles or Bulb Angles			
" " " "	4 1/2	ES. 40; 85.50	4 1/2 ES. 40 85.50	SIDE KEELSONS, Number			
CENTRE GIRDER, in Dbl. bottom, dpth. & thickness	4 1/2	ES. 40; 85.50	4 1/2 ES. 40 85.50	" Angles or Bulb Angles			
" " " Angles, Top	4 1/2	ES. 40; 85.50	4 1/2 ES. 40 85.50	" Plate above floors, for length			
" " " Bottom	4 1/2	ES. 40; 85.50	4 1/2 ES. 40 85.50	" Intercoastal Plate, for length			
" " " to Floors	4 1/2	ES. 40; 85.50	4 1/2 ES. 40 85.50	" Attached to outside plating with Angle			
SIDE GIRDERS, number and thickness	4 1/2	ES. 40; 85.50	4 1/2 ES. 40 85.50	BILGE KEELSON, Angles			
" " " state if flanged (top & bottom)	4 1/2	ES. 40; 85.50	4 1/2 ES. 40 85.50	" Intercoastal Plate, for length			
" " " Angles	4 1/2	ES. 40; 85.50	4 1/2 ES. 40 85.50	" Attached to outside plating with Angle			
MARGIN PLATE, depth (exclusive of flange) and thickness	4 1/2	ES. 40; 85.50	4 1/2 ES. 40 85.50	SIDE STRINGERS, Number			
" " " HORIZONTAL	4 1/2	ES. 40; 85.50	4 1/2 ES. 40 85.50	" " " Angle			
" " " to outside plating	4 1/2	ES. 40; 85.50	4 1/2 ES. 40 85.50	" " " Intercoastal Plate, for 1st 55' lng.			
" " " to floors	4 1/2	ES. 40; 85.50	4 1/2 ES. 40 85.50	" " " Attached to outside plating with Angle			
" " " Height of Brackets above at bilge	4 1/2	ES. 40; 85.50	4 1/2 ES. 40 85.50	Awning or Shelter Deck Stringer Plates, breadth and thickness			
INNER BOTTOM PLATING, breadth and thickness of Middle Line Strake	4 1/2	ES. 40; 85.50	4 1/2 ES. 40 85.50	" " " Angle on ditto			
" " " thickness in Engine and Boiler space	4 1/2	ES. 40; 85.50	4 1/2 ES. 40 85.50	" " " Tie Plates, fore and aft, outside Hatchways			
" " " Remainder in Holds	4 1/2	ES. 40; 85.50	4 1/2 ES. 40 85.50	" " " Deck * Iron or Steel, for whole lng.			
BEAMS, Awning or Shelter Dk., Single Angle, Bulb Angle, Plate, Tee Bulb or Channel	9	3 1/2	44	" " " Wood Deck, Material & thickness			
" " " Angles on upper edge	9	3 1/2	44	Upper or Second Deck Stringer Plate, breadth and thickness			
" " " Spacing	35	28	24 1/2	" " " Angles on ditto, No. 7			
BEAMS, Upper or Second Deck, Single Angle, Bulb Angle, Plate, Tee Bulb or Channel	10	3 1/2	50	" " " Tie Plates, outside Hatchways			
" " " Angles on upper edge	10	3 1/2	50	" " " Deck * Iron or Steel, for whole lng.			
" " " Spacing	35	28	24 1/2	" " " Wood Deck, Material & thickness			
BEAMS, Third or Fourth Deck, Single Angle, Bulb Angle, Plate, Tee Bulb or Channel	9	3 1/2	44	Third Deck Stringer Plates, breadth & thickness			
" " " Angles on upper edge	9	3 1/2	44	" " " Angles on ditto, No.			
" " " Spacing	35	28	24 1/2	" " " Tie Plates, outside Hatchways			
BEAMS, Fourth or Fifth Deck, Plate, Tee Bulb or Channel	10	3 1/2	50	" " " Deck * Material and thickness			
" " " Angles on upper edge	10	3 1/2	50	Fourth and Fifth Deck Stringer Plate, breadth and thickness			
" " " Spacing	35	28	24 1/2	" " " Angles on ditto, No.			
BEAMS, Poop Deck, Angle, Bulb Angle, Plate, Tee Bulb or Channel	9	3 1/2	44	" " " Tie Plates, outside Hatchways			
" " " Angles on upper edge	9	3 1/2	44	" " " Deck, Material and thickness			
" " " Spacing	35	28	24 1/2	Poop Deck Stringer Plate, breadth & thickness			
BEAMS, Bridge Deck, Angle, Bulb Angle, Plate, Tee Bulb or Channel	8	3	46	" " " Angles on ditto			
" " " Angles on upper edge	8	3	46	" " " Tie Plates			
" " " Spacing	24 1/2		24 1/2	" " " Deck, Material and thickness			
PILLARS, in 'tween Deck, size and spacing	24 1/2		24 1/2	Bridge Deck Stringer Plate, breadth & thickness			
" " " Hold	24 1/2		24 1/2	" " " Angles on ditto			
" " " Quarter, 'tween Dks., " "	24 1/2		24 1/2	" " " Tie Plates			
" " " in Hold	24 1/2		24 1/2	" " " Deck, Material and thickness			
WEB FRAMES, in Fore Body, No. and spacing	24 1/2		24 1/2	Forecastle Deck Stringer Plate, breadth & thickness			
" " " breadth & thickness	24 1/2		24 1/2	" " " Angles on ditto			
" " " No. of Side Stringers	24 1/2		24 1/2	" " " Tie Plates			
WEB FRAMES, in E. & B. Space, No. and spacing	24 1/2		24 1/2	" " " Deck, Material and thickness			
" " " breadth & thickness	24 1/2		24 1/2	Poop Deck Stringer Plate, breadth & thickness			
" " " No. of Side Stringers	24 1/2		24 1/2	" " " Angles on ditto			
WEB FRAMES, in After Body, No. and spacing	24 1/2		24 1/2	" " " Tie Plates			
" " " breadth & thickness	24 1/2		24 1/2	" " " Deck, Material and thickness			
" " " No. of Side Stringers	24 1/2		24 1/2	Bridge Deck Stringer Plate, breadth & thickness			
BRACKET PLATES to Stringers between Web Frames, depth and thickness	24 1/2		24 1/2	" " " Angles on ditto			



