





[illegible][illegible]



GENERAL REMARKS (continued)

PARTICULARS FOR RECORD in the REGISTER BOOK.—Length of Poop ☒ ft., R.Q.D. 73 ft., Bridge ☒ ft., Forecastle 21 ft.  
(in feet and tenths). When the Poop is joined to the B.D., this should be distinctly stated ☒

No. and Material of Decks (if Iron or Steel) and whether wholly or partially covered with wood, and No. of tiers of Beams (this information is to be given as it should appear in the Register Book) 1 steel dk.

Official No. ☒; Signal Letters ☒ State if Machinery is fitted aft Yes  
How are the surfaces preserved from oxidation? Inside Paint & Cement Outside paint

PARTICULARS OF WATER BALLAST.—State whether the Double bottom is constructed on the cellular system or with girders on floors

Where Fitted.	Length. Feet.	Water Capacity. Tons.	Where Fitted.	Length. Feet.	Water Capacity. Tons.
Double bottom, aft,			Fore peak tank,		
Double bottom, under Engines and Boilers,			After peak tank,		
Double bottom, if under Engines only,			Deep tank, aft,		
Double bottom, if under Boilers only,			Deep tank, forward,		
Double bottom, forward,			Other tanks, if fitted,		
			(If necessary, furnish further information by sketch.)		
Total capacity of double bottom					

\* The wells are not to be included in the lengths of the tanks.

State whether the above have been tested as required by the Rules.

Order for Special Survey No.

Date

No. in builder's yard.

DATES OF SURVEYS held while building

1908 Jan. 9, 11, 18, Feb. 8, Mar. 8, Apr. 3, 15, 17, 23, 29, 30 May 3, 6, 7, 13, 21, 24, 28  
Jun. 12, 15, 17, 24, 25, 29 July 16, 13, 19, 23, 29, 30 Aug. 6, 22, 22, Sept. 9, 16, 19  
Sep. 24, 30 Oct. 17, 18, 19, 22, 23, 26, 28, 30

Total No. of Visits 48

Surveyor's Signature

J. L. Davis

Lloyd's Register Foundation