

Forecastle? Yes  
end? Yes  
Yes

556  
28846

Preliminary (amended)

J.8.

Index No. 28846  
(For London Office only.)

# Lloyd's Register of Shipping.

## SURVEYS FOR FREEBOARD.—STEAM SHIPS.

ARTICULARS RELATING TO ALL STEAM SHIPS EITHER FLUSH DECKED, OR WITH TOP GALLANT FORECASTLES, SHORT POOPS AND BRIDGE HOUSES DISCONNECTED, OR WITH TOP GALLANT FORECASTLES HAVING LONG POOPS, OR RAISED QUARTER DECKS CONNECTED WITH BRIDGE HOUSES, OR OTHERWISE.

Port of Survey Nagasaki  
Date of Survey 23. 9. 20  
Name of Surveyor

Ship's Name	Port of Registry and Nationality	Official Number	Gross Tonnage	Date of Build	Particulars of Classification
<u>Yubichi</u>					<u>100 A1</u>
<u>346-7-8</u>					<u>Contempe.</u>
in Register Book					

LENGTH.	BREADTH.	DEPTH.	UNDER DECK TONNAGE.
<u>495</u>	<u>62.27</u>	<u>34.16</u>	<u>8265</u>
<u>495</u>	Frame Depth <u>12</u> Ceiling <u>7</u> Rule <u>5</u> Sheer <u>+0.84</u>	Peak <u>5</u> Tanks <u>level tank</u>	
<u>495</u>	<u>61.43</u>	<u>35.0</u>	<u>8265</u>

Moulded Depth as Swain measured 37-0  
Addition for Keel below base line for draught record.....inches.

NOTE.— If the depth is measured when vessel is afloat, the details of measurement should be reported.

CORRECTION FOR LENGTH.	
Length of Ship on Loadline.....	<u>495</u>
Length in Table .....	<u>444</u>
Difference .....	<u>51</u>
Correction for 10ft., Table A. ....	<u>1.7</u> Table C.
× Difference divided by 10 .....	<u>8.67</u> (if required.)
If $\frac{1}{10}$ ths length covered divide by 2	<u>4.33 + 4.34</u>

CORRECTION FOR IRON DECK.	
Proportion covered, if less than $\frac{1}{10}$ ths length covered .....	
Thickness of usual wood deck, less stringer .....	<u>3 1/2" wood sheathing</u>

CORRECTION FOR ROUND OF BEAM.	
Breadth at Gunwale amidships.....	<u>62</u>
Round of Beam .....	<u>15 1/2</u>
Normal round.....	<u>15 1/2</u>
Difference .....	<u>÷ 2 =</u>
Proportion of Deck uncovered (Para. 19) .....	

NOTE.— The round of beam should be reported on the full breadth of vessel at the gunwale.

fineness..... 777  
tion necessary {  
a) to (e)]\* }  
s corrected ..... Ray. 76 provisionally  
120 } 180 ÷ 2 = 90 ... Mean  
npost ... 60  
f the length from { Stem 66 } 99 ÷ 2 = 49.5 ... Mean  
                              { Sternpost 33 } ÷ .55  
an Sheer ..... 90 = 90  
ean Sheer [Table, Para. 18] ..... 59.5 Correction  
Difference..... 30.5 ÷ 4 =  
as Para. 18 (f) ..... - 7 1/2  
Sheer { At front of bridge house.....  
ships {  
(e)] { At after end of forecastle .....  
Sheer {  
(d) } ÷ 2 =  
covered ..... Correction

ALLOWANCE FOR DECK ERECTIONS:—  
Table C... (10-4 1/2) - (3-2) 7-2 1/2  
for Length, if required (Para. 12, 13, and 14) .....  
by Table A. corrected for sheer, and for length, if required (Para. 12, 13, and 14) 9-9  
as below..... 2-6 1/2  
43%  
13.11

Length.	Length allowed.	Height.
<u>54.8</u>	<u>54.8</u>	
<u>186 (94 closed)</u>	<u>163.0</u>	<u>8-1</u>
<u>94</u>	<u>94.0</u>	
Total <u>334.8</u>	<u>311.8</u>	
of Ship <u>495 = .676</u>	<u>495 = .63</u>	
ponding percentage { a. 11, 12, 13, or 14) <u>43%</u>		

for R. Q. Dk. if engine and boiler openings not covered by bridge house (Para. 11)  
for Deck Erections ..... -13

Freeboard, Table A .....	<u>10-4 1/2</u>
Correction for Sheer .....	<u>- 7 1/2</u>
Correction for Length .....	<u>+ 4 1/2</u>
Allowance for Deck Erections .....	<u>- 1-1</u>
Correction for Round of Beam.....	<u>9-0 1/2</u>
Correction for fall in Sheer (if any).....	
Correction for Iron Deck (if required) .....	
Additions for non-compliance with provisions of Para. 11 (d) and (e) ‡	
Other Corrections (if any) <u>To correspond to subdivision loadline of 28'0" moulded</u>	<u>+ 3 1/2</u>
	<u>9-3 3/4</u>

Winter Freeboard .....	
Summer Freeboard .....	<u>9-3 3/4</u>
Indian Summer Freeboard .....	
N. A. Winter Freeboard .....	
Correction necessary because clearside amidships, measured in accordance with the Statute is not taken at the intersection of the wood or iron deck with side.	<u>134</u>


Winter Freeboard from deck line .....	
Summer " " " " .....	<u>9-5 1/2"</u>
Indian Summer " " " " .....	
N. A. Winter " " " " .....	

FREEBOARD recommended amidships from centre of Disc to top of Statutory Deck Line, Wood (W) Deck:—

Fresh Water Line	above centre of Disc	<u>37-0 1/2</u>
Indian Summer Line	" " "	<u>3 1/2</u>
Winter Line	below " "	<u>13/16</u>
Winter North Atlantic Line	" " "	<u>37-5 3/16</u>

⊙ If the frames, skin planking, or ceiling are of unusual thickness the breadth of vessel to inside of ceiling should be reported if possible.  
† In vessels obtaining an allowance for deck erections under Para. 11 where the sheer drops abaft amidships the height of the R.Q.D. is to be taken from the level of the top of the amidship beam.  
‡ In flush-decked vessels the total standard mean sheer means the sheer measured at the stem and stern-post. In vessels having poops and forecastles, it means the sheer measured at points distant one-eighth of the vessel's length from stem and stern-post.

State dimensions of freeing port area on back of this form.  
The Surveyor should state whether the fall in sheer as reported is measured relatively to the straight line of keel or to the water line. If measured relatively to water line the vessel's draft at time of survey, and also the usual load draft forward and aft should be reported.



© 2021

Lloyd's Register Foundation