

Preliminary

28 DEC 1927

Index No. 3260
(For London Office only.)

Lloyd's Register of Shipping.

SURVEYS FOR FREEBOARD. STEAM SHIPS.

GLASGOW REPORT NO. 47+52

PARTICULARS RELATING TO ALL STEAM SHIPS EITHER FLUSH DECKED, OR WITH TOP GALLANT FORECASTLES, SHORT POOPS AND BRIDGE HOUSES DISCONNECTED, OR WITH TOP GALLANT FORECASTLES HAVING LONG POOPS, OR RAISED QUARTER DECKS CONNECTED WITH BRIDGE HOUSES, OR OTHERWISE.

Port of Survey ARDROSSAN
Date of Survey 27th DEC 1927
Name of Surveyor

Ship's Name. <u>Cardrossan Deck No. 340</u> <u>Motor Tanker</u>	Port of Registry and Nationality. <u>LONDON</u> <u>BRITISH</u>	Official Number. ✓	Gross Tonnage. ✓	Date of Build. ✓	Particulars of Classification. <u>+ 100A1 WITH FREEBOARD</u> <u>(CONTD)</u>
Number in Register Book					

Moulded Registered dimensions from Ship's Register.	LENGTH.	BREADTH.	DEPTH.	UNDER DECK TONNAGE. ABOUT
	205.0	36'-6"	15'-0"	800
Length on LOADLINE.	205.0	Mean Frame Depth 6" Rule " 4" x2 = -.33 Breadth est. 36.70 Nosparings +.33	Ceiling +.20 No Sheer +.15 Depth of floor 14.00	Peak Tanks } incl. Depth D.B. } in M.S. } +15.7.
CORRECTED DIMENSIONS.	205.0	36.70	14.35	815

Moulded Depth as measured..... 15'-0"
Addition for Keel below base line for draught record..... inches.

NOTE. - If the depth is measured when vessel is afloat, the details of measurement should be reported.

Co-efficient of fineness..... .755
Any modification necessary [Para. 4 (a) to (e)]* }
Co-efficient as corrected76 ✓

CORRECTION FOR LENGTH

Length of Ship on Loadline.....	205
Length in Table	180
Difference	25
Correction for 10ft., Table A.	1.0 Table C. ✓
x Difference divided by 10	2.5 (if required.)
If 1/10ths length covered divide by 2	1.25 +1/4" ✓

Sheer { Stem..... 48"
at { Sternpost ... 24"} 72 ÷ 2 = 36 ✓ ...Mean 36 1/2 .50
Sheer at 1/3 of the length from { Stem 26.4"
Sternpost 13.2"} 39.6 ÷ 2 = 19.8 ✓ ...Mean 19.8
Gradual mean Sheer 36.00
Standard mean Sheer [Table, Para. 18] 30.50
Difference..... 5.50 ÷ 4 = 1.375
§ If limited as Para. 18 (f) -1/4" ✓

CORRECTION FOR IRON DECK.
Proportion covered, if less than 1/10ths length covered ✓
Thickness of usual wood deck, less stringer 3" -3" ✓

Rise in Sheer from amidships [Para. 18 (e)] { At front of bridge house..... ✓
At after end of forecastle ✓
Fall in Sheer } Para. 18 (d) } ÷ 2 =
Length uncovered ✓ Correction

CORRECTION FOR ROUND OF BEAM.
Breadth at Gunwale amidships..... 36'-6"
Round of Beam 9"
Normal round..... 9.12
Difference 12 ÷ 2 =06
Proportion of Deck uncovered (Para. 19) 17-23 ✓

NOTE. - The round of beam should be reported on the full breadth of vessel at the gunwale.

ALLOWANCE FOR DECK ERECTIONS :-
Freeboard, Table C..... 0'-7" ✓
Correction for Length, if required (Para. 12, 13, and 14) ✓
Freeboard by Table A, corrected for sheer, and for length, if required (Para. 12, 13, and 14) } 2'-4 3/4"
Difference 1'-9 3/4"
Percentage as below..... 56.78% 62.68%
13.63
12.35
Correction for R. Q. Dk. if engine and boiler openings not covered by bridge house (Para. 11) } ✓
Allowance for Deck Erections 12 1/4 13 3/4"

Freeboard, Table A 2'-6" ✓
Correction for Sheer - 1/4"
Correction for Length 2'-4 3/4" ✓
Allowance for Deck Erections -1'-1 3/4" 0 1/4 ✓
Correction for Round of Beam..... 1'-4 1/4 5 3/4" ✓
Correction for fall in Sheer (if any)..... ✓
Correction for Steel Deck (if required) - 3"
Additions for non-compliance with provisions of Para. 11 (d) and (e) † }
Other Corrections (if any) 1'-1 1/4 2 3/4" ✓
Winter Freeboard 1'-1 1/4 2 3/4" ✓
Summer Freeboard 2" 0'-1 1/4 1'-0 3/4" ✓
Indian Summer Freeboard 0'-9 1/4 10 3/4" ✓
N. A. Winter Freeboard 4" 1'-3 1/4 4 3/4" ✓

	Length.	Length allowed.	Height.
Forecastle.....	43.0	43.00	7.5
TRUNK			
Bridge House.....	96.0 x 23.0W.D.E. x 8 = 36.5	60.50 48.40	4.5
† Raised Qr. Dk.....	66.0	66.00	4.5
Poop.....			
Total 205.0		169.50 157.40	
Length of Ship	205		82.68 76.78
Corresponding percentage } (Para. 11, 12, 13, or 14) } 62.68% 56.78% ✓			

Correction necessary because clearside amidships, measured in accordance with the Statute is not taken at the intersection of the wood or steel deck with side. } 1/2"
Winter Freeboard from deck line 1'-2 3/4" 4 1/4" ✓
Summer " " " " 1'-0 3/4" 2 1/4" ✓
Indian Summer " " " " 0'-10 3/4" 1'-0 1/4" ✓
N. A. Winter " " " " 1'-4 3/4" 6 1/4" ✓

FREEBOARD recommended amidships from centre of Disc to top of Statutory Deck Line, Wood (Steel) Deck :-
Fresh Water Line above centre of Disc ... 3 1/2"
Indian Summer Line " " " " ... 2"
Winter Line below " " " " ... 2"
Winter North Atlantic Line " " " " ... 1.4"

* If the frames, skin planking, or ceiling are of unusual thickness the breadth of vessel to inside of ceiling should be reported if possible.
† In vessels obtaining an allowance for deck erections under Para. 11 where the sheer drops abaft amidships the height of the R.Q.D. is to be taken from the level of the top of the amidship beam.
§ In flush-decked vessels the total standard mean sheer means the sheer measured at the stem and stern-post. In vessels having poops and forecastles, it means the sheer measured at points distant one-eighth of the vessel's length from stem and stern-post.

† State dimensions of freeing port area on back of this form.
‡ The Surveyor should state whether the fall in sheer as reported is measured relatively to the straight line of keel or to the water line. If measured relatively to water line the vessel's draft at time of survey, and also the usual load draft forward and aft should be reported.

Do all the Frames extend to the top height in the Poop? Raised Quarter Deck? YES Bridge House? Forecastle? YES

To what height do the Reverse Frames extend? BULB BULK FRAMES

Has the Poop or Raised Quarter Deck an efficient Iron Bulkhead at the fore end? YES

Give particulars of the means for closing the openings in Bulkhead NONE

Is the Poop or Raised Quarter Deck connected with the Bridge House? Has the Bridge House an efficient Bulkhead at the fore end?

Give particulars of the means for closing the openings in Bulkhead

What is the thickness of the Bridge Front plating? and Coaming plate?

Give scantlings and spacing of the Stiffeners

Are bracket plates fitted at each end of the Stiffeners? Are hor'l. brackets fitted connecting Bridge Bulk'd. with Bulwarks?

Has the Bridge House an efficient Iron Bulkhead at the after end?

How are the openings closed?

Is the Forecastle at least as high as the main or top-gallant rail? YES Has the Forecastle an efficient Iron or Wood Bulk'd. at after end? YES

Are the Engine and Boiler openings covered by a Bridge, Poop, Raised Quarter Deck, or enclosed by a Strong Iron or Steel Deckhouse? YES

If the openings are not so protected are the exposed parts of the Casings efficiently constructed?

Give thickness of plating; scantlings and spacing of Stiffeners

What is the height of the exposed Casings? Are suitable means provided for closing all openings in them in bad weather?

Are the Weather Deck Hatchways efficiently constructed and at least equal to the requirements of Section 28 of the Rules for 1904-5? Give particulars below:—

Position and Size.		Ship.	Rule.								
COAMING	Height above top of DECK										
	Thickness { Sides..... Ends.....										
SHIFTING BEAMS OR WEB PLATES.	Number										
	Section and Scantlings										
	Material										
* FORE AND AFTERS.	Number										
	Section and Scantlings										
	Material										
HATCHES	Thickness										
	Remarks.....										

* The depth of Fore and Afters should be stated from the underside of the hatches in all cases.

(If the sill of the lowest side scuttle will be less than 6 inches above the Indian Summer Load Line if assigned under the tables, state vertical distance from top of deck at side amidships to lower edge of lowest side scuttle.)

The following information is to be given in all Cases of vessels dealt with under Paras. 11, 12 (under 15 feet Moulded depth) and under Shelter Deck Rules.

What is the thickness of the Bridge Sheerstrake? _____ Strake between Main and Bridge Sheerstrakes? _____


Delete the words The Crew are, are not, berthed in the bridge house.
that do not apply The arrangements to enable them to get backwards and forwards from their quarters are, are not satisfactory.

Length of Bulwarks in well _____

Area of Freeing Ports required by Para. 11 (e) each side of vessel = _____ Sq. ft.

Ft. Tenths.	Ft. Tenths.	No.	} Freeing Ports (each side of vessel) = _____ Sq. ft.
x	x	x	
x	x	x	

Total deficiency or excess = _____ Sq. ft.



Show hereon line of Floors or Tank Top with position of any Breaks in same; also height of Peak Tank tops, &c., &c.

State any special features in the construction of the Vessel NO COVERING ON FREEBOARD DECK.

Builder's name and yard number ARDROSSAN DOCKYARD LTD N° 340.

Names of sister vessels

Owners ANGLO-SAXON PET. CO LTD

Address LONDON

Fee £ _____ Received by me _____

