

CLIPPING FOR EQUIVALENT DEPTH.  
 Lloyd's Register of Shipping.  
 SURVEYS FOR FREEBOARD.  
 (COMPUTATION FOR STEAMER, SAILING SHIP, AND ANKER.)

	Mean Covered Length (S) metres	Equivalent Enclosed Length (S) metres	Height	Height Correction	Effective Length (E) metres
Deep enclosed ...	22.31	22.31	2180 mm.		22.31
overhang ...					
R.Q.D. enclosed ...	26.23	26.23	1230 mm.	1215/1226	<del>26.23</del>
overhang ...					25.99
Bridge enclosed ...					
overhang aft ...					
overhang forward ...					
Flow enclosed ...	5.55	5.55	2831		5.55
overhang ...	1.22	1.22			1.22
Trunk aft ...					
forward ...					
Tonnage opening aft ...					
forward ...					
Total ...	55.31	55.31			55.31

  

Standard Height of Superstructure	1.835 M.
" " R.Q.D.	1.226 M.
Deduction for complete superstructure	792 mm
Percentage covered S =	72.15
" " L =	72.15
" " E =	72.15
Percentage from Table, Line A.	65.64%
(corrected for absence of forecastle (if required))	
Percentage from Table, Line B.	
(corrected for absence of forecastle (if required))	
Interpolation for bridge less than 2L (if required)	
Deduction =	792 x 65.64 = 520 mm.

Tropical Fresh Water Line	above Centre of Disc	...	...	Tropical Fresh Water Freeboard
Fresh Water Line	"	"	...	Fresh Water
Tropical Line	"	"	...	Tropical
Winter Line	below	"	...	Winter

Lloyd's Register  
Foundation

010219-010228-0110