

Dimensions of Ship per Register, Length 144.4 breadth 58.25 depth 31.35 Moulded depth, ft. 34 ins. 0 To Bridge Dk. Round of Dk. Beam.

FRAMING.

Inches in Ship. Inches in Ship. Inches in Ship. Inches per Rule Or as Approved. Inches per Rule Inches per Rule

PILLARS.

Inches. Size in Ship. Incl. Spacing in Ship.

Sm. 6.14.

1

Tusima Maru

Sent to Chief Surveyors 4.11.14

Received from Chief Surveyors

VESSEL'S NAME

Steel Tanker Tusima Maru

Report

Sub.

No. 16761

For the CHIEF SHIP SURVEYOR and CHIEF ENGINEER SURVEYOR.

(In cases which have to be submitted to the Classing Committee "the endorsement to contain a succinct summary of any repairs that have been required and to show the cause or causes of such repairs, and also to bring out clearly any exceptional features in connection with the case so that the Classing Committee may have all the salient points presented in the endorsement."—Extract from Sub-Committee's Report, 24/5/92.)

Nature of Survey

When due

100A-1. (steel)

2 Dks (steel)

WTB = Cee & B a 135' u 24' 18' 12556 DTA 39' 11466 a PT 636

FK 7BN. Cen. Lgd are P. 35' B 138' F 39'

Sub. 14.11.14

14.11.14



© 2021

Lloyd's Register

010283-010288-0066

Way or Long Bridge	36	48	82	48
Spacing	36	48	36	48
BEAMS, Second Deck, Single Angle, Bulb Angle, Plate, Tee Bulb, or Channel	9 1/2	13 1/2	148	9 1/2 3 1/2 48
Spacing	36		36	

breadth & thickness
Angles on ditto, No.
Tie Plates outside Hatchways
Deck Material & thickness
Poop Deck Stringer Plate, breadth & thickness

held
7 3 1/2
3 1/2 3 1/2
66
5 5
incl a
49
4 4
incl a

37