

doors, ventilators, coamings and covers, air and sounding pipes (striking)

VESSEL'S NAME REPORT No.

THICKNESSES OF PLATING ascertained by drilling, and comparison of same with the original thicknesses.

The thicknesses are in hundredths of an inch.

STRAKE.	AMIDSHIP.					FORWARD.					AFT.				REMARKS.		
	Original Thickness	Thickness by drilling.		Diminution if any.		Original Thickness	Thickness by drilling.		Diminution if any.		Original Thickness	Thickness by drilling.		Diminution if any.			
		Port.	Std.	Port.	Std.		Port.	Std.	Port.	Std.		Port.	Std.	Port.		Std.	
GESHEER AKE																	
below																	
R STRAKE	L	72	72	71	2	3	50	55	51	-	-	46	47	47	-	-	
ake below	K	69	56	56	13	13	55	49	49	1	1	46	47	47	-	-	
"	J	62	59	59	3	3	46	47	47	-	-	46	43	47	3	-	
"	H	62	48	44	14	18	46	32	39	14	7	46	47	47	-	-	
"	G	62	50	48	14	14	46	51	41	-	5	46	47	48	-	-	
"	F	62	57	59	5	3	46	39	39	7	7	46	43	43	3	3	
"	E	64	59	59	5	5	50	-	-	-	-	50	37	37	13	13	
"	D	64	59	60	5	4	50	57	47	-	3	50	-	-	-	-	
"	C	64	63	61	1	3	50	43	49	7	1	50	63	67	-	-	
"	B	64	59	57	5	7	50	59	59	-	-	50	39	39	-	-	
"	A	64	57	59	7	5	50	55	55	-	-	50	63	67	-	-	
Keel		85					75					75					
"	✓						1										

Drillings at ends to be made in the vicinity of the peak bulkheads.

010294-010299-0119

Lloyd's Register
Foundation

This vessel. is in good and efficient condition and is eligible