

PARTICULARS OF LONGITUDINAL FRAMING.

GENE

FRAMING.		AMIDSHIPS.			ENDS.			AMIDSHIPS.			ENDS.			RIVETING.				
		In Ship.			In Ship.			Per Rule or as approved.			Per Rule or as approved.			Rivets in Longitudinal Frames. Diam. Spacing.	Spacing of Rivets on each side of Transverses and Bulkheads. Inches.	Rivets in Brackets to Bulkheads.		
		Ins.	Ins.	Ins.	Ins.	Ins.	Ins.	Ins.	Ins.	Ins.	Ins.	Ins.	Number.			Diameter. Inches.		
Framing of <i>L, L or E</i> plate and angles																		
Frames in Bridge 'tween Decks ...		✓																
Frames from Uppermost Continuous Deck		No. 1	8	3½	.40	F 7	3½	.40	8	3½	.40	7	8	5¼	✓	8	7	8
Framing from Awning, Shelter or Upper Deck to Margin Plate.		" 2	8	3½	.44	A 8	3½	.40	8	3½	.44	-	-	-	-	-	-	-
		" 3	8	3½	.44	F 7	3½	.40	8	3½	.44	-	-	-	-	-	-	-
		" 4	10	3½	.44	A 8	3½	.40	8	3½	.44	-	-	-	-	-	-	-
		" 5	10	3½	.44	F 9	3½	.44	9½	3½	.46	-	-	4¾	-	10	-	-
		" 6	10	3½	.48	A 10	3½	.44	10	3½	.44	-	-	-	-	-	-	-
		" 7	10	3½	.52	F 9	3½	.44	10	3½	.48	-	-	-	-	-	-	-
		" 8	10	3½	.56	A 10	3½	.44	10	3½	.52	-	-	-	-	-	-	-
		" 9	10	3½	.56	F 10	3½	.44	10	3½	.56	-	-	-	-	-	-	-
		" 10	12	3½	.50	A 11	3½	.48	11	3½	.52	-	-	5¼	3½	-	-	-
		" 11	12	3½	.50	F 10	3½	.48	12	3½	.50	-	-	-	-	-	-	-
		" 12	14	3½	.40	A 12	3½	.40	14	3½	.40	-	-	-	-	-	-	-
		" 13	15	3½	.40	F 13	3½	.40	15	3½	.40	-	-	-	-	-	-	-
		" 14	16	3½	.40	A 14	3½	.40	16	3½	.40	-	-	-	-	-	-	-
		15 to 23 to 26 except 18 Wash Old		"	"	"	F 19	3½	.40	19	3½	.40	-	-	-	-	-	-
At Ends		27 to 29½	30 to 32	33 to 35	A 16	3½	.40	36 to 38	39 to 41	42 to 44	-	-	-	-	-	-	-	
Spacing of Longitudinal Frames		Amidships			At Ends													
Double Bottoms		Tank Top Longitudinals			Bottom													
Spacing of Longitudinals		Amidships			At Ends													
Transverses.														Rivets in Lugs to Shell Diam. Spacing.				
In Bridge		Depth and Thickness			15 38			15 38										
'tween Decks		Face Angles			4 3½ 40			4 3½ 40										
		Lugs to Shell			3½ 3½ 38			3½ 3½ 38						2¼ 3¾				
In Awning, Shelter or Upper 'tween Decks.		Depth and Thickness			18 40			18 40										
		Face Angles			4 3½ 44			4 3½ 44										
		Lugs to Shell			6 6 44			6 6 44						1 1/8 4				
In Hold.		Depth and Thickness			42 46			42 46										
		Face Angles			6½ 4½ 66			6½ 4½ 66										
		Lugs to Shell			6½ 6½ 44			6½ 6½ 44						1 1/8 4				
		Brackets			40 46			40 46										
Spacing of Transverse Frames		11-0			11-0			11-0										
Longitudinal Beams of <i>L or E</i>		Bridge Deck			6 3 34			6 3 34			39			Transverse Beams.				
		Upper			7½ 3 40			7½ 3 40			27							
		Second			8½ 3 46			8½ 3 46			27							
		Third																

The particulars of framing in peaks (if ordinary), Floors, Centre Girder, Side Girders and Margin Plate and their angle attachments, etc., to be entered in their respective places provided for on the Report Forms.

NOTE:—This slip to be pasted on the fourth page of the Report, and reference to same to be made under framing, etc., on the first page.

5-12-15. T.

PARTICULARS FOR RECORD in the REGISTER BOOK.—Length of Poop 36.25 ft., R.Q.D. ✓ ft., Bridge 32.66 ft., Forecastle 89.58 (in feet and tenths). When the Poop is joined to the B.D., this should be distinctly stated ✓

No. and Material of Decks (if Iron or Steel) and whether wholly or partially covered with wood, and No. of tiers of Beams (this information is to be given as should appear in the Register Book) 2 Bks (Ht) ✓ web frames, longitudinal framing

Official No. 140287; Signal Letters ✓ State if Machinery is fitted at amidships

How are the surfaces preserved from oxidation? Inside by paint ✓ clear of oil compartments Outside by paint and Portland cement ✓

PARTICULARS OF WATER BALLAST.—State whether the Double bottom is constructed on the cellular system or with girders on floors cellular

Where Fitted.	*Length.	Water Capacity.	Where Fitted.	*Length.	Water Capacity.
	Feet.	Tons.		Feet.	Tons.
Double bottom, aft,			Fore peak tank,		70
Double bottom, under Engines and Boilers,	87.25	383	After peak tank,		90
Double bottom, if under Engines only,			Deep tank, aft,	20.25	62
Double bottom, if under Boilers only,			Deep tank, forward,	48	196
Double bottom, forward,			Other tanks, if fitted,		✓
	Total capacity of double bottom	383	(If necessary, furnish further information by sketch.)		✓

* The wells are not to be included in the lengths of the tanks.

State whether the above have been tested as required by the Rules.....yes

Order for Special Survey No. 2860.	DATES OF SURVEYS held while building
Date 21-9-15	(1915) Sep. 20. 21. Oct. 7. 8. 13. 19. 20. 21. 22. 25. 26. 28. 29. Nov. 12. 5. 9. 10. 11. 12. 17. 18. 23. 26. Dec. 1. 2. 6. 8. 9. 10. 16. 17. 21. 23. 27. 28. (1916) Jan. 7. 11. 12. 14. 17. 18. 19. 21. 24. 25. 28. 31. Feb. 1. 2. 4. 7. 8. 9. 14. 15. 17. 21. 25. 29. Mar. 2. 6. 7. 9. 10. 14. 15. 16. 17. 20. 21. 27. 28. 29. 30. 31. Apr. 5. 7. 12. 13. 17. 18. 20. 25. 26. 28. May. 1. 2. 3. 4. 9. 12. 15. 18. 30. 31. June. 1. 9. 23. 26. 27. 29. 30. July. 4. 6. 7. 12. 14. 17. 18. Aug. 8. 10. 11. 22. 28. 30. Sep. 1. 5. 8. 11. 13. 14. 15. 16. 21. 22. 25. 26. 27. 28. 29. Oct. 2. 3. 5. 6. 9. 10. 11. 13. 14. 15. 18. 21. 24. 25. 27. 30. Nov. 1. 3. 6. 7. 10. 14. 16. 17. 20. 21. 23. 24. 27. 28. 29. Dec. 1. 2. 5. 8. 12. 15. 16. 19. 20. 21. 23. 24. 26. 29. 30. Apr. 2. 3. Total No. of Visits 215.
No. 702 in builder's yard.	

Surveyor's Signature

Lloyd's Register Foundation