

Form No. 1B. WEB FRAMES. FORGINGS or CASTINGS. BULKHEADS. COLLISION PARTITION LONGITUDINAL. PLATING. STRAKES. AWNING or Shelter Deck Stringer Plate. Upper Deck Stringer Plate. FRAMES extend in one length from. REVERSED FRAMES on floors and frames extend from. MASTS, SPARS, &c. LOWER MASTS. Bowsprit. Topmasts, and Remainder of Spars. Rigging, Material and Size, Shrouds Fore. Sails, and the following spare sails.

EQUIPMENT No. 33190 LETTER Y. ANCHORS. CHAIN CABLES. HAWSERS AND WARPS. Boats 2 Life Boats. Pumps, Number DOWNTON & 1 SMALL P. F. R. Windlass is By Builders. Engine Room Skylights. Coal Bunker Openings. Number of Scuppers, and numbers and dimensions of Freeing Ports, &c. Ceiling in Holds, thickness and material. Cargo Hatchways. State size No. 1 Hatch. Number of Web Plates, Shifting Beams and Fore and Afters to each Hatch. Bulwarks, height above deck. The foregoing is a correct description. Builder's Signature. Correspondence. Workmanship. Is the riveted work properly closed? Are the liners between the frames and plates solid single pieces? to plate, &c., conform well to each other? Are the butts of plating, Stringers, &c., properly shifted and strapped? Have all the upper and weather decks been tested as required by the Rules (Sec. 26, par. 20)? Have all the gutterways been tested as required by the Rules (Sec. 26, par. 20)? General Remarks (State quality of workmanship, &c.). Committee's Minute. Character assigned.

GENERAL REMARKS—(continued).

PARTICULARS FOR RECORD in the REGISTER BOOK.—Length of Poop ☒ ft., R.Q.D. ☒ ft., Bridge ☒ ft., Forecastle ☒ ft.
(in feet and tenths). When the Poop is joined to the B.D., this should be distinctly stated ☒

No. and Material of Decks (if Iron or Steel) and whether wholly or partially covered with wood, and No. of tiers of Beams (this information is to be given as should appear in the Register Book) 2 Dks (Steel) and Awning dk (Steel)
Official No. 26163 ; Signal Letters R. S. J. D. State if Machinery is fitted aft No
How are the surfaces preserved from oxidation? Inside Cement + paint Outside Paint

PARTICULARS OF WATER BALLAST.—State whether the Double bottom is constructed on the cellular system or with girders on floors Cellular D. B.

Where Fitted.	*Length. Feet.	Water Capacity. Tons.	Where Fitted.	*Length. Feet.	Water Capacity. Tons.
Double bottom, aft,	116.9	342	Fore peak tank,		126.0
Double bottom, under Engines and Boilers,	44.6	182	After peak tank,		93.0
Double bottom, if under Engines only,			Deep tank, aft,		
Double bottom, if under Boilers only,			Deep tank, forward,		
Double bottom, forward,	172.1	594	Other tanks, if fitted,		
	Total capacity of double bottom	1118.	(If necessary, furnish further information by sketch.)		

* The wells are not to be included in the lengths of the tanks.

State whether the above have been tested as required by the Rules Yes

Order for Special Survey No.

Date

No. 466 in builder's yard.

DATES of Surveys held while building

1919. June 26, 30; July 11, 16, 21, 28, 29, 31; Aug 4, 5, 7, 12, 15, 16, 18, 19, 20, 21, 23, 25, 26, 27, 29;
Sept 2, 3, 6, 8, 10, 11, 18; Oct 1, 3, 6, 7, 14.—

Surveyor's Signature

Alexander Watt

Total No. of Visits 35.